

DELAUDER COMMUNICATIONS, INC.

5568 General Washington Drive, Suite A-218

Alexandria, Virginia 22312

(703) 658-5390

ENGINEERING REPORT

Cooperative TV Association of Southern Minnesota
St. James, MN (Channel 41- Minor Modification—Displacement for K54AC)

EXHIBIT 7 - ENVIRONMENTAL STATEMENT

This proposal does not involve a site location specified under Section 1.1307(a) through (a)(8) of the FCC Rules.

Assuming: (a) a maximum ERP of 1.32 kilowatts and circular polarization (for approximately 3 kW total with aural carrier); (b) a relative field of less than 0.4 in the critical downward angles; and (c) a distance of at least 170 meters from the lowest antenna element to 2 meters above ground level, the maximum power density is calculated as follows:

$$S = 33.4 (F)(F)(ERP) / [(R)(R)]$$

Where, S equals power density in uW/cm²
F equals the relative field factor
ERP equals the effective radiate power in watts
R equals the distance in meters

$$= 33.4 (0.4)(0.4)(3,000) / [(170)(170)]$$

$$= 0.6 \text{ uW/cm}^2$$

0.6 uW/cm² represents less than 1% of the uncontrolled power density limit (423.3 uW/cm²). The electromagnetic radiation from this proposed operation will not produce a value in excess of the radiation standard. The electromagnetic radiation from the proposed operation will not combine with other facilities on or near the structure to produce a significant change in value.

If this is a structure that may support various other operations, the applicant will cooperate with the other operators in establishing a plan for work done on the structure in close proximity to the existing antenna.

DELAWDER COMMUNICATIONS, INC.
5568 General Washington Drive, Suite A-218
Alexandria, Virginia 22312
(703) 658-5390

ENGINEERING REPORT

Community Service Television Company
San Diego, CA (Amendment to BMP TTL-19990903AAS for Ch. 36(o))