

Non-Interference Compliance

Regarding Facility id 146178

Channel 237

Description of Exhibit 13 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 5 of this exhibit is an aerial photo of the vicinity surrounding the proposed translator's tower site.

Note: There are no buildings or major roads within the zone of predicted interference so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
1651182	BLH20140924ADB	KWHF	62.7	62.7
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				62.7

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **62.7 dBμ**, this makes the proposed translator's worst-case interfering contour **102.7 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **398.2 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population").

Note: There are no buildings or major roads within the zone of predicted interference so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer:	SCA
Antenna Model:	FMV-1
CORAGL:	9 m
Maximum ERP:	0.06 kW
Interfering Contour:	102.7 dBμ
Max Int. Contour Distance:	398.2 m

Adjacent Channel Study
For Station K290BS, Facility_id: 146178

Co-channel through third adjacent:

App_id	Fac_id	File_Number	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Char	Adj	Dist	Overlap
1651182	51923	BLH-20140924ADB	KWHF	EAST ARKANSAS BROADCASTING	C2	HARRISBURG	AR	LIC	40	226	240	3	45.4	0.358
180965	37792	BLFT-19930121TC	K234AC	BOARD OF TRUSTEES OF THE UNIVERSITY OF ARKANSAS	D	BATESVILLE	AR	LIC	0.25	156	234	3	32.7	0
1421110	52903	BLED-20110314AAF	KLJK	EDUCATIONAL MEDIA FOUNDATION	A	WEINER	AR	LIC	6	153	234	3	46.3	0
1493156	146186	BLFT-20120509AFJ	K237FI	EAST ARKANSAS BROADCASTING	D	JONESBORO	AR	LIC	0.25	243	237	0	50	0
1145537	164173	BLH-20060822AIK	KVHU	GEORGE S. FLINN, JR.	C3	JUDSONIA	AR	LIC	14	193	237	0	59.1	0
1580835	138337	BLFT-20131021AHP	K238BN	EAST ARKANSAS BROADCASTING	D	WYNNE	AR	LIC	0.25	189	238	1	78.6	0
120056	51107	BLH-19881108KC	KAMS	E-COMMUNICATIONS, LLC	C1	MAMMOTH SPRING	AR	LIC	100	418	236	1	91.2	0
63171	61363	BLH-19831117BH	KSSN	CC LICENSES, LLC	C	LITTLE ROCK	AR	LIC	92	632	239	2	150.7	0



