



## Exhibit 12-B (cont.)

WVBE	610 kHz	App	Day	Facil. ID	41111	20060531
VA	Roanoke			10.000 kW	4 Towers	0 Augmentations
N. Lat:	37 18 11	W. Lon:	80 02 33			24 Measured Cond

Bearing	Radiation	Distance to Contours		
		5.000	2.000	0.500
101.0M*	1745.6	44.68	61.13	111.39
105.0+	1748.7	44.72	61.18	111.47
110.0+	1732.9	44.54	60.94	111.05
111.0-	1727.3	33.12	50.28	110.89
115.0-	1696.6	32.85	49.87	110.05
120.0M*	1641.1	32.35	49.12	108.52
123.0+	1599.5	31.97	48.55	107.34
125.0+	1568.5	31.68	48.13	106.44
130.0-	1481.0	30.85	46.89	87.45
133.0M*	1422.4	30.28	46.04	85.90
135.0+	1381.1	29.87	45.43	84.78
140.0-	1271.4	28.75	43.75	81.73
143.0M*	1202.0	28.01	42.65	79.71
145.0+	1154.7	27.49	41.88	78.29
150.0+	1033.8	26.10	39.82	74.52
153.0-	960.4	25.21	38.51	72.10
155.0-	911.5	24.59	37.60	70.43
160.0M*	790.7	22.99	35.23	66.07
165.0+	674.7	21.30	32.76	61.52
170.0M*	567.8	19.59	27.00	44.75
175.0+	476.5	17.96	27.00	41.20
180.0+	410.4	16.66	26.01	38.38
185.0-	380.5	16.03	20.00	37.03
190.0M*	391.8	16.28	20.00	37.55
195.0+	436.7	17.19	20.34	39.53
200.0-	500.5	16.65	24.99	42.17
205.0M*	571.0	17.79	24.99	44.87
210.0+	639.3	18.81	24.99	47.32
215.0+	700.0	19.67	25.56	49.38
220.0-	749.6	16.91	21.72	43.11
225.0M*	786.1	17.31	22.24	44.12
228.0+	801.4	17.48	22.46	44.53
230.0+	808.8	17.56	22.57	44.73
235.0-	818.5	33.77	51.18	80.43
238.0M*	818.5	33.77	51.18	80.43
240.0+	816.5	33.73	51.13	80.34
245.0+	805.2	33.51	50.82	79.86
248.0+	795.2	33.31	50.54	79.42
250.0-	787.6	33.16	50.33	91.12
255.0-	767.0	32.74	49.74	90.10
258.0-	754.6	32.48	49.39	89.49
260.0M*	746.8	32.32	49.17	89.10
265.0-	730.4	25.11	33.97	63.75

Exhibit 12-B (cont.)  
 Tabulation of Distance to WVBE Daytime Coverage Contours

WVBE	610 kHz	App Day	Facil. ID 41111	20060531
VA Roanoke			10.000 kW 4 Towers	0 Augmentations
N. Lat: 37 18 11	W. Lon: 80 02 33			24 Measured Cond

Bearing	Radiation	Distance to Contours		
		5.000	2.000	0.500
-----	-----	-----	-----	-----
268.0M*	723.5	25.00	33.83	63.48
270.0+	720.6	24.95	33.76	63.37
275.0+	719.9	24.94	33.75	63.34
278.0+	724.4	25.01	33.85	63.52
280.0-	729.7	20.00	26.08	47.22
285.0-	750.8	20.00	26.44	47.87
287.2-	763.6	20.00	26.65	48.25
288.0M*	768.8	20.00	26.74	48.41
290.0+	782.9	20.00	26.97	48.83
295.0-	825.1	17.73	27.66	50.06
297.2M*	846.4	17.96	28.00	50.67
298.0+	854.5	18.04	28.13	50.89
300.0+	875.5	18.26	28.46	51.48
305.0-	931.9	18.83	29.32	56.46
307.2-	957.9	19.08	29.71	57.19
310.0M*	991.5	19.41	30.20	58.12
315.0+	1051.3	19.97	31.06	59.72
320.0M*	1108.1	16.64	31.85	60.00
325.0+	1158.8	17.02	32.53	60.00
330.0+	1200.5	17.33	33.08	60.00
335.0-	1230.4	21.00	27.83	54.75
340.0M*	1246.3	21.00	28.00	55.08
345.0+	1246.3	21.00	28.00	55.08
350.0-	1229.1	21.55	30.00	54.72
355.0M*	1193.9	21.25	30.00	53.96
355.5+	1189.4	21.21	30.00	53.87