

REFERENCE	CH#	212C1 - 90.3	MHZ, Pwr= 26.5	kW, HAAT= 319.5	M, COR= 1842	M	DISPLAY DATES
42 51 46.0 N.				Average Protected F(50-50)= 60.51	km		DATA 08-14-08
112 31 03.0 W.				Standard Directional			SEARCH 09-10-08

REFERENCE
42 51 46.0 N.
112 31 03.0 W.

CH# 212C1 - 90.3 MHz, Pwr= 26.5 kW, HAAT= 319.5 M, COR= 1842 M
Average Protected F(50-50)= 60.51 km
Standard Directional

```

DISPLAY DATES
DATA      08-14-08
SEARCH    09-10-08

```

CH CITY	CALL	TYPE	ANT STATE	AZI --	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap	*OUT* in km)
212C3	KZJB	LIC	_VX	0.0	0.00	42 51 46.0	0.910	103.7	39.0	-154.45*	-164.24*
Pocatello		ID		0.0	BLED20050727ACZ	112 31 03.0	314	1842	Csn International		
06-2C	KPVI	LI	_HN	65.2	15.46	42 55 15.0	100.000	19.3	127.4	194.5R	-131.3M
Pocatello		ID		245.3	BLCT2335	112 20 44.0	466	2078	Oregon Trail Broadcasting		
212C2	KUWJ	LIC	_CN	64.5	158.19	43 27 40.0	3.000	124.3	50.2	3.75	24.12
Jackson		WY		245.7	BLED19921207KC	110 45 09.0	337	2489	University Of wyoming		
213A	KAIO	LIC	_VX	33.9	91.44	43 32 37.0	0.500	37.7	25.0	16.98	10.07
Idaho Falls		ID		214.3	BLED20060927AMH	111 53 07.0	161	1708	Educational Media Foundati		
214C	KCIR	LIC	_CY	237.0	106.75	42 20 07.0	20.000	8.5	84.3	32.38	14.72
Twin Falls		ID		56.2	BMLED19920811KA	113 36 17.0	768	2547	Faith Communications Corp		

Terrain database is NGDC 30 SEC Distance + R = 73.215 or FCC Spacings in KM, Distance + M = Margin in KM
Contour distances are on direct line to and from reference station. Reference zone = 2. With 3rd Adj Channels.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
"*"affixed to 'IN' or 'OUT' values = site inside protected contour.
"<" = Contour Overlap