

EXHIBIT 13

Waiver Request of Section 74.1204

Shasta, CA K225AJ 10 Watts ERP

Minor Channel Change 249

Calvary Chapel of Twin Falls, Inc.

September 2015

The proposed site is contained entirely inside the service contour of second-adjacent FM Stations KNCQ Redding, CA and KVIP-FM Redding

KNCQ

The proposed site is contained entirely inside the service contour of third-adjacent FM Station KNCQ.LIC, 247C, 28kW, Redding, CA and it's APP to change City of License to Weaverville – same contour as its Licensed operation. The level of least arriving protected F(50,50) signal at the proposed transmitter site is 0.00-dBu because KNCQ is collocated with K225AJ and its proposed frequency change. The interfering contour is less than 1 meter from the center of radiation, which remains on the tower and does not touch the ground. This tower is located at a remote site on Shasta Bally and the only structures are other towers and enclosures for equipment. This interference contour does not touch the ground. Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second-adjacent FM Station KNCQ Redding.

KVIP-FM

The proposed site is contained entirely inside the service contour of third-adjacent FM Station KVIP-FM, 251C, 30kW, Redding, CA. The level of least arriving protected F(50,50) signal at the proposed transmitter site is 71.5dBu and using the U/D method for calculating proposed interference, the interfering contour is 111.5-dBu (free-space contour method employed). The interfering signal would, in the worst case at the maximum radial, extend 60 meters, or 197 feet, from the base of the tower. Attached is a portion of the USGS Shasta Bally(CA) Quadrangle, with an interference contour marked in yellow which covers an area of 500 feet from the base of the tower. This tower is located on Shasta Bally, in an unpopulated area. The boxes located within the interference contour house equipment for the towers located on the mountain. There are no businesses, residences or major roadways located within this interfering contour, Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second-adjacent FM Station KVIP-FM.

<div> <div>REFERENCE</div> <div>40 36 10.0 N.</div> <div>122 38 58.0 W.</div> </div> <div> <div>CH# 249D - 97.7 MHz, Pwr= 0.01 kW, HAAT= 1054.6 M, COR= 1880 M</div> <div>Average Protected F(50-50)= 17.27 km</div> <div>Omni-directional</div> </div> <div> <div>Redding CA K225AJ Minor Change</div> <div>Calvary Chapel Of Twin Falls, Inc.</div> <div>DISPLAY DATES</div> <div>DATA 09-29-15</div> <div>SEARCH 09-29-15</div> </div>											
CH CITY	CALL	TYPE ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*	
247C Weaverville	KNCQ	RSV-A ____ CA	220.1 40.1	2.22	40 35 15.0 122 39 59.0	100.000 600	15.8 1433	97.8 Results	-28.6*	-95.8*	Radio Of Redding L
247C Weaverville	KNCQ	APP _CX CA	0.0 0.0	0.00 BPH20140828ACE	40 36 10.0 122 38 58.0	28.000 1088	10.5 1913	95.1 Results	-28.7*	-95.3*	Radio Of Redding L
247C Redding	KNCQ	LIC _CN CA	0.0 0.0	0.00 BLH19851104KF	40 36 10.0 122 38 58.0	28.000 1088	10.5 1913	95.1 Results	-28.7*	-95.3*	Radio Of Redding L
249C1 Ferndale	AL6818	RSV-A ____ CA	265.8 84.8	139.04 RMIn v-11	40 30 03.0 124 17 08.0	100.000 299	171.3 488	71.9	-48.0*	9.4	
251C Redding	KVIP-FM	LIC _CN CA	61.5 241.6	12.20 BMLED19971006KC	40 39 18.0 122 31 21.0	30.000 521	2.4 1045	23.6 Paci fic	-9.0*	-11.7*	Cascade Communi cat
249B1 Gridley	KHHZ	LIC _C_ CA	136.5 317.4	167.10 BLH20080821ACX	39 30 18.0 121 18 35.0	1.500 389	122.0 1003	56.1 Deer Creek Broadcasting, L	27.1	34.0	
249L1 Eureka	KKDS-LP	LIC ____ CA	280.7 99.8	128.49 BLL20061114ABG	40 48 29.0 124 08 45.0	0.100	12		94.7 Dell ' Arte, Inc.	67.2	

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
 Contour distances are on direct line to and from reference station. Reference zone= , Co to 3rd adjacent.
 All separation margins (if shown) include rounding.
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
 "*"affixed to 'IN' or 'OUT' values = site inside restricted contour.

