

MINOR CHANGE APPLICATION
STYLES MEDIA GROUP, LLC
WJRL-FM RADIO STATION
CH 280C3 - 103.9 MHZ - 25.0 KW
FORT RUCKER, ALABAMA
February 2005

EXHIBIT A

§73.215 Compliance

The WJRL-FM antenna location is shortspaced to the authorized facilities of WAAO-FM, Channel 279A, Andalusia, Alabama, as can be seen on Exhibit A1. Styles proposes to use the provisions of §73.215 of the Commission's rules to address this shortspaced situation. This shortage complies with §73.215(e) of the Commission's rules. Exhibit A2 specifically demonstrates that there will be no prohibited overlap between the proposed WJRL-FM and authorized WAAO-FM. The contours of WAAO-FM are based on 6.0 kilowatts effective radiated power at a height above average terrain (HAAT) of 100.0 meters.²

Attached as Exhibits A3 and A4 are the tabulated distances to the protected and interfering contours, along the pertinent arcs, of the proposed WJRL-FM and authorized WAAO-FM. Further, attached as exhibit A5 are the tabulated and protected contours of the proposed facility, in ten degree increments. Again, there is no prohibited overlap between the facilities.

2) WAAO-FM is authorized with 3.0 kilowatts at 100 meters HAAT. The power of the station was increased to 6.0 kilowatts for the §73.215 analysis.

MINOR CHANGE APPLICATION
STYLES MEDIA GROUP, LLC
WJRL-FM RADIO STATION
CH 280C3 - 103.9 MHZ - 25.0 KW
FORT RUCKER, ALABAMA
February 2005

EXHIBIT A1

Clearance study for WJRL-FM Fort Rucker, Alabama
Using present/proposed site as reference

REFERENCE	CLASS = C3	DISPLAY DATES
31 26 25 N	Current	DATA 02-09-05
85 33 49 W	Spacings	SEARCH 02-09-05
----- Channel 280 - 103.9 MHz -----		

Call	Channel N. Lat.	Location W. Lng.	Ant	Dist Power	Azi HAAT	FCC	Margin
WJRLFM	LIC-N 280C3	Ozark		AL 0.00	0.0	153.0	-153.00
	31 26 25	85 33 49	NCN	25.000 kW	89 M		
	Styles Media Group, LLC			BLH-19920701KD			
AL280	RSV 280C3	Fort Rucker		AL 2.33	83.9	153.0	-150.67
	31 26 33	85 32 21		25.000 kW	100 M		
	> Reserved for WJRL-FM per MB Docket #04-146 RM10871						
* WAAOFM	LIC 279A	Andalusia		AL 86.65	262.9	89.0	-2.35
	31 20 27	86 28 02	CN	3.000 kW	100 M		
	Companion Broadcasting Ser.			BMLH-19900212KF			
WAAOFM	CP 279C3	Andalusia		AL 98.87	264.7	99.0	-0.13
	31 21 14	86 35 54	CX	25.000 kW	74 M		
	Companion Broadcasting Ser.			BPH-20020531AAU			
WHLW	LIC-N 282C1	Luverne		AL 82.02	316.5	76.0	6.02
	31 58 28	86 09 44	NCN	13.500 kW	558 M		
	Capstar TX Limited Partner			BLH-19970731KB			
WGLF	LIC 281C	Tallahassee		FL 184.18	126.2	176.0	8.18
	30 27 09	84 00 50	CY	100.000 kW	425 M		
	Cumulus Licensing LLC			BMLH-19920818KH			
WMXS	LIC 277C	Montgomery		AL 122.39	331.0	96.0	26.39
	32 24 11	86 11 48	CN	100.000 kW	334 M		
	Cumulus Licensing LLC			BLH-19890419KB			
930701	VAC 279A	Cusseta		GA 121.49	37.5	89.0	32.49
	32 18 18	84 46 30	N	6.000 kW	100 M		
930701	APP 279A	Cusseta		GA 122.73	37.8	89.0	33.73
	32 18 39	84 45 45	CN	6.000 kW	100 M		
	Signature Broadcasting Ltd.			BPH-19930701ME			
WBBKFM	LIC-N 226C2	Blakely		GA 50.87	107.9	17.0	33.87
	31 17 55	85 03 18	NCX	45.000 kW	100 M		
	Styles Media Group, LLC			BLH-20040914AAU			
WYOK	LIC 281C	Atmore		AL 218.43	246.0	176.0	42.43
	30 37 35	87 38 50	CN	100.000 kW	474 M		
	Cumulus Licensing LLC			BMLH-19880321KA			

* Note: This shortage is addressed under §73.215 of the rules. See Exhibit A.

MINOR CHANGE APPLICATION
STYLES MEDIA GROUP, LLC
WJRL-FM RADIO STATION
CH 280C3 - 103.9 MHZ - 25.0 KW
FORT RUCKER, ALABAMA
February 2005

EXHIBIT A3

WJRL-FM - Proposed
Channel = 280C3
Max ERP = 25 kW
RCAMSL = 179 M
N. Lat = 31 26 25
W. Lng = 85 33 49

WAAO-FM - BMLH-19900212KF
Channel = 279A
Max ERP = 6 kW
RCAMSL = 186 M
N. Lat = 31 20 27
W. Lng = 86 28 02

Protected
60 dBu

Interfering
54 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
245.0	025.0000	0086.5	036.7	094.7	006.0000	0091.9	053.0	49.9
246.0	025.0000	0086.5	036.7	094.1	006.0000	0090.9	052.7	49.9
247.0	025.0000	0086.4	036.7	093.5	006.0000	0090.5	052.4	50.0
248.0	025.0000	0086.4	036.6	092.8	006.0000	0090.5	052.1	50.1
249.0	025.0000	0086.2	036.6	092.2	006.0000	0090.4	051.9	50.2
250.0	025.0000	0086.1	036.6	091.5	006.0000	0090.4	051.6	50.2
251.0	025.0000	0086.1	036.6	090.9	006.0000	0090.2	051.4	50.3
252.0	025.0000	0086.1	036.6	090.2	006.0000	0090.0	051.2	50.4
253.0	025.0000	0086.5	036.7	089.5	006.0000	0090.0	050.9	50.5
254.0	025.0000	0087.1	036.8	088.9	006.0000	0089.1	050.6	50.5
255.0	025.0000	0088.0	037.0	088.2	006.0000	0087.6	050.3	50.5
256.0	025.0000	0088.9	037.1	087.5	006.0000	0087.6	050.0	50.6
257.0	025.0000	0089.7	037.3	086.8	006.0000	0086.2	049.7	50.6
258.0	025.0000	0090.3	037.4	086.1	006.0000	0084.9	049.5	50.6
259.0	025.0000	0090.6	037.4	085.3	006.0000	0084.4	049.4	50.6
260.0	025.0000	0090.6	037.4	084.6	006.0000	0084.4	049.3	50.6
261.0	025.0000	0090.0	037.3	083.8	006.0000	0084.3	049.4	50.5
262.0	025.0000	0089.2	037.2	083.0	006.0000	0084.0	049.5	50.5
263.0	025.0000	0088.7	037.1	082.3	006.0000	0083.4	049.6	50.4
264.0	025.0000	0088.5	037.0	081.5	006.0000	0083.4	049.6	50.4
265.0	025.0000	0088.2	037.0	080.8	006.0000	0082.9	049.7	50.3
266.0	025.0000	0088.0	037.0	080.1	006.0000	0082.1	049.8	50.2
267.0	025.0000	0088.1	037.0	079.3	006.0000	0081.3	049.9	50.1
268.0	025.0000	0087.9	036.9	078.6	006.0000	0081.3	050.0	50.1
269.0	025.0000	0087.8	036.9	077.9	006.0000	0080.6	050.1	50.0
270.0	025.0000	0087.8	036.9	077.1	006.0000	0079.7	050.3	49.8
271.0	025.0000	0087.7	036.9	076.4	006.0000	0079.1	050.4	49.7
272.0	025.0000	0087.2	036.8	075.7	006.0000	0079.1	050.7	49.6
273.0	025.0000	0086.7	036.7	075.1	006.0000	0078.8	050.9	49.5
274.0	025.0000	0086.4	036.7	074.4	006.0000	0078.6	051.2	49.4
275.0	025.0000	0086.6	036.7	073.7	006.0000	0078.6	051.4	49.3
276.0	025.0000	0086.4	036.7	073.1	006.0000	0078.7	051.7	49.3
277.0	025.0000	0086.1	036.6	072.4	006.0000	0078.7	052.0	49.1
278.0	025.0000	0085.4	036.5	071.9	006.0000	0078.7	052.4	49.0
279.0	025.0000	0084.6	036.3	071.3	006.0000	0078.7	052.8	48.9
280.0	025.0000	0084.2	036.2	070.8	006.0000	0078.7	053.1	48.7
281.0	025.0000	0083.8	036.2	070.2	006.0000	0078.5	053.5	48.6
282.0	025.0000	0083.2	036.0	069.7	006.0000	0078.5	053.9	48.4
283.0	025.0000	0082.5	035.9	069.2	006.0000	0078.1	054.4	48.2
284.0	025.0000	0081.6	035.7	068.8	006.0000	0078.1	054.9	48.1
285.0	025.0000	0080.7	035.5	068.3	006.0000	0077.5	055.4	47.8

MINOR CHANGE APPLICATION
STYLES MEDIA GROUP, LLC
WJRL-FM RADIO STATION
CH 280C3 - 103.9 MHZ - 25.0 KW
FORT RUCKER, ALABAMA
February 2005

EXHIBIT A4

WAAO-FM - BMLH-19900212KF
Channel = 279A
Max ERP = 6 kW
RCAMSL = 186 M
N. Lat = 31 20 27
W. Lng = 86 28 02

WJRL-FM - Proposed
Channel = 280C3
Max ERP = 25 kW
RCAMSL = 179 M
N. Lat = 31 26 25
W. Lng = 85 33 49

Protected
60 dBu

Interfering
54 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
070.0	006.0000	0078.5	025.3	268.0	025.0000	0087.9	062.2	52.5
071.0	006.0000	0078.7	025.3	267.6	025.0000	0087.9	062.1	52.6
072.0	006.0000	0078.7	025.3	267.2	025.0000	0088.1	062.0	52.6
073.0	006.0000	0078.7	025.3	266.8	025.0000	0088.1	061.8	52.6
074.0	006.0000	0078.6	025.3	266.4	025.0000	0088.0	061.8	52.7
075.0	006.0000	0078.8	025.3	266.0	025.0000	0088.0	061.6	52.7
076.0	006.0000	0079.1	025.3	265.6	025.0000	0088.0	061.5	52.7
077.0	006.0000	0079.7	025.4	265.2	025.0000	0088.2	061.4	52.8
078.0	006.0000	0080.6	025.6	264.8	025.0000	0088.2	061.2	52.9
079.0	006.0000	0081.3	025.7	264.4	025.0000	0088.5	061.0	52.9
080.0	006.0000	0082.1	025.8	264.0	025.0000	0088.5	060.9	53.0
081.0	006.0000	0082.9	025.9	263.5	025.0000	0088.5	060.7	53.0
082.0	006.0000	0083.4	026.0	263.1	025.0000	0088.7	060.7	53.1
083.0	006.0000	0084.0	026.1	262.7	025.0000	0088.7	060.6	53.1
084.0	006.0000	0084.3	026.1	262.2	025.0000	0089.2	060.6	53.1
085.0	006.0000	0084.4	026.1	261.8	025.0000	0089.2	060.6	53.1
086.0	006.0000	0084.9	026.2	261.4	025.0000	0090.0	060.5	53.2
087.0	006.0000	0086.2	026.4	260.9	025.0000	0090.0	060.4	53.3
088.0	006.0000	0087.6	026.6	260.5	025.0000	0090.6	060.2	53.3
089.0	006.0000	0089.1	026.8	260.0	025.0000	0090.6	060.1	53.4
090.0	006.0000	0090.0	026.9	259.5	025.0000	0090.6	060.0	53.4
091.0	006.0000	0090.2	026.9	259.1	025.0000	0090.6	060.1	53.4
092.0	006.0000	0090.4	027.0	258.6	025.0000	0090.6	060.2	53.4
093.0	006.0000	0090.5	027.0	258.2	025.0000	0090.3	060.3	53.3
094.0	006.0000	0090.9	027.0	257.8	025.0000	0090.3	060.4	53.3
095.0	006.0000	0091.9	027.2	257.3	025.0000	0089.7	060.4	53.2
096.0	006.0000	0092.8	027.3	256.8	025.0000	0089.7	060.4	53.2
097.0	006.0000	0093.5	027.4	256.4	025.0000	0088.9	060.5	53.1
098.0	006.0000	0093.8	027.4	255.9	025.0000	0088.9	060.6	53.1
099.0	006.0000	0093.6	027.4	255.5	025.0000	0088.9	060.8	53.0
100.0	006.0000	0093.4	027.4	255.1	025.0000	0088.0	061.1	52.9
101.0	006.0000	0093.4	027.4	254.7	025.0000	0088.0	061.3	52.8
102.0	006.0000	0093.7	027.4	254.3	025.0000	0087.1	061.5	52.7
103.0	006.0000	0094.2	027.5	253.9	025.0000	0087.1	061.6	52.6
104.0	006.0000	0094.8	027.6	253.4	025.0000	0086.5	061.8	52.6
105.0	006.0000	0095.2	027.6	253.0	025.0000	0086.5	062.0	52.5
106.0	006.0000	0095.6	027.7	252.6	025.0000	0086.5	062.2	52.4
107.0	006.0000	0096.0	027.8	252.2	025.0000	0086.1	062.4	52.3
108.0	006.0000	0096.6	027.8	251.8	025.0000	0086.1	062.7	52.3
109.0	006.0000	0097.2	027.9	251.4	025.0000	0086.1	062.9	52.2
110.0	006.0000	0097.6	028.0	251.0	025.0000	0086.1	063.2	52.1

MINOR CHANGE APPLICATION
STYLES MEDIA GROUP, LLC
WJRL-FM RADIO STATION
CH 280C3 - 103.9 MHZ - 25.0 KW
FORT RUCKER, ALABAMA
February 2005

EXHIBIT A5

Predicted contour:

N. Lat. = 31 26 25 - Tabulated Protected and Interfering Contour Data
W. Lng. = 85 33 49 - WJRL-FM Radio Station - Fort Rucker, Alabama

HAAT and Distance to Contour - FCC Method - 30 Arc Second terrain database								
Azi.	HAAT	ERP kW	dBk	Field	60-F5	40-F1	54-F1	100-F1
000	88.8	25.0000	13.98	1.000	37.11	111.64	57.99	3.83
010	79.2	25.0000	13.98	1.000	35.23	109.91	55.90	3.61
020	83.3	25.0000	13.98	1.000	36.05	110.65	56.81	3.71
030	97.2	25.0000	13.98	1.000	38.62	113.14	59.65	4.00
040	104.1	25.0000	13.98	1.000	39.74	114.35	60.92	4.15
050	85.3	25.0000	13.98	1.000	36.44	111.01	57.25	3.75
060	72.9	25.0000	13.98	1.000	33.90	108.76	54.37	3.47
070	79.9	25.0000	13.98	1.000	35.38	110.05	56.06	3.63
080	77.2	25.0000	13.98	1.000	34.81	109.55	55.42	3.56
090	86.1	25.0000	13.98	1.000	36.60	111.15	57.42	3.77
100	95.9	25.0000	13.98	1.000	38.39	112.90	59.40	3.97
110	91.0	25.0000	13.98	1.000	37.52	112.03	58.44	3.87
120	96.0	25.0000	13.98	1.000	38.40	112.91	59.41	3.98
130	99.0	25.0000	13.98	1.000	38.92	113.46	60.00	4.04
140	95.5	25.0000	13.98	1.000	38.32	112.83	59.32	3.97
150	98.0	25.0000	13.98	1.000	38.74	113.27	59.80	4.02
160	97.9	25.0000	13.98	1.000	38.72	113.25	59.77	4.01
170	96.7	25.0000	13.98	1.000	38.52	113.04	59.55	3.99
180	90.7	25.0000	13.98	1.000	37.45	111.97	58.37	3.87
190	95.9	25.0000	13.98	1.000	38.38	112.90	59.39	3.97
200	99.1	25.0000	13.98	1.000	38.94	113.48	60.01	4.04
210	111.3	25.0000	13.98	1.000	40.83	115.64	62.20	4.29
220	102.3	25.0000	13.98	1.000	39.45	114.04	60.59	4.11
230	91.8	25.0000	13.98	1.000	37.67	112.18	58.61	3.89
240	90.1	25.0000	13.98	1.000	37.34	111.86	58.24	3.85
250	86.1	25.0000	13.98	1.000	36.60	111.15	57.42	3.77
260	90.6	25.0000	13.98	1.000	37.44	111.96	58.35	3.86
270	87.8	25.0000	13.98	1.000	36.91	111.45	57.77	3.80
280	84.2	25.0000	13.98	1.000	36.23	110.81	57.01	3.73
290	81.0	25.0000	13.98	1.000	35.60	110.24	56.31	3.65
300	80.8	25.0000	13.98	1.000	35.56	110.20	56.26	3.65
310	73.6	25.0000	13.98	1.000	34.07	108.91	54.56	3.48
320	71.6	25.0000	13.98	1.000	33.63	108.53	54.04	3.44
330	87.6	25.0000	13.98	1.000	36.89	111.43	57.75	3.80
340	98.3	25.0000	13.98	1.000	38.79	113.32	59.85	4.02
350	94.8	25.0000	13.98	1.000	38.20	112.71	59.19	3.95

AMSL= 179 M