


1:1,000,000

Scale in km



W205BP 205D .05kW 260M AMSL

N. Lat. 41 25 51 W. Lng. 83 31 19

W205BP

CCTF - 06/06

Contour.out

TERRAIN AND CONTOUR DATA

PEMBERVILLE, OH W205BP

CALVARY CHAPEL OF TWIN FALLS, INC.

JUNE 2006

N. Lat. = 41 25 51 W. Lng. = 83 31 19

HAAT and Distance to Contour - FCC Method - 03 Arc Sec.

Azi .	AV EL	HAAT	ERP kW	dBk	Fi el d	60-F5
000	195.2	64.8	0.0500	-13.01	1.000	6.93
030	194.6	65.4	0.0500	-13.01	1.000	6.96
060	194.4	65.6	0.0500	-13.01	1.000	6.96
090	197.4	62.6	0.0500	-13.01	1.000	6.82
120	202.6	57.4	0.0500	-13.01	1.000	6.54
150	205.3	54.7	0.0500	-13.01	1.000	6.39
180	205.2	54.8	0.0500	-13.01	1.000	6.40
210	205.9	54.1	0.0500	-13.01	1.000	6.36
240	207.4	52.6	0.0500	-13.01	1.000	6.27
270	203.6	56.4	0.0500	-13.01	1.000	6.48
300	199.7	60.3	0.0500	-13.01	1.000	6.70
330	196.8	63.2	0.0500	-13.01	1.000	6.85

Ave EI = 200.67 M HAAT= 59.33 M AMSL= 260

Contour.out

TERRAIN AND CONTOUR DATA
CANADIAN COMPLIANCE

PEMBERVILLE, OH W205BP

CALVARY CHAPEL OF TWIN FALLS, INC.

JUNE 2006

N. Lat. = 41 25 51 W. Lng. = 83 31 19

HAAT and Distance to Contour - FCC Method - 03 Arc Sec.

Azi.	AV EL	HAAT	ERP kW	dBk	Field	34-F1
000	195.2	64.8	0.0500	-13.01	1.000	33.25
030	194.6	65.4	0.0500	-13.01	1.000	33.43
060	194.4	65.6	0.0500	-13.01	1.000	33.46
090	197.4	62.6	0.0500	-13.01	1.000	32.64
120	202.6	57.4	0.0500	-13.01	1.000	31.12
150	205.3	54.7	0.0500	-13.01	1.000	30.33
180	205.2	54.8	0.0500	-13.01	1.000	30.36
210	205.9	54.1	0.0500	-13.01	1.000	30.15
240	207.4	52.6	0.0500	-13.01	1.000	29.68
270	203.6	56.4	0.0500	-13.01	1.000	30.82
300	199.7	60.3	0.0500	-13.01	1.000	31.99
330	196.8	63.2	0.0500	-13.01	1.000	32.80

Ave EI = 200.67 M HAAT= 59.33 M AMSL= 260