

Exhibit 15-P-3 Tabulation of Distance to WRJZ Daytime Allocation Contours

WRJZ 620 kHz Lic DANU BL791210AE 20060523
 TN KNOXVILLE 5.000 kW 1 Tower 0 Augmentations
 N. Lat: 35 59 24 W. Lon: 83 50 15 15 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.
 All distances are in kilometers (US metric curves)
 All radiations are in mV/m at one kilometer

'M*' bearing is supplemented by measurements.
 '+-' 10 deg. variance from measured bearing.

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0-	651.3	84.09	112.53
3.0M*	651.3	84.09	112.53
4.0+	651.3	84.09	112.53
5.0+	651.3	84.09	112.53
10.0-	651.3	84.09	112.53
13.0-	651.3	84.09	112.53
14.0M*	651.3	84.09	112.53
15.0+	651.3	84.09	112.53
20.0+	651.3	84.09	112.53
24.0+	651.3	84.09	112.53
25.0	651.3	84.09	112.53
30.0	651.3	84.09	113.02
33.0-	651.3	87.00	118.41
35.0-	651.3	87.00	120.12
40.0-	651.3	88.02	124.81
43.0M*	651.3	88.86	126.43
45.0+	651.3	89.37	126.93
50.0+	651.3	90.37	127.94
53.0-	651.3	97.94	135.50
55.0-	651.3	98.22	135.78
60.0M*	651.3	98.75	136.32
63.0+	651.3	98.96	136.52
65.0+	651.3	99.00	136.57
70.0-	651.3	93.56	131.13
73.0M*	651.3	93.42	130.99
75.0+	651.3	93.28	130.85
80.0+	651.3	92.76	124.90
83.0+	651.3	92.32	121.65
85.0	651.3	86.24	115.80
90.0	651.3	84.09	112.53
93.0-	651.3	86.24	114.68
95.0-	651.3	86.24	114.68
100.0-	651.3	86.24	114.68
103.0M*	651.3	86.24	114.68
105.0+	651.3	86.24	114.68
108.0+	651.3	86.24	114.68b

Exhibit 15-P-3 (cont.)
 Tabulation of Distance to WRJZ Daytime Allocation Contours

WRJZ	620 kHz	Lic	DANU	BL791210AE	20060523
TN	KNOXVILLE			5.000 kW 1 Tower	0 Augmentations
N. Lat:	35 59 24	W. Lon:	83 50 15		15 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
110.0+	651.3	86.24	114.68
113.0-	651.3	84.09	112.53
115.0-	651.3	84.09	112.53
118.0M*	651.3	84.09	112.53
120.0+	651.3	84.09	112.53
121.0+	651.3	84.09	112.53
125.0-	651.3	71.93	100.37
128.0-	651.3	71.93	100.37
130.0-	651.3	71.93	100.37
131.0M*	651.3	71.93	100.37
135.0+	651.3	71.93	100.37
140.0+	651.3	71.93	100.37
141.0+	651.3	71.93	100.37
145.0	651.3	84.09	112.53
150.0	651.3	84.09	112.53
155.0	651.3	84.09	112.53
159.0-	651.3	84.09	112.53
160.0-	651.3	84.09	112.53
165.0-	651.3	84.09	112.53
169.0M*	651.3	84.09	112.53
170.0+	651.3	84.09	112.53
175.0+	651.3	84.09	112.53
176.0+	651.3	84.09	112.53
179.0-	651.3	84.09	112.53
180.0-	651.3	84.09	112.53
185.0-	651.3	84.09	112.53
186.0M*	651.3	84.09	112.53
190.0+	651.3	84.09	112.53
194.0+	651.3	84.09	112.53
195.0+	651.3	84.09	112.53
196.0-	651.3	84.09	112.53
200.0-	651.3	84.09	112.53
204.0M*	651.3	84.09	112.53
205.0+	651.3	84.09	112.53
210.0+	651.3	84.09	112.53
214.0+	651.3	84.09	112.53
215.0	651.3	84.09	112.53
220.0	651.3	84.09	112.53
225.0	651.3	84.09	112.53
230.0	651.3	84.09	112.53
235.0	651.3	84.09	112.53
240.0	651.3	84.09	112.53
243.0-	651.3	84.09	112.53

Exhibit 15-P-3 (cont.)
 Tabulation of Distance to WRJZ Daytime Allocation Contours

WRJZ	620 kHz	Lic	DANU	BL791210AE	20060523
TN	KNOXVILLE			5.000 kW 1 Tower	0 Augmentations
N. Lat:	35 59 24	W. Lon:	83 50 15		15 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
245.0-	651.3	84.09	112.53
250.0-	651.3	84.09	112.53
253.0M*	651.3	84.09	112.53
255.0+	651.3	84.09	112.53
260.0-	651.3	84.09	112.53
263.0-	651.3	84.09	112.53
265.0M*	651.3	84.09	112.53
270.0+	651.3	84.09	114.80
275.0+	651.3	84.09	116.84
280.0	651.3	84.09	115.52
285.0	651.3	84.09	114.49
290.0	651.3	84.09	113.27
293.0-	651.3	84.09	112.53
295.0-	651.3	84.09	112.53
300.0-	651.3	84.09	112.53
303.0M*	651.3	84.09	112.53
305.0+	651.3	84.09	112.53
310.0+	651.3	84.09	112.53
313.0+	651.3	84.09	112.53
315.0	651.3	84.09	112.53
320.0	651.3	84.09	112.53
325.0	651.3	84.09	112.53
327.0-	651.3	84.09	112.53
330.0-	651.3	84.09	112.53
335.0-	651.3	84.09	112.53
337.0M*	651.3	84.09	112.53
340.0+	651.3	84.09	112.53
345.0+	651.3	84.09	112.53
347.0+	651.3	84.09	112.53
350.0	651.3	84.09	112.53
353.0-	651.3	84.09	112.53
355.0-	651.3	84.09	112.53