

EXHIBIT 12

COMPLIANCE WITH RADIOFREQUENCY RADIATION GUIDELINES

The proposed DTV Companion Channel installation for WYGN-LP will be co-located with other broadcast facilities. The site will, therefore, be considered a “multiple use” site.

The proposed antenna will be a Model DRV-1/4HO manufactured by the Scala Division of Kathrein Inc. The antenna will be mounted with its center of radiation 137.2 meters above ground, making it 135.2 meters above an observer on the ground, who is assumed to be 2 meters tall. A maximum effective radiated power of 0.15 kW (150 watts) has been authorized. The addition of this antenna does not require any alteration of the Antenna Structure Registration for this site.

Equation 10 of OET Bulletin No. 65 can be used to predict the potential exposure to radiofrequency radiation for human observers on the ground as indicated by total power density expressed in units of $\mu\text{W}/\text{cm}^2$. This equation states:

$$S = \frac{33.4(F^2)ERP}{R^2}$$

where: S = Total Power Density in units of $\mu\text{W}/\text{cm}^2$

F = Relative Field of Pattern

ERP = Effective Radiated Power in Watts

R = Distance in Meters

In the case of the instant application, the proposed antenna consists of only one bay of four panels (mounted around the perimeter of the tower) operating at a VHF frequency. Therefore, the vertical plane pattern is quite broad. A relative field value of 1.0 has been used as a “worst case” scenario. The ERP was set equal to 150 watts, and a distance of 135.2 meters was used, which would be the antenna height above a 2 meter tall observer standing at the base of the tower. This is also the shortest possible distance from an observer on the ground to the antenna. Solving the above equation for S yields a total power density of $0.2741 \mu\text{W}/\text{cm}^2$.

At Channel 10, the FCC guideline for uncontrolled environments is $200 \mu\text{W}/\text{cm}^2$. Thus, the maximum predicted total power density from the proposed installation will be 0.14% of the limit for uncontrolled environments. At this frequency, the limit for uncontrolled environments is one-fifth of the limit for controlled environments. Therefore, the predicted exposure level is 0.03% of the limit for controlled environments.

Chapter 47 of the Code of Federal Regulations, §1.1307(b)(3) states: *“In general, when the guidelines specified in §1.1310 are exceeded in an accessible area due to the emissions from multiple fixed transmitters, actions necessary to bring the area into compliance are the shared responsibility of all licensees whose transmitters produce, at the area in question, power density levels that exceed 5% of the power density exposure limit applicable to their particular transmitter or field strength levels that, when squared, exceed 5% of the square of the electric or magnetic field strength limit applicable to their particular transmitter. Owners of transmitter sites are expected to allow applicants and licensees to take reasonable steps to comply with the requirements contained in §1.1307(b) and, where feasible, should encourage co-location of transmitters and common solutions for controlling access to areas where the RF exposure limits contained in §1.1310 might be exceeded.”* Should the level of radiofrequency radiation at the proposed “multiple use” site ever exceed the FCC guidelines, the proposed companion channel facility for WYGN-LP is categorically exempt from responsibility for bringing the shared transmitter site into compliance because its contribution is less than 5.0% of the applicable limit.

The facility will be properly marked with signs, and entry will be restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed. In the event work would be required in proximity to the antenna such that the person or persons working in the area would potentially be exposed to fields in excess of the guidelines, the station will cooperate with other licensees at the site to reduce power or cease operation during the critical period.