

April 2010
KUCC(FM) Channel 201A
Clarkston, WA
NIER Analysis

Facilities Proposed

The proposed operation will be on Channel 201A (88.1 MHz) with an effective radiated power of 0.24 kilowatts. Operation is proposed with a 1-element circularly-polarized omni-directional antenna, which will be mounted on the KZID(FM) tower located along the Central Grade road near Hatwai, Idaho.

The antenna support structure will not exceed 60.96 meters (200 feet) above ground and does not require notification to the Federal Aviation Administration. Therefore, this structure does not require an Antenna Structure Registration Number.

NIER Calculations

OET Bulletin 65 Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields (Edition 97-01) states in part that:

When performing an evaluation for compliance with the FCC's RF guidelines all significant contributors to the ambient RF environment should be considered. . . For purposes of such consideration, significance can be taken to mean any transmitter producing more than 5% of the applicable exposure limit (in terms of power density or the square of the electric or magnetic field strength) at accessible locations.

As will be demonstrated below, the proposed operation of KUCC will produce less than 5% of the applicable exposure limit for both controlled and uncontrolled environments. Thus, the proposed facility is categorically excluded from the requirement of further study. Therefore, pursuant to §1.1307(b)(3) of the Commission's Rules no calculations are required for the other FM and TV facilities in the vicinity, and precise calculations are made only with regard to the levels from this proposal.

The power density calculations shown below were made using the techniques outlined in OET Bulletin No. 65. "Ground level" calculations in this report have been made at a reference height of 2 meters above ground to provide a worst-case estimate of exposure for persons standing on

the ground in the vicinity of the tower. The equation shown below was used to calculate the ground level power density figures from each antenna.

$$S(\text{mW} / \text{cm}^2) = \frac{33.40981 \times \text{AdjERP}(\text{Watts})}{D^2}$$

Where: *AdjERP(Watts)* is the maximum lobe effective radiated power times the element pattern factor times the array pattern factor.

D is the distance in meters from the center of radiation to the calculation point.


Calculations of the power density produced by the KUCC antenna system assume a Type 6 element pattern, which is the appropriate element pattern for the Shively 6812B-1 antenna to be used by KUCC. Ground level power densities have been calculated for locations extending from the base of the tower to a distance of 1000 meters. Values past this point are increasingly negligible.

The highest calculated ground level power density from KUCC occurs at a distance of 33 meters from the base of the antenna support structure. At this point the power density is calculated to be 3.3 $\mu\text{W}/\text{cm}^2$, which is 0.3% of 1000 $\mu\text{W}/\text{cm}^2$ (the FCC standard for controlled environments) and 1.7% of 200 $\mu\text{W}/\text{cm}^2$ (the FCC standard for uncontrolled environments).

These calculations show that the maximum calculated power density produced at two meters above ground level by the proposed operation of KUCC alone is less than 5% of the applicable FCC exposure limit at all locations between 1 and 1000 meters from the base of the antenna support structure. Section 1.1307(b)(3) of the Commission's Rules excludes applications for new facilities or modifications to existing facilities from the requirement of preparing an environmental assessment when the calculated emissions from the applicants proposed facility are predicted to be less than 5% of the applicable FCC exposure limit. Therefore, the proposed facility is in compliance with Section 1.1301 et seq and no further analysis of non-ionizing radiation at this site is required in this application.

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency radiation in excess of FCC guidelines.

Hatfield & Dawson Consulting Engineers



Ground-Level NIER

OET FMModel

KUCC 201A Clarkston

Antenna Type: Shively 6812B-1

No. of Elements: 1

Element Spacing: dna

Distance: 1000 meters

Horizontal ERP: 0.24 kW

Vertical ERP: 0.24 kW

Antenna Height: 34 meters AGL

Maximum Power Density is 19.0 : W/cm^2 at 51 meters from the antenna structure.