

Non-Interference Compliance

Regarding Facility id 151295

Channel 282

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 contains a tabulation of the vertical radiation pattern of the proposed antenna and the minimum ground clearance of the interfering contour based on this pattern.

Page 4 includes a tabulation of the vertical radiation pattern for the proposed antenna provided by the antenna manufacturer.

Page 5 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 6 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 7 of this exhibit is a high resolution aerial photo of the vicinity surrounding the proposed translator's tower site provided by the U.S. Geological Survey's National Aerial Photography Program. It has been included to provide clarification of the nature of the buildings in the vicinity.

Note: The USGS Quadrangle and the aerial photo indicate the presence of buildings not exceeding 30ft in height. This application provides 11.5m (37.7ft) ground clearance which is adequate for clearing these buildings, so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
19948	BLH19800505AB	WQHQ	66.1	66.1
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				66.1

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **66.1 dBμ**, this makes the proposed translator's worst-case interfering contour **106.1 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **147.4 m** from the transmit antenna.

The maximum horizontal plane of the interfering contour was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 6 of this exhibit). However, the field strength of the proposed translator's antenna varies with angle of depression from horizontal. The antenna relative fields are tabulated on the following page at 5 degree increments, starting at 5 degrees below horizontal. Antenna relative field strength data was provided and certified by the manufacturer of the proposed antenna. Using a free-space calculation that neglects any loss due to reflection, the vertical ground clearance of the proposed translator's interference contour has been tabulated. As shown on the following page, the area of interference clears the tower ground level (TGL) by **11.5 m** at the lowest point. The applicant has taken into account USGS quadrangles and relevant aerial photography in stating that no structures, except possibly tower support structures, puncture the area of interference. Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Note: The USGS Quadrangle and the aerial photo indicate the presence of buildings not exceeding 30ft in height. This application provides 11.5m (37.7ft) ground clearance which is adequate for clearing these buildings, so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer:	NIC
Antenna Model:	BKG77
CORAGL:	77 m
Maximum ERP:	0.018 kW
Interfering Contour:	106.1 dBμ
Max Int. Contour Distance:	147.4 m
Min Ground Clearance:	11.5 m

Depression Angle Below Horizontal	Antenna Relative Field	ERP (watts)	Distance to Interfering Contour from Antenna (m)	Horizontal Distance of Interfering Contour from Tower (m)	Vertical Clearance of Interfering Contour above TGL (m)
5	.999	18.0	147.3	146.7	64.2
10	.982	17.4	144.8	142.6	51.9
15	.954	16.4	140.7	135.9	40.6
20	.918	15.2	135.4	127.2	30.7
25	.871	13.7	128.4	116.4	22.7
30	.818	12.0	120.6	104.5	16.7
35	.758	10.3	111.8	91.6	12.9
40	.691	8.6	101.9	78.0	11.5
45	.616	6.8	90.8	64.2	12.8
50	.538	5.2	79.3	51.0	16.2
55	.465	3.9	68.6	39.3	20.8
60	.391	2.8	57.7	28.8	27.1
65	.313	1.8	46.2	19.5	35.2
70	.239	1.0	35.2	12.1	43.9
75	.176	0.6	26.0	6.7	51.9
80	.128	0.3	18.9	3.3	58.4
85	.103	0.2	15.2	1.3	61.9
90	.105	0.2	15.5	0.0	61.5
Minimum Clearance above TGL:					11.5 m



BK077

Vertical	-66	0.297	54	0.479	174	0.468
Values	-63	0.345	57	0.436	177	0.479
-180	0.487	-60	0.391	60	0.391	
-177	0.478	-57	0.436	63	0.345	
-174	0.467	-54	0.479	66	0.297	
-171	0.460	-51	0.523	69	0.253	
-168	0.454	-48	0.568	72	0.211	
-165	0.447	-45	0.616	75	0.176	
-162	0.439	-42	0.661	78	0.145	
-159	0.429	-39	0.706	81	0.120	
-156	0.419	-36	0.745	84	0.105	
-153	0.402	-33	0.783	87	0.100	
-150	0.385	-30	0.818	90	0.105	
-147	0.369	-27	0.852	93	0.118	
-144	0.359	-24	0.881	96	0.134	
-141	0.350	-21	0.910	99	0.151	
-138	0.338	-18	0.934	102	0.168	
-135	0.326	-15	0.954	105	0.185	
-132	0.314	-12	0.972	108	0.202	
-129	0.303	-9	0.987	111	0.219	
-126	0.290	-6	0.999	114	0.236	
-123	0.278	-3	0.999	117	0.252	
-120	0.265	0	1.000	120	0.265	
-117	0.251	3	0.999	123	0.278	
-114	0.236	6	0.999	126	0.290	
-111	0.218	9	0.987	129	0.304	
-108	0.202	12	0.972	132	0.314	
-105	0.185	15	0.954	135	0.327	
-102	0.168	18	0.934	138	0.338	
-99	0.151	21	0.910	141	0.350	
-96	0.134	24	0.881	144	0.360	
-93	0.118	27	0.852	147	0.370	
-90	0.105	30	0.818	150	0.386	
-87	0.100	33	0.783	153	0.403	
-84	0.105	36	0.745	156	0.420	
-81	0.120	39	0.706	159	0.430	
-78	0.145	42	0.661	162	0.440	
-75	0.176	45	0.616	165	0.448	
-72	0.211	48	0.568	168	0.455	
-69	0.253	51	0.523	171	0.461	

Better than SWR

Adjacent Channel Study **For Station W282AU, Facility_id: 151295**

Co-channel through third adjacent:

Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
19948	28166	BLH	19800505AB	WQHQ	CUMULUS LICENSING CORP.	B	OCEAN CITY-SALISBUR	MD	LIC	33	189	284	2	40	0.4276
1204179	28166	BXPH	20070911AAU	WQHQ	CAPSTAR TX LIMITED PARTNERSHIP	B	OCEAN CITY - SALISBU	MD	CP	20	90	284	2	40	0.4276
1197425	152275	BLFT	20070727AIY	W282AW	EDGEWATER BROADCASTING INC.	D	OCEAN PINES	MD	LIC	0.012	99	282	0	26.7	0
1204591	152275	BPFT	20070911ADD	W282AW	EDGEWATER BROADCASTING INC.	D	OCEAN PINES	MD	APP	0.019	100	282	0	26.8	0
646020	152810	BNPFT	20030317EYX	NEW	EDGEWATER BROADCASTING, INC.	D	WILDWOOD	NJ	APP	0.019	101	281	1	39.2	0
270524	47107	BLH	19980630KF	WOCQ	GREAT SCOTT BROADCASTING	A	BERLIN	MD	LIC	6	111	280	2	41.2	0
632144	140732	BNPFT	20030310AQV	NEW	CALVARY CHAPEL OF TWIN FALLS, INC.	D	SEA ISLE CITY	NJ	APP	0.066	66	281	1	68	0
633915	142154	BNPFT	20030311AAQ	NEW	EDWARD A. SCHOBBER	D	PALERMO	NJ	APP	0.038	85	281	1	68.1	0
633088	141493	BNPFT	20030311ACN	NEW	EDWARD A. SCHOBBER	D	RIO GRANDE	NJ	APP	0.038	82	283	1	72.2	0
1176355	141393	BLFT	20070313AAU	W279BA	PRIORITY RADIO, INC.	D	EAST NEW MARKET	MD	LIC	0.019	102	279	3	81.8	0
986811	61100	BXLH	20040330BET	WMGM	SOUTH JERSEY RADIO, INC.	B	ATLANTIC CITY	NJ	LIC	8	85.3	279	3	91.1	0
257282	61100	BLH	19971121KA	WMGM	SOUTH JERSEY RADIO, INC.	B	ATLANTIC CITY	NJ	LIC	50	112	279	3	91.1	0
1117117	57357	BXPH	20060215AAW	WSJO	MILLENNIUM EGG HARBOR LICENSE HOLDCO, LL	B1	EGG HARBOR CITY	NJ	CP	0.44	132	285	3	93.6	0
163328	57357	BLH	19910726KB	WSJO	MEGA COMMUNICATIONS OF EGG HARBOR LI	B1	EGG HARBOR CITY	NJ	LIC	10	167	285	3	100.8	0
615113	53488	BLH	20021015ABT	WXCY	DELMARVA BROADCASTING COMPANY	B	HAVRE DE GRACE	MD	LIC	37	217	279	3	126.2	0
696899	53488	BXMLH	20031031ACJ	WXCY	DELMARVA BROADCASTING COMPANY	B	HAVRE DE GRACE	MD	LIC	33	157	279	3	127.3	0
262634	8684	BLH	19980219KF	WSMJ	CITICASTERS CO.	B	BALTIMORE	MD	LIC	32	221	282	0	139	0



