

08-09-2013

Terrain Data: USGS 03 SEC

FMOver Analysis

WYSZ BLED19921113KA

WTPG

Channel = 207A
 Max ERP = 2.45 kW
 RCAMSL = 290 M
 N. Lat. 41 38 55.0
 W. Lng. 83 42 22.0
 Protected
 60 dBu

Channel = 205B1
 Max ERP = 12.3 kW
 RCAMSL = 282 M
 N. Lat. 41 25 39.0
 W. Lng. 83 36 30.0
 Interfering
 100 dBu

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)	IX (km)
150.0	002.2862	0101.6	022.9	035.0	012.3000	0085.1	005.7	89.74	
151.0	002.2659	0101.4	022.9	032.6	012.3000	0085.2	005.4	90.80	
152.0	002.2457	0101.2	022.8	029.7	012.3000	0085.1	005.1	91.79	
153.0	002.2256	0101.0	022.7	026.4	012.3000	0085.4	004.8	92.79	
154.0	002.2055	0100.9	022.7	022.8	012.3000	0085.3	004.5	93.73	
155.0	002.1856	0100.8	022.6	018.8	012.3000	0085.0	004.3	94.61	
156.0	002.1657	0100.7	022.6	014.2	012.3000	0084.7	004.1	95.43	
157.0	002.1460	0100.5	022.5	009.0	012.3000	0084.9	003.9	96.16	
158.0	002.1263	0100.5	022.4	003.6	012.3000	0085.4	003.8	96.83	
159.0	002.1067	0100.6	022.4	357.7	012.3000	0086.7	003.7	97.45	
160.0	002.0872	0100.8	022.4	351.7	012.3000	0087.5	003.6	97.90	
161.0	002.0638	0101.1	022.3	345.4	012.3000	0087.0	003.5	97.96<--	
162.0	002.0405	0101.1	022.3	339.2	012.3000	0087.7	003.6	97.81	
163.0	002.0173	0101.1	022.2	333.2	012.3000	0087.0	003.7	97.26	
164.0	001.9942	0101.3	022.2	327.6	012.3000	0086.3	003.8	96.64	
165.0	001.9713	0101.5	022.1	322.5	012.3000	0085.8	004.0	95.91	
166.0	001.9485	0101.6	022.1	317.9	012.3000	0084.9	004.2	94.97	
167.0	001.9258	0101.5	022.0	314.0	012.3000	0083.8	004.5	93.87	
168.0	001.9033	0101.4	022.0	310.6	012.3000	0083.2	004.7	92.82	
169.0	001.8809	0101.4	021.9	307.6	011.4325	0082.7	005.0	91.47	
170.0	001.8587	0101.2	021.8	305.1	010.5775	0082.4	005.3	90.04	