

R. Morgan Burrow Jr., P.E.
Everett, PA 15537

EXHIBIT 12-B

NEW-Translator Ch. 255D York, PA 0.25 kW HV - DA
PROPOSED DIRECTIONAL ALLOCATION TO WQLV Millersburg, PA

WQLV Ch. 255A Millersburg, PA 0.78 kW HV RCAMSL 466 m
Co-Channel Protection from Proposed Translator

BR FROM WQLV	HAAT FROM WQLV (m)	DIST TO PC (km)	COORDS. AT PC	DIST FROM TRANS. (km)	BR FROM TRANS.	ERP FROM TRANS.	REL FLD	HAAT FROM TRANS. (m)	DIST TO IX CONT	CLEAR (km)
100 deg T	294.3	29.171	40 27 32.0-77 46 43.7	57.901	353.32	225 watts	0.949	118.2	46.278	11.623
110	293.7	29.142	40 24 53.2-76 47 41.5	53.168	351.20 deg T	225	0.949	121.2	47.870	5.298
120	321.3	30.482	40 22 02.3-76 48 24.1	48.150	349.05	225	0.949	123.6	47.034	1.116
130	324.4	30.638	40 19 38.3-76 50 28.8	44.514	344.25	150	0.775	130.2	43.442	1.072
140	296.1	29.258	40 18 10.6-76 53 46.6	43.510	337.36	140	0.748	129.7	42.843	0.667
150	299.9	29.441	40 16 30.9-76 56 39.9	42.557	330.67	130	0.721	127.5	41.994	0.563
150.28 dir.	299.9	29.451	40 16 28.3-76 56 45.0	42.547	330.48	130	0.721	127.9	41.994	0.553
160	265.2	27.747	40 16 12.5-77 00 21.3	44.908	324.51	140	0.748	121.6	42.047	2.861
170	278.0	28.376	40 15 12.0-77 03 34.5	46.315	318.58	140	0.748	122.5	42.047	4.268
180	270.9	28.027	40 15 09.3-77 07 03.0	49.677	314.27	225	0.949	122.6	46.898	2.779
190	243.3	26.660	40 16 06.7-77 10 18.9	54.275	313.23	225	0.949	123.4	47.008	7.267
200	249.8	26.984	40 16 35.7-77 13 33.6	58.350	309.87	225	0.949	124.7	47.184	11.166
210	248.6	26.925	40 17 41.6-77 16 33.0	62.925	308.85	225	0.949	125.5	47.293	15.632