

Exhibit 7-RFR
KIMG-LP Ventura, CA Channel 20
Prepared by WES Broadcast Consultants, INC.

GUIDELINES FOR HUMAN EXPOSURE TO RADIOFREQUENCY RADIATION
EVALUATION OF COMPLIANCE WITH FCC-SPECIFIED GUIDELINES FOR
EXPOSURE TO RADIOFREQUENCY RADIATION FROM A SINGLE
UHF TV BROADCAST STATION

ANTENNA COR AGL? 98.4

ENTER VIS AND AUR ERP (KW)? 2.38

CHANNEL 20

506-512 Mhz

VISUAL CARRIER 507.25 Mhz

VISUAL ERP

2.4 KW

AURAL CARRIER 511.75 Mhz

AURAL ERP

0.0 KW

MAXIMUM POWER DENSITY AT CHANNEL 20

1.691 mW/CM2

ANTENNA COR AGL 30.0M 98.4 FT

POWER DENSITY AT 98 FT FROM COR (WORST CASE)

0.035 mW/cm2

POWER DENSITY AT 98 FT FROM COR (.1 REL FIELD)

0.000 mW/cm2

MINIMUM REQUIRED DISTANCE (WORST CASE)

4.3 M

14.2 FT

MINIMUM REQUIRED DISTANCE (.1 REL FIELD)

0.4 M

1.4 FT

CLEAR BY (COR-MAH) (WORST CASE)

25.7 M

84.2 FT

CLEAR BY (COR-MAH) (.1 REL FIELD)

29.6 M

97.0 FT

FOR MULTIPLE SOURCES: SUM PERCENTAGES OF ANSI STANDARDS
SUMATION NOT TO EXCEED 100 %

PERCENT OF ANSI STANDARD AT GROUND LEVEL (WORST CASE)

2.1 %

PERCENT OF ANSI STANDARD AT GROUND LEVEL (0.1 REL FIELD)

0.0 %

THE TOWER IS CLEARLY MARKED WITH A CLEARLY VISIBLE RADIATION HAZARD
PLACARD.

IN THE EVENT THAT MAINTENANCE IS TO BE PERFORMED PERSONNEL ARE TRAINED
TO LOWER POWER OR SHUT OFF TRANSMITTER.