

August 4, 2003

I certify that the following translators have been checked for spurious emissions and modulation and that they comply with the requirements of 47 C.F.R. Sections 73.317(b) through 73.317(d) as demonstrated below.

Measurements were taken using a calibrated RF spectrum analyzer.

Signed:

Isaac B. Moore, PE
Consulting Engineer
CSN International

COMPLIANCE VERIFICATION TABLE

Station	Freq. Of un-modulated carrier (MHz)	Station unmod. Carrier is ref. (dB below ref.)	Mea. with respect to unmod. carrier (kHz)	Station unmod. Carrier is ref. (dB below ref.)	Mea. with respect to unmod. carrier	Station unmod. Carrier is ref. (dB below ref.)	Mea. with respect to unmod. carrier	Station unmod. Carrier is ref. (dB below ref.)	Highest Freq. Meas. (MHz)
47CFR 73.317 compliance			(b)	(b)	(c)	(c)	(d)	(d)	
K209EW	89.7	0	120 to 240	>84	240 to 600	>84	>600	>84	270.5
K213DT	90.5	0	120 to 240	>80	240 to 600	>80	>600	>80	271.5

Noise Floor >80 dB below K209EW unmodulated carrier and >81 dB below K213DT unmodulated carrier

NOTES:

47 CFR 73.317 (b) requires >25 dB below unmodulated carrier

47 CFR 73.317(c) requires >35 dB below unmodulated carrier

47 CFR 73.317(d) requires >61 dB below unmodulated carrier for K209EW and >57 dB below unmodulated carrier for K213DT