

EXHIBIT 12
Page #1, Waiver Request of Section 74.1204

K206DJ, Klamath Falls, OR 10 Watts ERP

Calvary Chapel of Twin Falls, Inc. 09/02

The proposed site is contained entirely inside the service contour of second-adjacent Station, KAGO-FM, Klamath Falls, OR.

KAGO-FM

The proposed site is contained entirely inside the service contour of second-adjacent Station KAGO-FM, Channel 258, Class C1, 60 kW, Klamath Falls, OR. As shown by the map on **page #2** of this waiver request, the level of the second -adjacent station KAGO-FM arriving protected F(50,50) signal at the proposed transmitter site is 80-dBu. Using the Undesired-to-Desired method for calculating proposed interference (the basis of the FCC current contour overlap regulations and an acceptable method for the purposes of determining lack of interference for an FM Translator), the proposed interfering contour with respect to KAGO-FM is 120-dBu (free-space contour method employed). This means that the 120-dBu interfering signal would extend 23 meters from the center of radiation, which is proposed at 24 meters AGL. Since no population inhabits this interference area (please see TOPO Map Exhibit), Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second -adjacent channel station KAGO-FM.

The Commission's implementation of the Revised FM Engineering Rules, released in a *Report and Order* November 1, 2000 found in the "1998 Biennial Regulatory Review" in MM Docket 98-93, have been applied.