

ENGINEERING REPORT

FM Translator Minor Construction Permit Application

for

W278BJ – Le Roy, IL

Pending License Operation
BLFT-20090804AAX

August, 2009

COPYRIGHT 2009

MUNN-REESE, INC.
Broadcast Engineering Consultants
Coldwater, MI 49036

TABLE OF CONTENTS

Discussion of Report

FM Booster/Fill-in Translator Requirements (See Discussion)

Interference Requirements

Exhibit 12.1 - USGS Topographic Map of Site

Exhibit 12.2 - Vertical Plan of Antenna System and Support Tower

Exhibit 12.3 - Present vs Proposed Service Contour Study

Exhibit 12.4 - Proposed vs Primary Station Service Contour Study

Contour Overlap Requirements

Exhibit 12.5 - Tabulation of Proposed Allocation

TV Channel 6 Protection Requirements (See Discussion)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 16.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of a minor construction permit application for FM translator W278BJ, Le Roy, IL, pending license BLFT-20090804AAX. W278BJ presently operates on 103.5 MHz with 55 watts of non-directional power with an antenna COR of 231 meters AMSL. A new site location and AMSL height are requested. Operation on CH224D with 150 watts ERP at 244 meters AMSL is requested. The translator will rebroadcast new FM station WCFF(FM), Urbana, IL, CH223B1, facility ID No. 41592 and remain licensed to Le Roy, IL.

TOWAIR has been consulted and the proposed tower does not require Antenna Structure Registration. A copy of the USGS topographic mapping depicting the site has been included in **Exhibit 12.1**. A copy of the vertical antenna system has been included in **Exhibit 12.2**. It has been determined the translator may be used in the area without interference to any existing FM broadcast station or facility with the exception of primary station WCFF(FM) – CH223B1, Urbana, IL. General allocation details are found in **Exhibit 12.5**. First adjacent channel interference to the primary station is allowable under §74.1204(e) as long as the area of interference does not occur over the primary city of license. In this instance the area of interference will be restricted to areas outside of Urbana, IL as noted in **Exhibit 12.4**. It is believed sufficient clearance exists precluding the need for additional contour protection showings.

The applicant would like to note all allocation and contour showings have been determined using the 30 sec NGDC terrain database.

The proposed 60 dBu contour of the translator lies inside of the WCFF(FM) primary service contour therefore qualifying for “Fill-In” translator status . A map of the proposed service area in relation to the primary station service contour has been included in **Exhibit 12.4**.

Regarding protection of international concerns, the facility is and will remain more than 320 km from the common border between the United States and Canada or Mexico. As a result, no further international showings are required.

The proposed operating parameters have been changed from the licensed values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 12.3**.

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules.

The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

Discussion (continued)

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1310 of the Commission's rules. **Exhibit 16.1** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1.

N. Lat. = 401214.0 W. Lng. = 882459.0 HAAT and Distance to Contour, FCC, FM 2-10 Mi, 51 pts Method - NGDC 30 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	224.2	19.8	0.1500	-8.24	1.000	6.24
030	215.0	29.0	0.1500	-8.24	1.000	6.24
060	218.7	25.3	0.1500	-8.24	1.000	6.24
090	227.2	16.8	0.1500	-8.24	1.000	6.24
120	233.4	10.6	0.1500	-8.24	1.000	6.24
150	216.6	27.4	0.1500	-8.24	1.000	6.24
180	214.2	29.8	0.1500	-8.24	1.000	6.24
210	211.3	32.7	0.1500	-8.24	1.000	6.47
240	214.7	29.3	0.1500	-8.24	1.000	6.24
270	219.7	24.3	0.1500	-8.24	1.000	6.24
300	227.0	17.0	0.1500	-8.24	1.000	6.24
330	228.6	15.4	0.1500	-8.24	1.000	6.24
Ave El= 220.89 M HAAT= 23.11 M AMSL= 244 M						