

Robert Moore

Csn International										
REFERENCE		CH# 260D - 99.9 MHz, Pwr= 0.013 kW, HAAT= 0.0 M, COR= 413 M							DISPLAY DATES	
41 41 52.0 N.		Average Protected F(50-50)= 3.36 km							DATA 08-26-13	
84 59 09.0 W.		Omni-directional							SEARCH 08-28-13	
CH	CALL	TYPE	ANT	AZI	DIST	LAT	PWR(kw)	INT(km)	PRO(km)	*OUT*
CITY		STATE		<--	FILE #	LNG	HAAT(M)	COR(M)	LICENSEE	(Overlap in km)
260D	1563193	APP _C_		0.0	0.00	41 41 52.0	0.013	21.6	6.5	-28.1*
Angola		IN		0.0	BNPFT20030317KII	84 59 09.0		413	Csn International	
262A	WLKI	LIC NCN		214.4	2.28	41 40 51.0	4.000	2.6	27.0	-25.0*
Angola		IN		34.4	BLH19920429KA	85 00 05.0	120	428	Swick Broadcasting Company	
Accepted by Canada on 911002										
257A	WBET-FM	LIC _C_		282.7	36.83	41 46 11.0	4.400	2.4	24.5	12.0
Sturgis		MI		102.4	BLH20090925ACG	85 25 09.0	100	367	Swick Broadcasting Company	

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference zone= East Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
Incoming contour overlap is ignored.
"*"affixed to 'IN' or 'OUT' values = site inside protected contour.