

Non-Interference Compliance

Regarding Facility id 152214

Channel 209

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 contains a tabulation of the vertical radiation pattern of the proposed antenna and the minimum ground clearance of the interfering contour based on this pattern.

Page 4 includes a tabulation of the vertical radiation pattern for the proposed antenna provided by the antenna manufacturer.

Page 5 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 6 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 7 of this exhibit is a high resolution aerial photo of the vicinity surrounding the proposed translator's tower site provided by the U.S. Geological Survey's National Aerial Photography Program. It has been included to provide clarification of the nature of the buildings in the vicinity.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
1017980	BLED20040927ALP	WABE	61	61.1
1198644	BPED20070820ABQ	WABE	61.1	61.1
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				61.1

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **61.1 dBμ**, this makes the proposed translator's worst-case interfering contour **101.1 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **163.5 m** from the transmit antenna.

The maximum horizontal plane of the interfering contour was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 6 of this exhibit). However, the field strength of the proposed translator's antenna varies with angle of depression from horizontal. The antenna relative fields are tabulated on the following page at 5 degree increments, starting at 5 degrees below horizontal. Antenna relative field strength data was provided and certified by the manufacturer of the proposed antenna. Using a free-space calculation that neglects any loss due to reflection, the vertical ground clearance of the proposed translator's interference contour has been tabulated. As shown on the following page, the area of interference clears the tower ground level (TGL) by **18.4 m** at the lowest point. The applicant has taken into account USGS quadrangles and relevant aerial photography in stating that no structures, except possibly tower support structures, puncture the area of interference. Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer:	NIC
Antenna Model:	BKG77
CORAGL:	91 m
Maximum ERP:	0.007 kW
Interfering Contour:	101.1 dBμ
Max Int. Contour Distance:	163.5 m
Min Ground Clearance:	18.4 m

Depression Angle Below Horizontal	Antenna Relative Field	ERP (watts)	Distance to Interfering Contour from Antenna (m)	Horizontal Distance of Interfering Contour from Tower (m)	Vertical Clearance of Interfering Contour above TGL (m)
5	.999	7.0	163.3	162.7	76.8
10	.982	6.8	160.6	158.1	63.1
15	.954	6.4	156.0	150.7	50.6
20	.918	5.9	150.1	141.1	39.7
25	.871	5.3	142.4	129.1	30.8
30	.818	4.7	133.8	115.8	24.1
35	.758	4.0	123.9	101.5	19.9
40	.691	3.3	113.0	86.6	18.4
45	.616	2.7	100.7	71.2	19.8
50	.538	2.0	88.0	56.5	23.6
55	.465	1.5	76.0	43.6	28.7
60	.391	1.1	63.9	32.0	35.6
65	.313	0.7	51.2	21.6	44.6
70	.239	0.4	39.1	13.4	54.3
75	.176	0.2	28.8	7.4	63.2
80	.128	0.1	20.9	3.6	70.4
85	.103	0.1	16.8	1.5	74.2
90	.105	0.1	17.2	0.0	73.8
Minimum Clearance above TGL:					18.4 m



BK077

Vertical	-66	0.297	54	0.479	174	0.468
Values	-63	0.345	57	0.436	177	0.479
-180	0.487	-60	0.391	60	0.391	
-177	0.478	-57	0.436	63	0.345	
-174	0.467	-54	0.479	66	0.297	
-171	0.460	-51	0.523	69	0.253	
-168	0.454	-48	0.568	72	0.211	
-165	0.447	-45	0.616	75	0.176	
-162	0.439	-42	0.661	78	0.145	
-159	0.429	-39	0.706	81	0.120	
-156	0.419	-36	0.745	84	0.105	
-153	0.402	-33	0.783	87	0.100	
-150	0.385	-30	0.818	90	0.105	
-147	0.369	-27	0.852	93	0.118	
-144	0.359	-24	0.881	96	0.134	
-141	0.350	-21	0.910	99	0.151	
-138	0.338	-18	0.934	102	0.168	
-135	0.326	-15	0.954	105	0.185	
-132	0.314	-12	0.972	108	0.202	
-129	0.303	-9	0.987	111	0.219	
-126	0.290	-6	0.999	114	0.236	
-123	0.278	-3	0.999	117	0.252	
-120	0.265	0	1.000	120	0.265	
-117	0.251	3	0.999	123	0.278	
-114	0.236	6	0.999	126	0.290	
-111	0.218	9	0.987	129	0.304	
-108	0.202	12	0.972	132	0.314	
-105	0.185	15	0.954	135	0.327	
-102	0.168	18	0.934	138	0.338	
-99	0.151	21	0.910	141	0.350	
-96	0.134	24	0.881	144	0.360	
-93	0.118	27	0.852	147	0.370	
-90	0.105	30	0.818	150	0.386	
-87	0.100	33	0.783	153	0.403	
-84	0.105	36	0.745	156	0.420	
-81	0.120	39	0.706	159	0.430	
-78	0.145	42	0.661	162	0.440	
-75	0.176	45	0.616	165	0.448	
-72	0.211	48	0.568	168	0.455	
-69	0.253	51	0.523	171	0.461	

Better than SWR

Adjacent Channel Study **For Station W209CD, Facility_id: 152214**

Co-channel through third adjacent:

Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
1198644	3538	BPED	20070820ABQ	WABE	BOARD OF EDUCATION OF THE CITY OF ATLANTA	C0	ATLANTA	GA	CP	100	615	211	2	53.6	0.0418
1017980	3538	BLER	20040927ALP	WABE	BOARD OF EDUCATION OF THE CITY OF ATLANTA	C1	ATLANTA	GA	LIC	96	531.2	211	2	53.7	0.0418
1318752	5125	BPED	20090630ACV	WYFW	BIBLE BROADCASTING NETWORK, INC.	A	WINDER	GA	CP	6	333	208	1	20	0
252347	5125	BLER	19970821KA	WYFW	BIBLE BROADCASTING NETWORK, INC.	A	WINDER	GA	LIC	6	330	208	1	20.6	0
83875	6706	BLER	19851202KD	WBCX	BRENAU COLLEGE	A	GAINESVILLE	GA	LIC	0.84	447	206	3	25.3	0
1213950	176071	BNPED	20071022AQA	NEW	COMMON GROUND ATHENS, INC.	A	NICHOLSON	GA	APP	1	338.5	210	1	45.2	0
1213933	176054	BNPED	20071022ACZ	NEW	IGLESIA JESUCRISTO ES MI REFUGIO DE AUSTIN	A	GROVE LEVEL	GA	APP	0.5	275	210	1	45.2	0
1212211	174934	BNPED	20071018BBB	NEW	TEMPLO APOSTOLES Y PROFETAS BETHEL	A	COMMERCE	GA	APP	0.5	243	210	1	45.9	0
1223998	172115	BNPED	20071015ABL	NEW	COMMUNITY PUBLIC RADIO, INC.	A	COMMERCE	GA	APP	0.18	340	210	1	46.7	0
581027	76477	BLER	19980915AAA	WNGU	GEORGIA PUBLIC TELECOMMUNICATIONS COMPANY	A	DAHLONEGA	GA	LIC	0.75	573	208	1	47	0
1210948	174196	BNPED	20071016AHT	NEW	HOPE THROUGH EDUCATION, INC.	A	COMMERCE	GA	APP	0.5	269	210	1	47.1	0
1215501	177060	BNPED	20071022BFC	NEW	EDGEWATER BROADCASTING, INC.	A	COMMERCE	GA	APP	0.94	398	210	1	47.3	0
1208736	54585	BLER	20071001DQH	WRFG	RADIO FREE GEORGIA BROADCASTING FOUNDATION	C1	ATLANTA	GA	LIC	65	432	207	2	50.2	0
606645	123145	BNPFT	20000407AAM	NEW	FAITH PLEASES GOD CHURCH CORP.	D	WINTERVILLE	GA	APP	0.01	276	209	0	56.1	0
546276	90471	BLER	20010111AAE	WTFH	TOCCOA FALLS COLLEGE	A	HELEN	GA	LIC	0.015	842	210	1	73.9	0
1118648	77327	BLER	20010125ABQ	WTRX	TOCCOA FALLS COLLEGE	A	TOCCOA FALLS	GA	LIC	0.4	387	209	0	75.5	0
1242151	92827	BPFT	20080404AAW	W209BJ	CALVARY CHAPEL OF TWIN FALLS, INC.	D	DANIELSVILLE	GA	CP	0.013	287	207	2	75.8	0
624061	92827	BLFT	20030124AEF	W209BJ	CALVARY CHAPEL OF TWIN FALLS, INC.	D	DANIELSVILLE	GA	LIC	0.013	287	209	0	75.8	0

