

EXHIBIT 34
ENVIRONMENTAL COMPLIANCE
KTYV STEAMBOAT SPRINGS, COLORADO 255A
RADIO PARTNERS LLC
FCC FORM 301
AUGUST 2012

From what was authorized in the CP, the applicant proposes to lower the ERP of KTYV from 1.85 kW to 0.8 kW and to change the antenna system from a ERI single bay rototiller to a Nicom BKG77, 2 bay, 0.7 wave-spaced, antenna system that is circularly polarized. The original ERI antenna would have a predicted peak exposure of 165 uW/cm². Calculations for the new antenna system using FM Model for Windows, version 2.10, predict a peak exposure of 58.726 W/cm² at a distance of 2.2 meters from the base of the tower. This represents less than 30% of the allowable Maximum Permissible Exposure (MPE) of 200 W/cm² for uncontrolled environments and is less than 36% of the approved antenna system in the CP.

The applicant will ensure that the public access to the antenna system is restricted by fencing, anti-climb devices or other appropriate measures. The site will be posted with RF warning signs. If access to the antenna system by authorized personnel becomes necessary, transmitter power will be reduced to safe operating levels or transmission will be terminated, if necessary, as not to exceed the RF exposure limits to workers. The licensee will cooperate with other users at the site with the scheduling of such maintenance.

The National Programmatic Agreement generally allows such a collocation without consultation or review under Section 106 and Subpart B of 36 CFR §800. The

applicant believes that it is in full compliance with the Agreement, and that no further study is required.