



332N

65678

United States of America

**FEDERAL COMMUNICATIONS COMMISSION**  
**FM BROADCAST STATION LICENSE**

Official Mailing Address:

THE HEARST CORPORATION  
400 ARDMORE BLVD  
PITTSBURGH, PA 15221

Authorizing Official:

Dale E. Bickel  
Supervisory Engineer  
Audio Services Division  
Mass Media Bureau

MBZ

Grant Date: August 11, 1992

Call Sign: WVTY

This license expires 3:00 a.m.  
local time, August 01, 1998

License File No.: BLH-920206KC

This authorization re-issued to reflect a corrected value for the  
transmitter output power. Reissued 9/25/1996.

Subject to the provisions of the Communications Act of 1934,  
subsequent acts and treaties, and all regulations heretofore or  
hereafter made by this Commission, and further subject to the  
conditions set forth in this license, the licensee is hereby  
authorized to use and operate the radio transmitting apparatus herein  
described.

This license is issued on the licensee's representation that the  
statements contained in licensee's application are true and that the  
undertakings therein contained so far as they are consistent herewith,  
will be carried out in good faith. The licensee shall, during the term  
of this license, render such broadcasting service as will serve the  
public interest, convenience, or necessity to the full extent of the  
privileges herein conferred.

This license shall not vest in the licensee any right to operate the  
station nor any right in the use of the frequency designated in the  
license beyond the term hereof, nor in any other manner than  
authorized herein. Neither the license nor the right granted hereunder  
shall be assigned or otherwise transferred in violation of the  
Communications Act of 1934. This license is subject to the right of  
use or control by the Government of the United States conferred by  
Section 606 of the Communications Act of 1934.

Name of Licensee:

THE HEARST CORPORATION

Station Location:

PA-PITTSBURGH

Frequency (MHz): 96.1

Channel: 241

Class: B

Hours of Operation: Unlimited

Main Studio Address:

PA-400 ARDMORE BOULEVARD, WILKINSBURG

Transmitter location (address or description):

AGNEW ROAD, BALDWIN, PA

Remote Control Point Address:

PA - 400 ARDMORE BOULEVARD, WILKINSBURG

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670  
of the Commission's Rules.

Transmitter output power: 15.5 kW

Antenna type: (directional or non-directional): Non-Directional

Description: JAMPRO JBBP-6R, SIX SECTIONS, CIRCULARLY POLARIZED ANTENNA,  
SIDE-MOUNTED ON A GUYED STEEL TOWER

Antenna Coordinates: North Latitude : 40 23 49  
West Longitude : 79 57 43

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW).....:	44	44
Height of radiation center above ground (Meters).....:	90	90
Height of radiation center above mean sea level (Meters).....:	464	464
Height of radiation center above average terrain (Meters).....:	159	159

Antenna structure registration number: none

Overall height of antenna structure above ground  
(including obstruction lighting if any): 100 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

PARAGRAPH 01.0, FCC FORM 715 (OCTOBER 1985):

Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 100 feet nor less than 1 and 1/2 feet in width. All towers shall be cleaned and repainted as often as necessary to maintain good visibility.

PARAGRAPH 03.0, FCC FORM 715 (APRIL 1985):

There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 20 feet in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

PARAGRAPH 12.0, FCC FORM 715 (APRIL 1985):

On levels at approximately two-thirds and one-third of the over-all height of the tower, there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of at least one light at each level from aircraft at any normal angle of approach.

PARAGRAPH 21.0, FCC FORM 715 (APRIL 1985):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

Special operating conditions or restrictions:

None Required

\*\*\* END OF AUTHORIZATION \*\*\*