

EXHIBIT 8
Environmental Analysis
WQAW-LP
FCC File No. BLTTL-20050610AFH
Facility ID No. 131071

The proposed LPTV CH 8 facilities were evaluated in terms of potential radiofrequency radiation (RFR) exposure at ground level at the base of the tower in accordance with OST Bulletin No. 65, "Evaluating Compliance With FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation." The calculated power density at the base of the tower was calculated using the appropriate equation on Page 13 of the Bulletin. Using a greater than expected vertical relative field value of 0.2, a maximum visual effective radiated power of 3 kilowatts and 10 percent aural power, the calculated power density at 2 meters above ground level at the base of the tower is 0.009 milliwatt per square centimeter (MW/ CM²), or 4.0 percent of the Commission's recommended limit applicable to general population/uncontrolled exposure areas (0.223 MW/CM² for TV channel 8). However, as this is a multi-user site, measurements will be made to substantiate compliance with the RF emission rules.

Access to the transmitting site will be restricted and appropriately marked with warning signs. Furthermore, as this is a multi-user site, an agreement will be in effect in the event that workers or other authorized personnel enter the restricted area or climb the tower to ensure that appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing "accepted" RFR protective clothing and/or RFR exposure monitors or scheduling work when the stations are at reduced power or shut down.