

Crossfire Incorporated
 REFERENCE CH# 250D - 97.9 MHz, Pwr= 0.028 kW, HAAT= 236.3 M, COR= 495.1 M DISPLAY DATES
 43 44 53.0 N. Average Protected F(50-50)= 11.59 km DATA 02-04-11
 91 17 51.0 W. Omni-directional SEARCH 02-28-11

CH CITY	CALL	TYPE STATE	ANT	AZI <--	DIST FILE #	LAT LNG	PWR(kw) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*OUT*
250D La Crosse	W250AX	LIC _V_ WI		6.9 186.9	0.7 BLFT20071001AER	43 45 17.0 91 17 47.0	0.010	16.9 371	5.2 Crossfire Incorporated	-48.3*
252C2 Spring Grove	KQYB	LIC _CN MN		258.8 78.5	37.8 BLH19901121KD	43 40 53.0 91 45 28.0	33.000 185	6.7 506	56.9 Family Radio, Inc.	-19.5*<
250C1 Stevens Point	WSPT-FM	LIC _CN WI		56.5 237.7	162.0 BLH19961015KB	44 32 17.0 89 35 43.0	100.000 103	147.1 436	51.7 Americus Communications, L	71.3
248C Rochester	KNXR	LIC _C_ MN		291.7 110.9	89.9 BLH19990505KB	44 02 28.0 92 20 25.0	100.000 317	9.9 671	71.2 United Audio Corporation	18.3

Terrain database is FCC NGDC 30 Sec , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
 In & Out distances between contours are shown at closest points. Reference zone = 2, Co to 3rd adjacent.
 Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
 Incoming contour overlap is ignored.
 "*"affixed to 'IN' or 'OUT' values = site inside protected contour.