

[Exhibit 12]

Non-Interference Compliance

Regarding FCC File Number: BNPFT-20030317CXC

Channel: 259

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all the applicable rule sections and that this application for a construction permit is in full compliance with 47 CFR 74.1204.

Page 2 of this exhibit is an explanation of the tabulated data, which is included as evidence on page 4 of this exhibit.

Page 3 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference protection provisions based on 47 CFR 74.1204(d), which states:

"an application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable."

In addition, page 3 includes a tabulation of the second and third adjacent stations which this application is required to protect and the field strengths of those stations in the vicinity of the proposed translator. The field strengths given were based on contours predicted using FCC contour algorithms and 3 arc second terrain data.

Let it be noted that should any actual real world interference occur, the applicant certifies that it will promptly suspend operation of this translator in accordance with 47 CFR 74.1203.

Page 4 of this exhibit is the tabulated data from the interference analysis, which shows all stations that this application had to consider for contour protection. These tabulated values were generated using high resolution 3 arc second terrain data for the best possible accuracy.

Page 5 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 min quadrangle at full scale with the calculated area of interference overlayed. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using a free-space calculation (see FCC 98-117, Appendix A, pg. 41 for reference to the equation used).

At the end of this exhibit are plots of the protected and interference contours of the proposed translator and any other stations from which the applicant is willing to accept interference. These contours were plotted using 3 arc second terrain data for the highest degree of accuracy possible.

Since the proposed translator is 13.3 km from the Mexican border, 47 CFR 74.1235(d) has been taken into account and this applicant certifies that in the direction of the Mexican border, the 34 dBu F(50,10) does not extend beyond 32 km, nor does the 60 dBu F(50,50) extend beyond 8.7 km. The maximum effective radiated power (ERP) for the proposed translator is 19 watts, which is less than the limit of 50 watts. This application is therefore in full compliance with 47 CFR 74.1235(d)(1), and hence in compliance with 47 CFR 74.1204(h).

Explanation of Frequency Finder Results

The interference analysis for this application was performed using the "Frequency Finder" module in RadioSoft's Comstudy, version 2.2.

Frequency Finder analyzes data taken directly from the FCC's FM database and looks for prohibited overlap with contours of adjacent stations and prohibited proximity to stations 53 or 54 channels from the proposed station (IF) using 3 arc second terrain data and the FCC's contour algorithms. The results tabulated are the stations returned from that analysis. (Note: Because Comstudy was looking at the FCC's FM database, it took into account the proposed translator when doing the analysis and returned it in the tabulated results. For the sake of simplicity, that record has been deleted from all tabulated results.)

The first several columns of the table are self-explanatory. They give various data on the stations in question. The column labeled "Clr" gives the proposed translator's "clearance" with respect to the tabulated station, either in dB or km. The values listed with no units are given in km and are for stations located on an IF to the proposed site's channel.

A negative value in the "Clr" column does NOT necessarily represent prohibited contour overlap, as explained below.

A negative value listed in the "Clr" column would indicate either overlap of interference and protected contours or prohibited proximity to an IF station except in the following situations:

- Since the proposed station's Effective Radiated Power (ERP) is 19 watts, a negative value in km (no units listed in the table) does not represent a violation of the CFR, according to 47 CFR 1204(g), which states that "FM translator stations and booster stations operating with less than 100 watts ERP will be treated as class D stations and will not be subject to intermediate frequency separation requirements."

- A second or third adjacent LP100 station cannot represent a violation of the CFR, as 47 CFR 74.1204(a)(4) requires protection of only co-channel and first adjacent LP100 stations.

- 47 CFR 74.1204(a) requires only the protection of "AUTHORIZED commercial or noncommercial educational FM broadcast stations, FM translators, ..." Any entry with a status listed as "RSV," "USE" or "APP" does not represent an authorized station and therefore is not protected under 47 CFR 74.1204. The one exception is the case of LP100 applications. The note to 47 CFR 74.1204(a)(4) states that "LPFM applications and permits that have not yet been licensed must be considered as operating with the maximum permitted facilities." Therefore, any first adjacent or co-channel LP100 station, no matter the status, is protected.

- Entries highlighted in red are those stations where there is overlap of predicted contours and lack of population has been demonstrated within the area of interference.

- Entries highlighted in blue are those that were returned in the results because of interference caused to this proposed translator. Contours were plotted by RadioSoft's Comstudy, version 2.2, using the FCC's contour algorithms, and these are included at the end of this exhibit showing that interference is caused only to the proposed translator and not by it.

Compliance with 47 CFR 74.1204(d)

The proposed translator's Maximum Effective Radiated Power (ERP) is 0.019kW at 81 meters above ground level. According to 47 CFR, 74.1204(a), the desired to undesired ratio between 2nd/3rd adjacent stations is 40dB, making the proposed translator's interfering contour 109.6dBu F(50,10).

Using a free-space calculation (equation referenced in FCC 98-117, Appendix A, pg. 41), this proposed translator's F(50,10) interference contour was calculated and plotted on the pertinent portion of a USGS quadrangle (page 5 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the calculated area of interference (Note: FCC 02-244, II, A, 6 states that USGS quadrangles are sufficient for demonstrating lack of population). Hence, in accordance with 47 CFR 74.1204(d) and the clarification provided by the FCC in the decision Re: Living Way Ministries (FCC 02-244), a lack of population has been demonstrated within the area of interference and therefore this application is in full compliance with 47 CFR 74.1204.

CORAGL: 81m

Maximum ERP: 0.019kW

F(50,10) Interfering Contour: 109.6dBu

F(50,10) Max Distance: 101.2m

Antenna Manufacturer: SCA

Antenna Model: CA5-FM/CP

Antenna Rotation: 300

The F(50,50) signal strength of all relevant second and third adjacent stations have been examined, and are tabulated below. Column three shows the station's signal level at the proposed translator's tower site, and column four gives the minimum value within the entire proposed translator's standard F(50,10) contour (100 dBu for most classes, 94 dBu for class B's, 97 dBu for class B1's). For signal levels too great to determine, 999 was entered. The minimum F(50,50) contour within the proposed translator's standard F(50,10) contour was used to calculate the proposed translator's interference contour, thereby assuring a minimum undesired-to-desired ratio of 40dB for all relevant adjacent stations, as required in 47 CFR, 74.1204(a).


FCC File Number	Call Sign	F(50,50) Contour at Tower	Min. F(50,50) Contour
BLH20020220AAC	KMXX	70.3dBu	69.6dBu
BLH20020903ABP	KGBA	94.2dBu	92.2dBu

Minimum F(50,50) Protected Contour of Adjacent Station
Within Proposed Translator's standard F(50,10) Contour: **69.6dBu**

Frequency Finder

Callsign	State	City	Channel	ERP_w	Licensee	ARN	Class	Status	Distance_km	Clr	Facility_id
KGBA	CA	HOLTVILLE	261	6000	THE VOICE OF INTERNATIONAL CHRISTIAN EVANGELISM, INC.	BLH20020903ABP	A	LIC	3.87	-34.85 dB	66640
KGBA	CA	HOLTVILLE	261	0	THE VOICE OF INTERNATIONAL CHRISTIAN EVANGELISM, INC.		A	USE	3.89	-10.82 dB	66640
KMXX	CA	IMPERIAL	257	6000	ENTRAVISION HOLDINGS, LLC	BLH20020220AAC	A	LIC	14.3	-10.83 dB	6665
KMXX	CA	IMPERIAL	257	0	ENTRAVISION HOLDINGS, LLC		A	USE	9.3	6.03 dB	6665
NEW	CA	CALIPATRIA	259	55	EDGEWATER BROADCASTING INC.	BNPFT20030317CVT	D	APP	37.76	9.99 dB	151336
NEW	AZ	YUMA	259	250	EDGEWATER BROADCASTING INC.	BNPFT20030317CTL	D	APP	86.83	14.67 dB	151315
	BN	ESPERANZA	206	3000			A		22.29	14.3	96134
XHBCNFM*	BN	TIJUANA	259	100000		FM ALLOTMENT	C1	USE	132.48	15.60 dB	-2
XHBCNFM	BN	TIJUANA	259	100000			C1		132.48	15.60 dB	94288
KJMB-FM	CA	BLYTHE	262	36000	J.S. MAYSON	BLH19861209KB	B	LIC	127.86	27.97 dB	29590
KMRJ	CA	RANCHO MIRAGE	258	3000	DANIEL P. MITCHELL	BLH19980724KA	A	LIC	137	27.41 dB	15475
NEW	AZ	YUMA	258	250	EDGEWATER BROADCASTING INC.	BNPFT20030317CTH	D	APP	86.83	28.67 dB	151309
NEW	AZ	YUMA	260	250	EDGEWATER BROADCASTING INC.	BNPFT20030317CTR	D	APP	86.83	28.67 dB	151322
XHBCNFM	BN	TIJUANA	259	25000			B1		138.33	28.01 dB	94288
	BN	TIJUANA	259	25000		RM	B1		138.33	28.01 dB	-2
KOLA	CA	SAN BERNARDINO	260	29500	INLAND EMPIRE BROADCASTING CORP.	BLH19910926KB	B	LIC	209.66	31.47 dB	55240
	BN	ENSENADA	262	50000			B		146.4	35.26 dB	95993
XHKYFM	BN	TIJUANA	257	25000			B1		144.57	36.10 dB	96466
XHKYFM	BN	TIJUANA	257	25000			B1		144.57	36.10 dB	96466
KLVJ	CA	JULIAN	261	110	EDUCATIONAL MEDIA FOUNDATION	BLED20011019AAN	A	LIC	109.54	38.43 dB	49854
XHATEFM	BN	TECATE	257	3000			A		107.38	39.83 dB	94903
	SO	PUERTO PENASCO	256	100000			C		249.83	39.32 dB	95888
XHATEFM	BN	TECATE	257	3000			A		108.39	39.83 dB	94903

Map Header



Map Footer

County Borders State Borders Highways Lat/Lon Grid