

TECHNICAL EXHIBIT
CONCERNING HUMAN EXPOSURE TO RF ELECTROMAGNETIC ENERGY
PREPARED FOR
STATION WWDP-DT
NORWELL, MASSACHUSETTS
CH 10 5 KW 142 M


Technical Statement

The proposed facilities were evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the proposed DTV antenna is located 149.2 meters above ground level. The maximum DTV ERP is 5 kW (horizontal polarization). A “conservative” vertical plane relative field value of 0.2 (for angles below 60 degrees downward) was presumed for the antenna's downward radiation (see Figure 2). The calculated power density at a point 2 meters above ground level is 0.0003 mW/cm^2 . This is 0.15% of the FCC's recommended limit of 0.20 mW/cm^2 for channel 10 for an “uncontrolled” environment. Therefore, based on the responsibility threshold of 5%, the proposal will comply with the RF emission rules.

Access to the transmitting site will be restricted and appropriately marked with RFR warning signs. Furthermore, in the event that workers or other authorized personnel enter the restricted area or climb the tower, appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing “accepted” RFR protective clothing and/or RFR exposure.

Finally, it is noted that this technical exhibit only addresses the potential for radio frequency electromagnetic field exposure. All other aspects of the

environmental processing analysis will be or already has been provided to the FCC by the tower owner as part of the tower registration process.



Jerome J. Manarchuck

du Treil, Lundin & Rackley, Inc.

201 Fletcher Avenue

Sarasota, Florida 34237-6019

(941) 329-6000

JERRY@DLR.COM

March 13, 2008



Proposal Number	C-02196	
Date	14-Dec-07	
Call Letters	WWDP-DT	Channel 10
Location	Norwell, MA	
Customer		
Antenna Type	THV-5A10-R O4	

ELEVATION PATTERN

RMS Gain at Main Lobe	5.00 (6.99 dB)	Beam Tilt	1.50 deg
RMS Gain at Horizontal	4.70 (6.72 dB)	Frequency	195.00 MHz
Calculated / Measured	Calculated	Drawing #	05V050150-90

