

EXHIBIT 30-1

WQYK-FM FCC 302-FM Application
Section III Certification
Environmental
CBS Radio Inc. of Florida
January 21, 2010

Measurements were made January 20, 2010, from 10:45AM to 11:45AM EST of the shared WQYK-FM transmitter site to determine whether the site is in compliance with the Commission's rules pertaining to RF exposure with the installation of the shared WQYK-FM and WRBQ-FM antenna. The antenna is a ERI model COG3-20P-8CP master FM antenna with -.5 degree beam tilt. Element bay spacing is .8 wavelength.

A Narda SRM-3000 Selective Radiation Meter and 3-axis broadband dipole antenna (30 mHz to 3 GHz.) were used for the survey. Both transmitters were operating at appropriate power levels to yield 100 kW ERP H & V from each station for a combined power density of 400 kW.

The property was scanned out to a distance of .25 km radius from the base of the tower. There were no areas on the ground that measured greater than 1% (peak reading) of the MPE for General Population. Therefore, no further analysis was made.

Based on the above measurements, the proposed transmitting facilities will continue to comply with the FCC guidelines limiting human exposure to radio frequency energy when the auxiliary antenna is in use. Accordingly, the proposed facility is categorically excluded by FCC Rules from having to consider the contributions of other stations at the site.

If work is done on the tower in an area where over exposure could occur, the Licensee in coordination with the other users will take necessary action to prevent the overexposure of workers on the tower including reducing the transmitting power or ceasing operation completely.

A handwritten signature in blue ink that reads "Edwin L. Nass". The signature is written in a cursive style with a large initial 'E' and 'N'.

Edwin L. Nass, Director of Spectrum Management

CBS Broadcasting