

Report Of Intermodulation Product Findings

**WQYK 99.5 MHz. St. Petersburg, FL.
WRBQ 104.7 MHz. Tampa, FL.**

Project# 24000

January 11, 2010

**Electronics Research Inc.
7777 Gardner Road
Chandler, Indiana 47610
Phone (812) 925-6000 Fax (812) 925- 4030**

TABLE OF CONTENTS

Report of Findings for Intermodulation Product Measurements

Page 3-4.....	Introduction
Page 5	Carrier Reference Levels
Page 5	Table of Third order Products Expected
Page 5	Intermodulation Product Measurements
Page 6	Conclusion
Page 7	Affidavit

Exhibits Accompanying This Report

EXHIBIT A	Antenna and Combiner Specification Sheet and Drawing
A-1.....	Drawing Depicting Antenna
A-2.....	ERI Antenna Specification Sheet
A-3.....	Drawing Depicting Combiner Module
A-4.....	ERI Combiner Specification Sheet
A-5.....	Theoretical Vertical Plane Relative Field Antenna Plots
EXHIBIT B-1	Intermodulation Product Measurement Equipment Layout
B-2.....	Broadcasting Scheme of the Multiplexed System

REPORT OF FINDINGS

WQYK / WRBQ

99.5 MHz. / 104.7 MHz.

Introduction: This report of findings is based on data collected at the WQYK and WRBQ broadcast facility located in Tampa, Florida. The report includes measurements offered as proof that the combined operations of WQYK (99.5 MHz.) and WRBQ (104.7) transmitters are in compliance with the FCC Rules and Regulations as required by the Code of Federal Regulations (CFR) Title 47 section 73.317 paragraph (b) through (d). In brief, the collection of measurements presented in this report shows that all possible third order inter-modulation (IM) products generated by this duplex system are less than the maximum allowable level as required by section 73.317 (b) through (d). Jeff Taylor of Electronics Research, Inc. located in Chandler, Indiana performed the measurements summarized herein on January 11, 2010.

The following exhibits are provided:

Exhibit A:

- A-1 Drawing Depicting Antenna.
- A-2 COG3-20P-8CP-2 Antenna Specification Sheet.
- A-3 Drawing Depicting Diplexed Scheme.
- A-4 973-8 Constant Impedance Combiner Specification Sheet.
- A-5 Theoretical Vertical Plane Relative Field Antenna Plots

Exhibit B:

- B-1 Equipment Employed In Intermodulation Product Measurement.
- B-2 Broadcasting Scheme of the Multiplexed Systems.

Table 1. Carrier Reference Levels.

Table 2. Calculated Third Order Products.

Table 3. Intermodulation Analysis Measurements.

Exhibits Accompanying Report: Exhibit A provides comprehensive information on both antenna and filters used by these radio stations. Exhibit B illustrates the broadcasting scheme of each station, the layout of the equipment used to isolate and measure potential intermodulation products and forward carrier reference levels. Found within Table 1 are the narrow band carrier frequency measurements that provide relative output signal levels for the IM analysis. Table 2 lists the calculated third order products that can be generated from FM transmitters broadcasting from the multiplexed system. The IM Analysis Measurements, in Table 3, provides detailed information obtained from the product frequency investigation.

The Nature of Intermodulation Products (IM): Intermodulation products result from inadequate transmitter-to-transmitter isolation. Intermodulation products are commonly generated from radio stations operating into multiplexed facilities and congested antenna broadcast sites. The mechanics associated with the phenomenon have been well documented. When two or more transmitters are coupled to each other, new spectral components are produced by the mixing of the station frequencies in the active circuits of each transmitter. The common term used to describe this phenomenon is third order product denoted by the mathematical expression $[2(F_1)-(F_2)]$, where F_1 signifies the frequency of the transmitter that is generating the intermodulation product, and F_2 signifies the frequency causing the interference.

The Multiplexed System: These measurements were taken with both FM stations operating from the combined antenna system. The WQYK and WRBQ multiplexed system is fundamentally comprised of antenna, feed line and multiplexer unit. The COG3-20P-8CP-2 (antenna), 973-8 combiner units, and 6 1/8" feedline are products of Electronics Research, Inc. Refer to Exhibit B-1, for an illustration of the Broadcasting Scheme of these stations.

To accomplish the aggregation of two transmitter signals into a common antenna feed and provide transmitter-to-transmitter isolation, a multiplexing scheme consisting of 973-8 Constant Impedance Combiner, filter system was installed. Specifically, the combiner utilizes two ERI Model 973-8 modules for each frequency (99.5 MHz. and 104.7 MHz.). An interconnecting "u-link" is required to complete the combiner which is illustrated in the attached Exhibit A-3. The multiplexer, fully assembled, exhibited transmitter port-to-port isolation in excess of -86 dB. Other performance measurements, such as match, loss, group-delay, etc, revealed that the multiplexer unit was in proper working condition. Refer to Exhibit A-4 for the Combiner Specification Sheet.

The IM Investigation: Directional Couplers were placed at key locations throughout the combiner to monitor and maintain the multiplexer's performance. All couplers furnished with the system are factory calibrated and capable of delivering accurate and repeatable RF measurements. To facilitate the taking of the measurements, the coupler located at the antenna output of the multiplexed system was used. Care was taken in the selection of the measurement location to insure that the measurements would be made far removed from transmitters and any filtering used to reduce broadcast emissions. The coupler selected would normally be used for antenna reflection measurements and thus would provide greater than -30 dB directivity and a forward signal sample of -45 dB.

The forward port of the coupler was used for sampling the outgoing carrier levels and IM products. The IM sampled signal was fed by shielded cable into a Band Pass Filter where all extraneous energy was steeply attenuated. Various attenuation pads were used, when needed, on the band pass filter and/or the Spectrum Analyzer to ensure an adequate signal level for measurements without overloading the measurement equipment. A Rohde & Schwarz ZVL Vector Network Analyzer with Spectrum Analyzer serial# 100396 was employed to record the level of all signals investigated. The Rohde & Schwarz was also used for selective tuning of the Band Pass Filter. The Spectrum Analyzer portion of the Rohde & Schwarz was used to measure the close in spectral attenuation of each carrier and wide band search for any anomalies that may need further investigation. See attached Exhibit B-1 for an illustration of the measurement equipment.

Prior to recording measurements, all pertinent broadcasting equipment including Transmitters, Multiplexer, Feed Line and Antenna were adjusted to optimal performance. Also, it was confirmed before taking any measurements that all transmitters were operating at full licensed power. From the equipment setup described above, the relative output signal level of each stations forward carrier was made. The resulting signal levels of these measurements are listed in Table 1, column labeled "Adjusted Level". This level will be used as the reference level for possible IM products of each carrier and was necessary to confirm that no significant levels of spurious energy, referenced to each carrier, were present from any transmitter operating from the multiplexed system.

Table 1 - Carrier Reference Levels.

Carrier Frequency (MHz)	Pad One (dB)	Bandpass Filter Loss (dB)	Measured Level (dBm)	Adjusted Level (dBμ)	Notes
WQYK 99.5	40	-	9.16	30.84	
WRBQ 104.7	40	-	9.53	30.47	

Predictable third-order products due to system harmonics mixed with all on-site interfering frequencies that could be generated from the multiplexed system are calculated and listed in Table 2.

Table 2 - Third order Products.

		Carrier Frequencies	
Interfering Frequencies		99.5	104.7
WQYK	99.5	----	109.9
WRBQ	104.7	94.3	----

Using the equipment previously described the IM product measurements were recorded and are listed in Table 3. The signal levels referenced to the carriers are calculated and listed in the column labeled "Level Referenced to Carrier". Refer to Exhibit B-2 for a layout of the measurement equipment.

Table 3 – Intermodulation Measurements

Product Frequency (MHz)	Transmitter Frequency (MHz)	Interfering Frequency (MHz)	Pad (dB)	Bandpass Filter Loss (dB)	Total Loss	Measured Level (dBm)	Carrier Reference Level (dBm) (See Table 1)	Level Referenced to Carrier (dB)	Notes*
94.3	99.5	104.7	3	10.9	13.9	-78.74	30.84	-95.68	
101.9	104.7	99.5	3	10.5	13.5	-84.16	30.47	-101.13	

The Spectrum Analyzer was used to check the close in spectral attenuation of the carrier to confirm the operation of the transmitter is in compliance with Sections (b) and (c) of the FCC Rules and Regulations.

As a final proof of the systems IM Product performance, a wide band search was undertaken using the Spectrum Analyzer. The purpose for this measurement was to look for suspicious anomalies that may warrant further investigation. My search ranged the complete frequency span of the receiver and resulted in no additional investigations.

Conclusion: Based upon my observations and measurements taken on January 11, 2010 as summarized in this document, I, Jeff Taylor, find the subject system, specifically the transmitter and filter system for the operation of WQYK and WRBQ into the antenna to be in proper working order. Furthermore, based on the measured data, it is my opinion that there are no inter-modulation products in excess of 80 dB below carrier levels generated from or within the station operating on the installed system. Based on this recorded data, I conclude that WQYK and WRBQ are in compliance with the requirements of Section 73.317 paragraph (b) through (d) of the FCC Rules and Regulations.

Respectfully submitted,
Electronics Research, Inc.

Jeff Taylor, Field Technician

AFFIDAVIT

WARRICK COUNTY)
) SS:
STATE OF INDIANA)

MARK STEAPLETON, being duly sworn upon oath deposes and says:

That his qualifications are a matter of record with the Federal Communications Commission;

That he is a Field Technician for Electronics Research, Inc., which is a manufacturer of FM broadcast antennas, and has been employed by ERI for 29 years. He is familiar with and has assisted in the design, manufacturing and installation of FM Antennas and FM Multiplexers in his long tenure with ERI.

That this corporation as been retained by CBS Radio, Inc on behalf of radio station WQYQ and WRBQ to prepare this engineering statement;

That he has either prepared or directly supervised the preparation of all technical information contained in this engineering statement and that the facts stated in this engineering statement are true of his knowledge except as such statements as are herein stated to be on information and belief and as to such statements he believes them to be true.


Mark Steapleton
Mark Steapleton

Subscribed and sworn to before me on this 15th day of January, 2010.


Cindy D. Tomes
Cindy D. Tomes
Notary Public

My commission expires November 6, 2014

(Seal)



EXHIBIT, A-1



A-2 ERI Antenna Specification Sheet

Tampa, FL.

General Specifications

Antenna Type High Power FM-Broadcast, Suitable For Multiplexing
 Model Number COG3-20P-8CP-2
 Number of Bay Levels Eight
 Polarization Circular Polarized

Electrical Specifications


Antenna Input Power Capability 64 kW Max ⁽¹⁾
 Operating Frequency Band 99.5 ~ 104.7 Megahertz.
 VSWR <1.04:1 @ Operating Frequencies ⁽²⁾
 Azimuthal Pattern Circularity Better Than +/- 1dB From RMS (Free Space)
 Power Split 50/50 (Horizontal & Vertical)
 Frequency Specific Information:

<u>Frequency</u>	<u>Station ERP</u>	<u>Beam Tilt</u>	<u>First Null Fill</u>	<u>Second Null Fill</u>	<u>Power Gain</u>	<u>Line Loss</u> ⁽³⁾	<u>Filter Loss</u> ⁽⁴⁾	<u>Computed TPO</u>
99.5	100 KW	-.5°	10 %	0 %	3.454	-0.289 dB	.207 dB	32.5 kW
104.7	100 KW	-.5°	11 %	0 %	3.594	-0.297 dB	.152 dB	31.0 kW

Mechanical Specifications

Antenna Feed System Fed With One 6 1/8" Line
 Input Connector 6 1/8"-50 Ohm EIA Flanged
 Element Deicing None
 Interbay Spacing 92 Center to Center
 Array Length 54 Feet
 Construction Material (Antenna) All Noncorrosive
 Construction Material (Mounting) All Stainless Steel

- 1) Power Capability Has Been Rated Assuming an Operating Transmission VSWR of 1.5:1
 2) VSWR Specification Achieved After On Site Tuning For User Specific Frequencies.
 3) Line Loss Assumes A Feed Run of 596 Feet, 6 1/8" ERI MACXLine.
 4) Losses Taken From Actual Combiner.



A-4 ERI Combiner Specification Sheet

Tampa, FL.

General Specifications:

Multiplexer Type973-8 Constant Impedance Combiner
Number of Combining Units Two
Injected Port to Injected Port Isolation < - 86 dB
Output Connector 6 1/8 "50 Ohm EIA (Flanged)
Output Power (Designed) 64 kW⁽¹⁾

Heat Removal Natural Convection
Physical Arrangement One Bank of Filters Floor Standing / Other Bank Elevated on Stands

Injected Port Specifications:

Frequency Assignment99.5 and 104.7 MHz.
Power Rating, Each Injected Port (Designed).....32.5 kW for 99.5 MHz.
Power Rating, Each Injected Port (Designed).....31.0 kW for 104.7 MHz.
Input Connector3-1/8" 50 Ohm EIA (Flanged).
VSWR.....< 1.07:1 @ +/-200 KHz.⁽²⁾
Group DelayLess than 75 ns Overall Variation, Carrier @ +/- 150 KHz.
Insertion Loss (Measured):


99.5 MHz. - 0.207 dB

104.7 MHz. - 0.152 dB


1) Power Rating Listed is as Designed Only. Actual Power Capabilities May Vary.


2) When Terminated in 50 Ohm Resistive Load.

PROPOSAL
CBS Radio
Quotation Number: TN8070310-RF-FL
Date Quoted: July 3, 2008
Page 14



PROPOSAL
CBS Radio
Quotation Number: TN8070310-RF-FL
Date Quoted: July 3, 2008
Page 15





Broadcasting Scheme and Equipment Employed in Intermodulation Measurements

EXHIBIT B