

GREG BEST CONSULTING, INC.

9223 N. Manning Avenue
Kansas City, MO 64157
816-792-2913

July 27, 2010

Federal Communications Commission
Media Bureau
445 12th Street SW
Washington, DC 20554

Dear Sir,

This will serve as the exhibit for the RF Radiation Hazard calculation for this proposed facility.

The RF radiation near the ground (2 meters above ground) can be calculated using the OET-65 formula for broadcast television stations taking into account the following factors

S= power density in watts per square meter

P= total Effective Radiated Power from the antenna

F= field radiated on the axis to the ground level

R= distance to the ground level (actually 2 meters above ground)

Therefore, given the following data for the proposed channel 33 facility:

P= 360 watts

R=Radiation center above ground level – 2 meters)
= 27.6 meters

F= 0.1 for UHF antennas

The RF radiation near the ground level can be calculated with the following result:

0.16 $\mu\text{watts/cm}^2$

which is 0.04 % of the general population exposure limit of 391 $\mu\text{w/cm}^2$

In addition to the proposed facilities, there are other sources of RF radiation on that tower. In particular, radiation comes from K06LE, K08KX, K15HD-LD, K21FD-LD, and K43IA. The contributions from each source are calculated below and then summed to get the total RF exposure for this tower.

K06LE (CH 06)

P= 56 watts

R=Radiation center above ground level – 2 meters)
= 22 meters

F= 0.2 for VHF antennas

The RF radiation near the ground level can be calculated with the following result:

0.15 $\mu\text{watts/cm}^2$

which is 0.08 % of the general population exposure limit of 200 $\mu\text{w/cm}^2$

K08KX (CH 08)

P= 73 watts

R=Radiation center above ground level – 2 meters)
= 13 meters

F= 0.2 for VHF antennas

The RF radiation near the ground level can be calculated with the following result:

$0.58 \mu\text{watts/cm}^2$

which is 0.29 % of the general population exposure limit of $200 \mu\text{w/cm}^2$

K15HD-LD (CH 15)

P= 289 watts

R=Radiation center above ground level – 2 meters)
= 30.5 meters

F= 0.1 for UHF antennas

The RF radiation near the ground level can be calculated with the following result:

$0.10 \mu\text{watts/cm}^2$

which is 0.03 % of the general population exposure limit of $319 \mu\text{w/cm}^2$

K21FD-LD (CH 21)

P= 2100 watts

R=Radiation center above ground level – 2 meters)
= 31 meters

F= 0.1 for UHF antennas

The RF radiation near the ground level can be calculated with the following result:

$0.72 \mu\text{watts/cm}^2$

which is 0.21 % of the general population exposure limit of $343 \mu\text{w/cm}^2$

K43IA (CH 43)

P= 6200 watts

R=Radiation center above ground level – 2 meters)
= 25 meters

F= 0.1 for UHF antennas

The RF radiation near the ground level can be calculated with the following result:

$1.64 \mu\text{watts/cm}^2$

which is 0.38 % of the general population exposure limit of $431 \mu\text{w/cm}^2$

TOTAL RF EXPOSURE

The total RF exposure can be obtained by summing the individual percentages. Thus the total RF exposure predicted is $0.08+0.29+0.03+0.21+0.38+0.04=1.03$ % of the General Population Exposure limit.

Should you have any questions regarding this information please contact me.

Sincerely,

A handwritten signature in cursive script, appearing to read "Raymond B. Smith".

President