

Norsan Consulting Co-Location on WEWC (AM) Tower

REFERENCE 30 22 28.0 N. 81 44 28.0 W.		CH# 248D - 97.5 MHz, Pwr= 0.25 kW DA, HAAT= 33.5 M, COR= 42 M Average Protected F(50-50)= 7.4 km Standard Directional								DISPLAY DATES DATA 05-16-17 SEARCH 05-16-17	
CH CITY	CALL	TYPE	ANT STATE	AZI. <--	DIST FILE #	LAT. LNG.	Pwr(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
245C0 WJGL Jacksonville		LIC	C FL	122.8 302.9	20.16 BMLH20130124AAR	30 16 34.0 81 33 53.0	100.000 309	10.3 315	73.2 Cox Radio, Inc.	7.8	-53.1*
250C2 WKSL Neptune Beach		LIC	CX FL	122.4 302.5	19.43 BMLH20120611ABM	30 16 51.0 81 34 13.0	12.500 302	5.4 308	52.4 Clear Channel Broadcasting	12.0	-33.0*
248D W248CT Callahan		CP	C FL	60.1 240.1	0.06 BMPFT20170511AAR	30 22 29.0 81 44 26.0	0.002	6.2 17	2.0 Norsan Consulting And Mana	-11.3*	-18.5*
247D W247CF Orange Park		LIC	C FL	122.7 302.8	20.20 BLFT20151224AAH	30 16 34.0 81 33 51.0	0.099	25.6 280	17.2 Delmarva Educational Assoc	-7.4*	0.5
248L1 WFBB-LP Glen St Mary		LIC		254.3 74.1	42.13 BLL20140106DON	30 16 17.0 82 09 46.0	0.100 27			16.2	16.0
247C2 WSKY-FM MI canopy		LIC NCX	FL	211.1 30.8	108.54 BLH20080402AAT	29 32 09.0 82 19 18.0	50.000 150	78.0 173	52.3 Entercom License, Lic	26.0	53.4

Terrain database is USGS 03 SEC, R= 73.215 qualifying spacings or FCC minimum spacings in KM, M= Margin in KM
In & Out distances between contours are shown at closest points. Reference Zone= East Zone, Co to 3rd adjacent.
All separation margins (if shown) include rounding.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C, H, V, E), Beamtilt(Y, N, X)
***affixed to 'IN' or 'OUT' values = site inside restricted contour.
Reference station has protected zone issue: AM tower

Clearance to third-adjacent WJGL and second-adjacent WKSL will be derived through the use of Section 74.1204 (d).

Bromo Communications, Inc.
