

Engineering Exhibit  
KRVI (FM)  
Facility ID 37001  
September 29, 2006

The proposed facilities were evaluated in terms of potential radio frequency radiation exposure at ground level in accordance with OET Bulletin No. 65, "Evaluating Compliance With FCC-Specified Guidelines for Human Exposure to Radio frequency Radiation."

The proposed antenna system is an ERI, LPX-4E, 4- bay, 1.0 wave spaced "Roto Tiller" style antenna, mounted with its center of radiation 137 meters above ground level. This proposal will operate with an effective radiated power of 15 kilowatts in both the horizontal and vertical planes. At 2 meters above ground, at 55 meters from the base of the tower, this proposal will contribute worst case 4.77 microwatts per square centimeter, or 0.477 percent of the allowable ANSI limit for controlled exposure, and 2.38 percent of the allowable limit for uncontrolled exposure. It is therefore believed that this proposal is in compliance with OET Bulletin Number 65 as required by the Federal Communications Commission.

Further, the applicant will see that signs are posted in the vicinity of the tower, warning of potential radio frequency hazards at the site. The applicant will cooperate with other users of the tower to reduce power of the facility, or discontinue operation, as necessary to limit human exposure to levels less than specified by the Federal Communications Commission should anyone be required to climb the tower for maintenance or inspection.