

WGAM Nighttime 210 Degree Radial

<u>Point #</u>	<u>Distance</u>	<u>1960</u> <u>Proof ND</u> <u>(mV/M)</u>	<u>1960</u> <u>Proof DA</u> <u>(mV/M)</u>	<u>Current</u> <u>DA</u> <u>(mV/M)</u>	<u>Ratio</u> <u>DA/'60 DA</u>	<u>Log Ratio</u> <u>DA/'60 DA</u>	<u>Point Description</u>
8	1.8	27	12	12.5	1.0417	0.0177	42-59-16.28, -71-31-21.79
9	3.1	10	2.35	2.6	1.1064	0.0439	42-58-20.98, -71-32-5.33
10 - MP	3.6	7	1.85	1.78	0.9622	-0.0168	42-57-47.91, -71-32-31.4
11	3.9	5	1.45	1.39	0.9586	-0.0184	42-57-41.98, -71-32-36.19
12	5.25	2.5	0.51	0.56	1.0980	0.0406	42-56-42.57, -71-33-22.85
13	6.45	1.3	0.35	0.42	1.2000	0.0792	42-55-53.25, -71-34-1.75
14	7	1.4	0.41	0.43	1.0488	0.0207	42-55-19.88, -71-34-27.96
15	9.15	0.56	0.12	0.15	1.2500	0.0969	42-53-45.02, -71-35-42.92
16	10.6	0.29	0.15	0.18	1.2000	0.0792	42-52-44.03, -71-36-30.79
17	11.3	0.27	0.09	0.1	1.1111	0.0458	42-58-5.68, -71-36-57.11
18	12.1	0.38	0.075	0.06	0.8000	-0.0969	42-51-33.25, -71-37-21.65
19	12.9	0.33	0.08	0.09	1.1250	0.0512	42-50-56.91, -71-37-54.78
							ND IDF = 190 mV/M
							NIGHT DA IDF = 48.2 mV/M
				Average:	1.0751		STANDARD PATTERN LIMIT: 171.6 mV/M
				Log Average:		0.0286	
				IDF (mV/M):	51.82	51.48	

WGAM Nighttime 210 Degree Radial

<u>Point #</u>	<u>Distance</u>	<u>1960 Proof ND (mV/M)</u>	<u>1960 Proof DA (mV/M)</u>	<u>Current DA (mV/M)</u>	<u>Ratio DA/'60 DA</u>	<u>Log Ratio DA/'60 DA</u>	<u>Point Description</u>
9 - MP	1.45	37.5	30	29.5	0.9833	-0.0073	43-1-14.01, -71-31-56.68
13	2.8	8.3	7	8	1.1429	0.0580	43-1-41.31, -71-33-13.66
14	4.3	5	3.95	3.9	0.9873	-0.0055	43-2-15.2, -71-34-48.79
15	4.95	5.1	4	3.7	0.9250	-0.0339	43-2-30.15, -71-35-30.94
16	5.5	2.85	2.35	2.15	0.9149	-0.0386	43-2-42.42, -71-36-5.43
17	7.2	1.45	1.2	1	0.8333	-0.0792	43-3-20.04, -71-37-51.64
18	8.5	0.72	0.63	0.6	0.9524	-0.0212	43-3-52.79, -71-39-23.81
20	12.9	0.39	0.34	0.35	1.0294	0.0126	43-5-32.86, -71-44-6.4
21	13.9	0.4	0.31	0.25	0.8065	-0.0934	43-5-55.1, -71-45-9.07
							ND IDF = 190 mV/M
							NIGHT IDF = 149.5 mV/M
				Average:	0.9528		STANDARD PATTERN LIMIT = 255.7 mV/M
				Log Average:		-0.0232	
				IDF (mV/M):	142.44	141.73	

WGAM Nighttime 210 Degree Radial

<u>Point #</u>	<u>Distance</u>	<u>1960 Proof ND (mV/M)</u>	<u>1960 Proof DA (mV/M)</u>	<u>Current DA (mV/M)</u>	<u>Ratio DA/84DA</u>	<u>Log Ratio DA/84DA</u>	<u>Point Description</u>
9	1.7	11	4.7	6.2	1.3191	0.1203	43-2-6.2, -71-30-46.86
12 - MP	3.4	8.8	2.57	2.38	0.9261	-0.0334	43-3-27.52, -71-31-18.47
14	5.1	2.3	0.68	0.89	1.3088	0.1169	43-4-53.96, -71-31-50.63
15	6.2	0.92	0.3	0.34	1.1333	0.0544	43-5-52.27, -71-32-12.18
16	6.5	1.5	0.45	0.365	0.8111	-0.0909	43-6-5.43, -71-32-16.98
17	7.25	1.2	0.3	0.36	1.2000	0.0792	43-6-43.77, -71-32-31.35
18	8.6	0.73	0.275	0.215	0.7818	-0.1069	43-7-53.74, -71-32-56.87
19	9.6	0.38	0.18	0.169	0.9389	-0.0274	43-8-42.17, -71-33-14.58
20	11.3	0.52	0.175	0.143	0.8171	-0.0877	43-10-9.91, -71-33-36.08
							ND IDF = 190 mV/M
				Average:	1.0263		NIGHT IDF = 61.2 Mv/M
				Log Average:		0.0027	STANDARD PATTERN LIMIT = 112.7 mV/M
				IDF (mV/M):	62.81	61.58	