

**RF CERTIFICATION**  
**AND STATEMENT**

The proposed antenna system will be energized such that it produces 0.25 KW ERP, from the center of radiation of 54 meters above ground. The applicant will employ a single (1) bay SWR FM1-1 antenna system based on the formulas expressed in OET bulletin No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields" published by the Federal Communications Commission's Office of Engineering and applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**"). The highest calculated power density can be found at 14.48 meters from the tower and two (2) meters above ground. At this location, the value is 3.444 Microwatts per square centimeter. Since the tower site is fenced with a locked gate, (inaccessible to the public) this value amounts to 0.3445 percent of the maximum for a "controlled" environment. In an uncontrolled environment, a value of 1.7223 percent of the maximum amount. This proposal is in full compliance with all applicable FCC rules. These calculations were performed using the V-Soft Communications RFHaz3 program.

The proposed antenna system will be co-located on the same supporting structure as WXAG-AM. Pursuant to section 1.1307 (b) of the Commission's rules, the power density contribution of a co-located or nearby broadcast facility are not required to be calculated as the proposed density is less than five (5) percent of maximum allowed.

Should work be required on the supporting structure where exposure would be greater than the maximum allowed, the applicant would lower power or cease operation until the work is completed.

Regarding compliance with the nationwide programmatic agreement and NHPA Section 106 for tower co-location, the applicant has been informed by the FCC staff that compliance with the agreement is not required when: 1) the supporting structure was constructed prior to March 16, 2001; and 2) no new tower construction is proposed; and 3) the tower is not being substantially altered. Specifically, compliance is NOT necessary where an antenna and feed line are being attached to an existing structure. ***The proposed will NOT modify or change the existing structure.***

/s/ Clyde Scott  
EME Communications.

.

Phelps-Dodge "Ring Stub" EPA-Typ 1, 1 Bay, Spac= 1, H=.25 kW, V=.25 kW, 54 M AG

