



Doug Vernier
Telecommunications
Consultants

dvernier@v-soft.com
www.v-soft.com

721 W. 1st Street, Suite A
Cedar Falls, IA 50613
319-266-8402

Exhibit #9, Attachment E

**KVSS
License to Cover Application
Special Operating Conditions
As Established in BPED-20020425AAM**

**Theoretical vs. As –Built Pattern Relative Field Comparison
Vertical Plane**

Azimuth	Theoretical	As-Built
0	1.000	0.885
10	1.000	0.905
20	1.000	0.920
30	1.000	0.920
40	1.000	0.910
50	1.000	0.900
60	1.000	0.900
70	1.000	0.930
80	1.000	0.970
90	1.000	1.000
100	1.000	1.000
110	1.000	0.970
120	1.000	0.875
130	1.000	0.760
140	0.943	0.650
150	0.793	0.550
160	0.630	0.465
170	0.501	0.385

Azimuth	Theoretical	As-Built
180	0.400	0.320
190	0.340	0.285
200	0.310	0.260
210	0.289	0.255
220	0.289	0.260
230	0.310	0.290
240	0.380	0.350
250	0.479	0.440
260	0.602	0.540
270	0.758	0.645
280	1.000	0.770
290	1.000	0.875
300	1.000	0.960
310	1.000	1.000
320	1.000	0.995
330	1.000	0.950
340	1.000	0.905
350	1.000	0.885

The relative field strengths of the measured vertically polarized radiation component do not exceed at any azimuth the value indicated on the composite radiation pattern authorized under BPED-20020425AAM.

The horizontally polarized radiation component is omni-directional with 85 watts ERP, or 0.238 relative field, which is not exceeded at any azimuth by the as-built pattern.

The R.M.S. calculations submitted by Shively Labs in Attachment B of this exhibit have been confirmed by this office.