

EXHIBIT 13

Waiver Request of Section 74.1204

NEW BNPFT-20030310AWY Channel 288 and 55 Watts ERP

Calvary Chapel of Twin Falls, Inc.

3/2013

The proposed site is contained entirely inside the service contour of second-adjacent FM Station WNRQ Nashville, TN

WNRQ

The proposed site is contained entirely inside the service contour of second-adjacent FM Station WNRQ 290C, 100kW, Nashville, TN. The level of least arriving protected F(50,50) signal at the proposed transmitter site is 93.7-dBu. Using the U/D method for calculating proposed interference, the contour is 133.7-dBu (free-space contour method employed). The interfering signal would, in the worst case at the maximum radial, would extend 11 meters from the center of radiation, which is proposed at 80 meters AGL. This tower is located next to an interchange in an industrial area where there are no tall buildings. Attached is a portion of the USGS Topographic Map Nashville West (TN) and a Google Earth showing. This interference contour does not touch the ground and begins 69 meters AGL. There are no residences, businesses or major roadways that are located within this interference contour, therefore Calvary Chapel of Twin Falls, Inc. respectfully requests a waiver of the FM translator contour overlap regulations with respect to second-adjacent FM Station WNRQ Nashville.

Nashville, TN Channel 288 Minor Site Change

Calvary Chapel Of Twin Falls, Inc.

REFERENCE
36 10 37.0 N.
86 46 41.0 W.

CH# 288D - 105.5 MHz, Pwr= 0.055 kW, HAAT= 42.0 M, COR= 206 M
Average Protected F(50-50)= 5.72 km
Omni-directional

DISPLAY DATES
DATA 03-05-13
SEARCH 03-05-13

CH CITY	CALL	TYPE ANT STATE	AZI <--	DIST FILE #	LAT LNG	PWR(kW) HAAT(M)	INT(km) COR(M)	PRO(km) LICENSEE	*IN* (Overlap in km)	*OUT*
290C Nashville	WNRQ	LIC_CY TN	202.1 22.0	16.93 BLH19831212AN	36 02 08.0 86 50 56.0	100.000 376	11.7 611	80.7 Capstar Tx Lic	0.4	-64.3*
288D Goodlettsville	632592	APP_V_ TN	346.9 166.9	10.09 BNPFT20030310AWY	36 15 56.0 86 48 13.0	0.010 195	29.5 372	8.9 Calvary Chapel	-24.2*	-14.2 Of Twin Fal
288D Lebanon	W288BG	LIC_C_ TN	93.6 273.9	36.26 BLFT20061101ADK	36 09 20.0 86 22 33.0	0.010 151	23.3 337	6.9 Calvary Chapel	6.1	6.4 Of Twin Fal
286C2 Waverly	WVRY	LIC_CN TN	263.1 82.6	77.70 BLH19890619KB	36 05 25.0 87 38 05.0	50.000 150	5.5 355	48.7 Grace Broadcasting	64.9	28.5 Service
288A Fayetteville	WYTM-FM	LIC_C_ TN	171.2 351.4	117.80 BMLH20070327ACG	35 07 39.0 86 34 49.0	6.000 90	84.3 338	26.4 Time Broadcasters, Inc.	28.5	75.0
285A Woodbury	WBOZ	LIC_NCN TN	124.8 305.2	68.15 BLH19970214KB	35 49 33.0 86 09 28.0	6.000 100	3.5 352	36.6 Reach Satellite Network	58.8	31.1
287C3 Glasgow	WPTQ	LIC_ZCX KY	33.8 214.2	107.72 BLH20080818ACD	36 58 50.0 86 06 10.0	15.000 132	62.1 329	41.7 Newberry Broadcasting, Inc	39.5	57.2
288A Greenville	WKYA	LIC_DEN KY	341.3 161.1	119.49 BLH19811207AE	37 11 45.0 87 12 38.0	3.000 91	70.1 238	20.9 Starlight Broadcasting Co.	44.6	83.1
288A Paris	WAKQ	LIC_NCN TN	275.1 94.2	141.05 BLH19901219KB	36 16 45.0 88 20 31.0	3.700 128	86.4 273	29.9 Wenk Of Union City, Inc.	47.4	86.8
287A Morrison	WOWC	LIC_CX TN	127.4 307.9	100.68 BLH20080514AAP	35 37 27.0 85 53 37.0	6.000 74	40.1 402	26.0 Peg Broadcasting, Lic	54.9	66.6

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
Contour distances are on direct line to and from reference station. Reference zone= , Co to 3rd adjacent.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
"*"affixed to 'IN' or 'OUT' values = site inside protected contour.



