



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

BIRACH BROADCASTING CORPORATION
21700 NORTHWESTERN HWY STE 1190
TOWER 14
SOUTHFIELD MI 48075

Son Nguyen
Son Nguyen
Supervisory Engineer
Audio Division
Media Bureau

Facility Id: 22045

Call Sign: WPON

Permit File Number: BP-20180516AAA

Grant Date: **OCT 10 2018**
This permit expires 3:00 a.m.
local time, 36 months after the
grant date specified above.

This permit modifies BL-20150330AAI. The daytime facility is the same as in expired construction permit BP-20150330AAI, but now class B as night power and radiation pattern increased.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998).

Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
Local Standard Time (Non-Advanced)

Jan.	8:00 AM	5:30 PM	Jul.	5:15 AM	8:15 PM
Feb.	7:30 AM	6:00 PM	Aug.	5:45 AM	7:30 PM
Mar.	6:45 AM	6:45 PM	Sep.	6:15 AM	6:45 PM
Apr.	6:00 AM	7:15 PM	Oct.	6:45 AM	6:00 PM
May	5:15 AM	7:45 PM	Nov.	7:30 AM	5:15 PM
Jun.	5:00 AM	8:15 PM	Dec.	8:00 AM	5:00 PM

Callsign: WPON

Permit No.: BP-20180516AAA

Name of Permittee: BIRACH BROADCASTING CORPORATION

Station Location: WALLIED LAKE, MI

Frequency (kHz): 1460

Station Class: B

Antenna Coordinates:

Day

Latitude: N 42 Deg 32 Min 39 Sec

Longitude: W 83 Deg 33 Min 36 Sec

Night

Latitude: N 42 Deg 32 Min 39 Sec

Longitude: W 83 Deg 33 Min 36 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 0.67 Night: 0.58

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No. ASRN

1 None 60.6

2 None 60.6

3 None 60.6

4 None 60.6

Night:

Tower No. ASRN

1 None 60.6

2 None 60.6

3 None 60.6

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km) : Day: 235.84 Night: 256.93

Standard RMS (mV/m/km) : Day: 274.85 Night: 269.98

Augmented RMS (mV/m/km) :

Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	104.1
2	0.6300	-71.000	113.2000	63.500	0	104.1
3	0.5300	-6.000	186.0000	173.000	0	104.1
4	0.3340	-77.000	113.2000	63.500	1	104.1

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.6170	-119.200	0.0000	0.000	0	104.1
2	1.0000	0.000	93.0000	173.000	0	104.1
3	0.5600	159.500	186.0000	173.000	0	104.1

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:
14	168.1 mV/m
205	60.9 mV/m
321.5	127.4 mV/m

Night:

Azimuth:	Radiation:
86.5	106.3 mV/m
141.5	87.2 mV/m
204.5	87.2 mV/m
259.5	106.3 mV/m

Special operating conditions or restrictions:

- 1 The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.
- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 3 Ground system consists of 120 equally spaced, buried, copper radials about the base of each tower, each 64.6 meters in length (about towers 1 and 2), and 51.3 meters in length (about all remaining towers), except where terminated by property boundaries or where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers.
- 4 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 5 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.

Special operating conditions or restrictions:

- 6 Before program tests are authorized, sufficient data shall be submitted to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations WPON Walled Lake, MI (Facility ID #22045) and WCXI, Fenton, Michigan (Facility ID # 10475) , and there shall be filed with the license application copies of a firm agreement entered into by the two(2)

stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, Stations WPON Walled Lake, MI (Facility ID #22045) and WCXI, Fenton, Michigan (Facility ID # 10475) shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.

- 7 A proof of performance based on field strength measurements, per Section 73.151(a) , shall include a complete nondirectional proof of performance, in addition to a complete proof on the day and night directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.

Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c) , must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (1).

- 8 Prior to construction of the tower authorized herein, permittee shall notify AM Station WCXI, Fenton, Michigan (Facility ID # 10475) so that, if necessary that AM station: may determine operating power by a method described in Section 73.51(a) (1) or (d) , and/or request temporary authority from the Commission in Washington, D.C. to operate with parameters at variance in order to maintain monitoring point field strengths within authorized limits. Permittee shall be responsible for installation and continued maintenance of detuning apparatus necessary to prevent adverse effects upon the radiation pattern of the AM station. Both prior to construction of the tower and subsequent to the installation of all appurtenances thereon, a partial proof of performance, as defined by Section 73.154(a) of the Commission's Rules, shall be conducted to establish that the AM array has not been adversely affected and prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission.

*** END OF AUTHORIZATION ***