

Relative Field Tabulation

Elev.	Angle	Rel. Fld(dB)	Elev.	Angle	Rel. Fld(dB)	Elev.	Angle	Rel. Fld(dB)
6.2	.593	(-4.538)	-1.4	.976	(-0.208)	-9.0	.265	(-11.537)
6.0	.616	(-4.215)	-1.6	.969	(-0.272)	-9.2	.242	(-12.325)
5.8	.638	(-3.909)	-1.8	.961	(-0.345)	-9.4	.219	(-13.181)
5.6	.659	(-3.617)	-2.0	.952	(-0.427)	-9.6	.197	(-14.119)
5.4	.681	(-3.34)	-2.2	.942	(-0.518)	-9.8	.175	(-15.154)
5.2	.702	(-3.077)	-2.4	.931	(-0.617)	-10.0	.153	(-16.311)
5.0	.722	(-2.827)	-2.6	.92	(-0.727)	-10.2	.132	(-17.621)
4.8	.742	(-2.59)	-2.8	.907	(-0.845)	-10.4	.11	(-19.133)
4.6	.762	(-2.366)	-3.0	.894	(-0.973)	-10.6	.09	(-20.923)
4.4	.78	(-2.154)	-3.2	.88	(-1.111)	-10.8	.07	(-23.123)
4.2	.799	(-1.953)	-3.4	.865	(-1.258)	-11.0	.05	(-25.993)
4.0	.816	(-1.763)	-3.6	.85	(-1.416)	-11.2	.031	(-30.166)
3.8	.833	(-1.584)	-3.8	.833	(-1.584)	-11.4	.012	(-38.116)
3.6	.85	(-1.416)	-4.0	.816	(-1.763)	-11.6	.006	(-44.992)
3.4	.865	(-1.258)	-4.2	.799	(-1.953)	-11.8	.023	(-32.725)
3.2	.88	(-1.111)	-4.4	.78	(-2.154)	-12.0	.04	(-27.96)
3.0	.894	(-0.973)	-4.6	.762	(-2.366)	-12.2	.056	(-24.995)
2.8	.907	(-0.845)	-4.8	.742	(-2.59)	-12.4	.072	(-22.864)
2.6	.92	(-0.727)	-5.0	.722	(-2.827)	-12.6	.087	(-21.218)
2.4	.931	(-0.617)	-5.2	.702	(-3.077)	-12.8	.101	(-19.891)
2.2	.942	(-0.518)	-5.4	.681	(-3.34)	-13.0	.115	(-18.791)
2.0	.952	(-0.427)	-5.6	.659	(-3.617)	-13.2	.128	(-17.861)
1.8	.961	(-0.345)	-5.8	.638	(-3.909)	-13.4	.14	(-17.063)
1.6	.969	(-0.272)	-6.0	.616	(-4.215)	-13.6	.152	(-16.373)
1.4	.976	(-0.208)	-6.2	.593	(-4.538)	-13.8	.163	(-15.771)
1.2	.983	(-0.153)	-6.4	.57	(-4.878)	-14.0	.173	(-15.244)
1.0	.988	(-0.106)	-6.6	.547	(-5.235)	-14.2	.182	(-14.782)
.8	.992	(-0.068)	-6.8	.524	(-5.612)	-14.4	.191	(-14.375)
.6	.996	(-0.038)	-7.0	.501	(-6.008)	-14.6	.199	(-14.018)
.4	.998	(-0.017)	-7.2	.477	(-6.427)	-14.8	.206	(-13.706)
.2	1.00	(-0.004)	-7.4	.454	(-6.868)	-15.0	.213	(-13.434)
.0	1.00	(0)	-7.6	.43	(-7.335)	-15.2	.219	(-13.199)
-.2	1.00	(-0.004)	-7.8	.406	(-7.828)	-15.4	.224	(-12.997)
-.4	.998	(-0.017)	-8.0	.382	(-8.351)	-15.6	.228	(-12.828)
-.6	.996	(-0.038)	-8.2	.359	(-8.907)	-15.8	.232	(-12.688)
-.8	.992	(-0.068)	-8.4	.335	(-9.499)	-16.0	.235	(-12.576)
-1.0	.988	(-0.106)	-8.6	.311	(-10.131)	-16.2	.237	(-12.49)
-1.2	.983	(-0.153)	-8.8	.288	(-10.808)	-16.4	.239	(-12.43)

Systems With Reliability Inc.

Page 1 of 1

CLIENT: WOLR-FM

Date: 6/18/02

ANTENNA TYPE: FM3V/5 DA Exhibit 2

FREQUENCY: 91.3

PATTERN POL.: Vertical

DIRECTIVITY(Peak) 5.19/7.152 dBd

Beam Tilt (Deg.) : 0

DIRECTIVITY(Horiz) 5.19/7.152 dBd

Null Fill(s)(%) 0, 0, 0