



**SECTION III - Page 2**

9. Description of antenna system ((f directional antenna is used, the information requested below should be given for each element of the array. Use separate sheets if necessary.)

Type Radiator three guyed, uniform, cross-section, steel towers of equal height mounted on base piers and insulators	Overall height in meters of radiator above base insulator, or above base, if grounded. T1: 56.1 m T2: 56.1 m T3: 56.1 m	Overall height in meters above ground (without obstruction lighting) T1: 57.3 m T2: 57.3 m T3: 57.3 m	Overall height in meters above ground (include obstruction lighting) T1: 57.3 m T2: 58.2 m T3: 57.3 m	If antenna is either top loaded or sectionalized, describe fully in an Exhibit. <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 0 auto;">Exhibit No.</div>
---	---	---	---	--

Excitation  Series  Shunt ASR T1 = 1240874 ASR T3 = 1240876  
ASR T2 = 1240875

Geographic coordinates to nearest second. For directional antenna give coordinates of center of array. For single vertical radiator give tower location.

North Latitude	41 °	54 '	34 "	West Longitude	85 °	00 '	21 "
----------------	------	------	------	----------------	------	------	------

If not fully described above, attach as an Exhibit further details and dimensions including any other antenna mounted on tower and associated isolation circuits.

Exhibit No.

Also, if necessary for a complete description, attach as an Exhibit a sketch of the details and dimensions of ground system.

Exhibit No.


10. In what respect, if any, does the apparatus constructed differ from that described in the application for construction permit or in the permit?

No changes to the AM radiating tower or AM array have been implemented other than the addition of the FM translator antenna as authorized under W238CD – Coldwater, MI Construction Permit BMPFT-20111129DNU.

11. Give reasons for the change in antenna or common point resistance.

This Form 302-AM is being filed to reflect a new daytime antenna resistance measurement and nighttime common point measurement taken after the recent tower modifications associated with, and as a §73.1692(a) condition of licensing for, FM translator W238CD – Coldwater, MI, Construction Permit BMPFT-20111129DNU. In addition to the antenna mounting and subsequent AM antenna retuning and partial proof of performance measurements, general maintenance was performed on the AM sampling and monitoring system at that time as well.

I certify that I represent the applicant in the capacity indicated below and that I have examined the foregoing statement of technical information and that it is true to the best of my knowledge and belief.

Name (Please Print or Type) Justin W. Asher	Signature (check appropriate box below) 
Address (include ZIP Code) P.O. Box 220 385 Airport Drive Coldwater, MI 49036	Date January 13, 2012  Telephone No. (Include Area Code) 1(517)278-7339

- Technical Director  Registered Professional Engineer
- Chief Operator  Technical Consultant
- Other (specify)

**ENGINEERING REPORT**

**PARTIAL PROOF  
OF PERFORMANCE**

on

**WTVB(AM) – Coldwater, MI**  
Facility ID No. 67757

In response to  
W238CD - Coldwater, MI  
Translator Construction Permit  
File No. BMPFT-20111129DNU

January, 2012

COPYRIGHT 2012

**MUNN-REESE, INC.**  
Broadcast Engineering Consultants  
Coldwater, MI 49036

# **Table of Contents**

---

1. Table of Contents
2. Certification of Engineer
3. Discussion of Report
4. Exhibit 1.1 -Tabulation of Nighttime Radials 96.0°T & 115.0°T
5. Exhibit 1.2 -Tabulation of Nighttime Radials 163.0°T & 222.0°T
6. Exhibit 2.1 -Tabulation of Nighttime Ratios and Monitor Point Limits
7. Exhibit 3.1 - Vertical Plan of Recent Construction to AM Array
8. Exhibit 4.1 - Diagram of Phasing and Antenna Coupling Equipment of Recent Construction to AM Array

# Certification of Engineers

The firm of Munn-Reese, Inc., Broadcast Engineering Consultants, with offices at 385 Airport Drive, Coldwater, Michigan, has been retained for the purpose of preparing the technical data forming this report.

The data utilized in this report is based on field measurements made by the undersigned, or others under the supervision of the undersigned, on the dates and times indicated in the report.

The report has been prepared by properly trained electronics specialists under the direction of the undersigned whose qualifications are a matter of record before the Federal Communications Commission.

I declare under penalty of perjury that the contents of this report are true and accurate to the best of my knowledge and belief.

January 13, 2012

**MUNN-REESE, INC.**

By Wayne S. Reese  
Wayne S. Reese, President

By Edmond R. Trombley  
Edmond R. Trombley, Project Engineer

By Justin W. Asher  
Justin W. Asher, Project Engineer

385 Airport Drive, PO Box 220  
Coldwater, Michigan 49036

Telephone: 517-278-7339

**MUNN-REESE, INC.**  
Broadcast Engineering Consultants  
Coldwater, MI 49036

# **Discussion**

---

The firm of Munn-Reese, Inc., was retained to prepare this report detailing a Partial Proof of Performance on AM Radio Station WTVB(AM) – Coldwater, MI (Facility ID No. 67757), License No. BZ-19970924KC, as required by Special Condition/Restriction (3) on W238CD – Coldwater, MI (Facility ID No. 156715) Construction Permit File No. BMPFT-20111129DNU. The W238CD Construction Permit authorizes colocation of the FM Translator onto the center tower of the three (3) tower WTVB(AM) array, and operation W238CD as a Fill-In Translator rebroadcasting WTVB(AM).

WTVB(AM) – Coldwater, MI currently operates on 1590 kHz with 5.0 kW of daytime non-directional power and 1.0 kW of nighttime directional power employing a three (3) tower array. W238CD is authorized to operate with 0.250 kW (H&V) of non-directional power at 362 meters AMSL (54 meters AGL). As stated before the W238CD antenna will be mounted on the center tower of the WTVB(AM) three (3) tower array while rebroadcasting WTVB(AM) as an AM Fill-In Translator.

Nighttime directional field strength measurements were conducted by Mr. Edmond R. Trombley, an engineer in the employ of Munn-Reese, Inc. Mr. Trombley made his measurements using Potomac Instruments Field Intensity Meter, Model #FIM-21, Serial Number 1307. This meter was last calibrated March 21, 2011.

Measurements were taken on the four (4) nighttime monitor point radials, meeting the requirements of 47 C.F.R. §73.154 of the FCC Rules. Directional field strength measurements were taken on the dates and at the times indicated in the respective Tabulations of Field Strength Measurements, shown as **Exhibit(s) 1.1–1.2**. The tabulation sheets show the distance from the transmitter site to each point in units of kilometers and miles. The locations and point numbers for the 2012 nighttime directional measurements were derived from topographical maps used in the most recent full proof of performance as submitted in 1962. Handheld GPS equipment was also utilized in the measurement project. Isolated and minor distance errors were noted on a few select points between the 1962 proof tabulations and 1962 proof mapping. In instances where distance discrepancies were noted, conscientious effort was taken to best replicate the exact 1962 proof located as based on proof field mapping and field file notes. Suspected discrepancies have been noted as such in the supplied tabulations. .

The 1962 directional measurements were taken directly from the original 1962 proof as well, however, Antenna Monitor values and Monitor Point limits were taken from the most recent WTVB(AM) BZ-19970924KC Direct Measurement of Power license filing.

**Exhibit(s) 2.1** provides a summary of the field intensity measurements made on the nighttime directional operation as well as tabulations of the current Monitor Point values and limits. The Monitor Point field values remain within the allowable parameters.

A vertical plan of the W238CD Translator mounting on the WTVB(AM) Array has been included as **Exhibit 3.1**. The W238CD broadcasting element consists of a two (2) bay Shively 6812B-2 antenna. The feedline crosses the AM base pier and insulator via a Kintronics™ FMC 1.5 AM isocoupler. A revised diagram of phasing and antenna coupling equipment including the W238CD mounting has been included as **Exhibit 4.1**.

As stated before, partial proof measurements were made after the translator antenna installation with general maintenance performed on the AM sampling and monitoring system at that time as well. A slight retuning of the AM phasor was required, however the resulting operating parameters remain wholly within the nighttime standard (augmented) pattern as presently authorized. The WTVB(AM) operation also remains within tolerances of the WTVB(AM) Form 302-AM Direct Measurement of Power as concurrently submitted with this partial proof of performance. In light of the measurements taken and uniform results obtained, the recent FM Translator constructions for BMPFT-20111129DNU is believed to have had a negligible effect on the WTVB(AM) nighttime operation.



# Exhibit 1.2

## Tabulation of Nighttime Radial(s) 163.0°T & 222.0°T

<b>Call:</b>	<b>WTVB</b>			<b>Frequency (kHz):</b>			<b>1590</b>		<b>Power (kW):</b>			<b>1.0 kW</b>	
				<b>Bearing (°T):</b>			<b>163.0</b>						
<b>Point</b>	<b>1962 Day Proof Directional</b>			<b>2012 Day Directional</b>			<b>Distance</b>	<b>Distance</b>	<b>Direct</b>		<b>Log</b>		
<b>#</b>	<b>mV/m</b>	<b>Time</b>	<b>Date</b>	<b>mV/m</b>	<b>Time</b>	<b>Date</b>	<b>km</b>	<b>mi</b>	<b>Ratio</b>		<b>Ratio</b>		
19	14.80	---	1962	13.75	1410	01/11/12	2.99	1.86	0.9291			-0.0736	
20	9.10	---	1962	8.50	1413	01/11/12	4.66	2.90	0.9341	MP		-0.0682	
21	7.06	---	1962	6.70	1417	01/11/12	5.95*	3.70*	0.9490			-0.0523	
22	4.68	---	1962	4.20	1420	01/11/12	9.01*	5.60*	0.8974			-0.1082	
23	3.42	---	1962	3.20	1424	01/11/12	9.49*	5.90*	0.9357			-0.0665	
26	1.93	---	1962	1.80	1510	01/11/12	13.20	8.20	0.9326			-0.0697	
27	1.09	---	1962	1.00	1513	01/11/12	15.77	9.80	0.9174			-0.0862	
28	0.91	---	1962	0.81	1517	01/11/12	17.70	11.00	0.8901			-0.1164	
29	0.88	---	1962	0.80	1525	01/11/12	18.99	11.80	0.9091			-0.0953	
									<b>Arithmetic Ratio:</b>		<b>0.9216</b>		
									<b>Log Ratio:</b>		<b>0.9214</b>		

\* Denotes suspected distance error in 1962 Proof Tabulations

<b>Call:</b>	<b>WTVB</b>			<b>Frequency (kHz):</b>			<b>1590</b>		<b>Power (kW):</b>			<b>1.0 kW</b>	
				<b>Bearing (°T):</b>			<b>222.0</b>						
<b>Point</b>	<b>1962 Day Proof Directional</b>			<b>2012 Day Directional</b>			<b>Distance</b>	<b>Distance</b>	<b>Direct</b>		<b>Log</b>		
<b>#</b>	<b>mV/m</b>	<b>Time</b>	<b>Date</b>	<b>mV/m</b>	<b>Time</b>	<b>Date</b>	<b>km</b>	<b>mi</b>	<b>Ratio</b>		<b>Ratio</b>		
19	4.20	---	1962	1.60	1306	01/11/12	3.83	2.38	0.3810	MP		-0.9651	
20	1.45	---	1962	1.00	1310	01/11/12	5.39	3.35	0.6897			-0.3716	
21	1.07	---	1962	0.41	1313	01/11/12	6.03	3.75	0.3832			-0.9593	
22	0.95	---	1962	0.36	1317	01/11/12	7.64	4.75	0.3789			-0.9704	
23	0.66	---	1962	0.34	1322	01/11/12	9.09	5.65	0.5152			-0.6633	
24	0.49	---	1962	0.28	1328	01/11/12	10.46	6.50	0.5714			-0.5596	
25	0.42	---	1962	0.16	1332	01/11/12	10.94	6.80	0.3810			-0.9651	
26	0.22	---	1962	0.11	1337	01/11/12	12.63	7.85	0.5000			-0.6931	
27	0.114	---	1962	0.105	1342	01/11/12	14.96	9.30	0.9211			-0.0822	
									<b>Arithmetic Ratio:</b>		<b>0.5246</b>		
									<b>Log Ratio:</b>		<b>0.5005</b>		

## Exhibit 2.1 Tabulation of Nighttime Ratios

---

### Nighttime Operation:

Tabulation of Partial Proof Measurements				
Azimuth (° True)	1962 Full Proof DA (mV/m/km)	62 DA/12 DA (Log Ratio)	2012 Partial Proof DA (mV/m/km)	Augmented Pattern (mV/m/km)
96.0°T	20.92	0.9782	20.46	24.14
115.0°T	8.53	0.6747	5.76	24.14
163.0°T	80.47	0.9214	74.15	82.08
222.0°T	24.14	0.5005	12.08	24.14

Tabulation of Monitor Point Values			
Radial	1962 Proof MP Values (mV/m)	2012 Partial MP Value (mV/m)	Licensed MP Limits (mV/m)
96.0°T	8.77	9.50	14.00
115.0°T	1.14	2.60	4.40
163.0°T	9.10	8.50	11.30
222.0°T	4.20	1.60	4.80

Tabulation of Antenna Monitor Values		
	Licensed Values	2012 Partial Values
Transmitter Power	1,000 watts	1,000 watts
Common Point	4.65 amperes	4.65 amperes
Antenna Monitor	Current	Current
Tower #1	0.365	0.360
Tower #2	1.000	1.000
Tower #3	0.500	0.600
Antenna Phase	Degrees	Degrees
Tower #1	-128.0°	-124.0°
Tower #2	0.0°	000.0°
Tower #3	+128.0°	+128.0°

# Exhibit 3.1

## Vertical Plan of Antenna System

The site is located at 182 North Angola Road,  
the city of Coldwater, Branch County, Michigan.

### Site Location (NAD 27)


NL: 41° 54' 34"

WL: 85° 00' 21"

(41-54-34.5 NL; 85-00-21.3 WL NAD 1983)


**MUNN-REESE, INC.**  
Broadcast Engineering Consultants  
COLDWATER, MI 49036

**ASR 1240876 (North Tower)**  
41° 54' 35.9 NL  
85° 00' 22.0 WL  
(NAD 1983)




Ground Elevation = 307.8 m AMSL  
(1010 feet)  
Drawing is not to Scale

**ASR 1240875 (Center Tower)**  
41° 54' 34.5 NL  
85° 00' 21.3 WL  
(NAD 1983)



Ground Elevation = 307.8 m AMSL  
(1010 feet)  
Drawing is not to Scale

**ASR 1240874 (South Tower)**  
41° 54' 33.0 NL  
85° 00' 20.7 WL  
(NAD 1983)




Ground Elevation = 307.8 m AMSL  
(1010 feet)  
Drawing is not to Scale

**WTVB(AM) - Coldwater, MI (1590 kHz)**

Daytime 5.0 kW NDA & Nighttime 1.0 kW DA

**W238CD - Coldwater, MI (95.5 MHz)**

0.250 kW Non-directional FM Translator



X=RESISTANCE MEASUREMENT POINT

RELAYS IN DAY MODE

ST= SAMPLE TRANSFORMER

W238CD FM Shively 6812B-2 Antenna  
& Kintronics™ FMC-1.5 Isocoupler

