

<div style="text-align: center;"> Lihue HI KHJC Minor Change Calvary Chapel Of Twin Falls, Inc. Average Protected F(50-50)= 25.89 km Omni-directional </div>															
REFERENCE	CH#	205A	-	88.9	MHz,	Pwr=	2.5	kW,	HAAT=	127.9	M,	COR=	390	M	DISPLAY DATES
21 59 54.0 N.															DATA 02-13-14
159 25 35.0 W.															SEARCH 02-13-14

CH	CALL	TYPE	ANT	AZI	DIST	LAT	PWR(kW)	INT(km)	PRO(km)	*IN*	*OUT*
CITY		STATE		<--	FILE #	LNG	HAAT(M)	COR(M)	LICENSEE	(Overlap in km)	
205C3 KHJC		LIC _C_		0.0	0.00	21 59 54.0	21.000	96.7	22.6	-109.8*	-74.3*
Lihue		HI		0.0	BLED20001215AAA	159 25 35.0	111	390	Calvary Chapel Of Twin Fal		

Terrain database is USGS 03 SEC , R= 73.215 qualifying spacings or FCC minimum Spacings in KM, M= Margin in KM
Contour distances are on direct line to and from reference station. Reference zone= , Co to 3rd adjacent.
All separation margins (if shown) include rounding
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E), Beamtilt(Y,N,X)
***affixed to 'IN' or 'OUT' values = site inside protected contour.