

# EXHIBIT 15-W-2 Tabulation of Distance to WROU Daytime Allocation Contours

WROU        1240 kHz   Lic        ND1U        Facil. ID 60474        31-Dec-2006  
 VA   PETERSBURG        1.000 kW    1 Tower        0 Augmentations  
 N. Lat: 37 14 01   W. Lon: 77 22 36        0 Measured Cond

Conductivities are from M-3 map unless supplemented by measurements.  
 All distances are in kilometers (US metric curves)  
 All radiations are in mV/m at one kilometer

Bearing	Radiation	Distance to Contours	
		0.500	0.250
0.0	402.3	34.03	46.81
5.0	402.3	34.03	46.81
10.0	402.3	34.03	46.81
15.0	402.3	34.03	46.81
20.0	402.3	34.03	46.81
25.0	402.3	34.03	46.81
30.0	402.3	34.03	46.81
35.0	402.3	34.03	46.81
40.0	402.3	34.03	46.81
45.0	402.3	34.03	46.81
50.0	402.3	34.03	46.81
55.0	402.3	34.03	46.81
60.0	402.3	34.03	46.81
65.0	402.3	34.03	46.81
70.0	402.3	34.03	46.81
75.0	402.3	34.03	46.81
80.0	402.3	34.03	46.81
85.0	402.3	34.03	46.81
90.0	402.3	34.03	56.41
95.0	402.3	34.03	47.92
100.0	402.3	34.03	46.81
105.0	402.3	34.03	46.81
110.0	402.3	34.03	46.81
115.0	402.3	34.03	46.81
120.0	402.3	34.03	46.81
125.0	402.3	34.03	46.81
130.0	402.3	34.03	46.81
135.0	402.3	34.03	46.81
140.0	402.3	34.03	46.81
145.0	402.3	34.03	46.81
150.0	402.3	34.03	46.81
155.0	402.3	34.03	46.81
160.0	402.3	34.03	46.81
165.0	402.3	34.03	46.81
170.0	402.3	34.03	46.81
175.0	402.3	34.03	46.81

EXHIBIT 15-W-2 (cont.)  
 Tabulation of Distance to WROU Daytime Allocation Contours

WROU	1240 kHz	Lic	ND1U	Facil. ID 60474	31-Dec-2006
VA	PETERSBURG		1.000 kW	1 Tower	0 Augmentations
N. Lat:	37 14 01	W. Lon:	77 22 36		0 Measured Cond

Bearing	Radiation	Distance to Contours	
		0.500	0.250
-----	-----	-----	-----
180.0	402.3	34.03	46.81
185.0	402.3	34.03	46.81
190.0	402.3	34.03	46.81
195.0	402.3	34.03	46.81
200.0	402.3	34.03	46.81
205.0	402.3	34.03	46.81
210.0	402.3	34.03	46.81
215.0	402.3	34.03	46.81
220.0	402.3	34.03	46.81
225.0	402.3	34.03	46.81
230.0	402.3	34.03	46.81
235.0	402.3	34.03	46.81
240.0	402.3	34.03	46.81
245.0	402.3	34.03	46.81
250.0	402.3	34.03	46.81
255.0	402.3	34.03	46.81
260.0	402.3	34.03	46.81
265.0	402.3	34.03	46.81
270.0	402.3	34.03	46.81
275.0	402.3	34.03	46.81
280.0	402.3	34.03	46.81
285.0	402.3	34.03	46.81
290.0	402.3	34.03	46.81
295.0	402.3	34.03	46.81
300.0	402.3	34.03	46.81
305.0	402.3	34.03	46.81
310.0	402.3	34.03	46.81
315.0	402.3	34.03	46.81
320.0	402.3	34.03	46.81
325.0	402.3	34.03	46.81
330.0	402.3	34.03	46.81
335.0	402.3	34.03	46.81
340.0	402.3	34.03	46.81
345.0	402.3	34.03	46.81
350.0	402.3	34.03	46.81
355.0	402.3	34.03	46.81