

EXHIBIT B1

REFERENCE	CH#	259D	-	99.7	MHZ,	Pwr=	0.25	kW,	HAAT=	86.2	M,	COR=	153.3	M	DISPLAY	DATES
30 48 57.7 N.						Average	Protected	F(50-50)=	12.0	km					DATA	11-15-17
89 30 22.4 W.						Omni-directional									SEARCH	11-15-17
CH	CALL	TYPE	ANT	AZI.	DIST		LAT.	Pwr (kW)	INT (km)	PRO (km)	*IN*	*OUT*				
CITY		STATE		<--	FILE #		LNG.	HAAT (M)	COR (M)	LICENSEE	(Overlap	in km)				
258C0 WRNO-FM	LIC	CX	204.9	102.07		29 58 57.0	100.000	105.7	72.8	-16.5*	10.0					
New Orleans		LA	24.7	BMLH20090406AGA		89 57 09.0	306	306	Clear Channel Broadcasting							
259C0 WJMI	LIC	C	331.2	177.04		32 12 28.0	100.000	172.3	72.7	-6.3	67.6					
Jackson		MS	150.7	BLH20080123ADK		90 24 50.0	323	408	Alpha Media Licensee Llc							
262C0 WNSL	LIC	CX	24.0	86.55		31 31 37.0	100.000	10.6	74.6	64.9	10.8					
Laurel		MS	204.2	BMLH20060918AHV		89 08 07.0	324	394	Cc Licenses, Llc							
256C1 WKNN-FM	LIC	DEX	115.7	84.13		30 29 09.0	99.000	10.1	72.1	61.3	11.0					
Pascagoula		MS	296.1	BLH20020226ACB		88 42 53.0	300	308	Cc Licenses, Llc							
260C WMXC	LIC	C	94.6	160.75		30 41 20.0	100.000	134.6	90.2	13.7	52.0					
Mobile		AL	275.5	BMLH20130123AEM		87 49 49.0	535	569	Cc Licenses, Llc							
261D W261CU	APP	C	134.1	56.96		30 27 32.3	0.250	1.1	13.4	43.7	42.3					
Poplarville		MS	314.3	BPFT20170410AFL		89 04 44.7		135	John M. Dowdy							

```

Terrain database is FCC NGDC 30 Sec, R= 73.215 qualifying spacings or FCC minimum spacings in KM, M=
Margin In KM
In & Out distances between contours are shown at closest points. Reference Zone= East Zone, Co to 3rd
adjacent.
All separation margins (if shown) include rounding.
Ant Column: (D= DA Standard, Z= DA 73.215, N= Not DA 73.215, _= Omni), Polarization (C,H,V,E),
Beamtilt(Y,N,X)
***affixed to 'IN' or 'OUT' values = site inside restricted contour.
« = Station meets FCC minimum distance spacing for its class.
Reference station has protected zone issue: AM tower

```

MINOR CHANGE APPLICATION
DOWDY & DOWDY PARTNERSHIP
NEW FM TRANSLATOR STATION
CH 259D - 99.7 MHZ - 0.25 KW
POPLARVILLE, MISSISSIPPI
December 2017

EXHIBIT B2

N. Lat. = 30° 48' 57.7" - Protected and Interfering Contour Data
W. Lng. = 89° 30' 22.4" - New FM Translator, Poplarville, Mississippi

HAAT and Distance to Contour - FCC 30 second terrain database									
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5	40-F1	54-F1	100-F1
000	78.3	75.0	0.2500	-6.02	1.000	11.24	38.36	16.14	1.11
010	76.6	76.7	0.2500	-6.02	1.000	11.35	38.80	16.36	1.11
020	81.3	72.0	0.2500	-6.02	1.000	11.03	37.56	15.75	1.11
030	83.0	70.3	0.2500	-6.02	1.000	10.91	37.09	15.52	1.11
040	85.0	68.3	0.2500	-6.02	1.000	10.77	36.54	15.26	1.11
050	83.5	69.8	0.2500	-6.02	1.000	10.88	36.95	15.45	1.11
060	80.3	73.0	0.2500	-6.02	1.000	11.10	37.81	15.87	1.11
070	73.7	79.6	0.2500	-6.02	1.000	11.55	39.55	16.73	1.11
080	64.0	89.3	0.2500	-6.02	1.000	12.18	41.91	17.94	1.11
090	58.0	95.3	0.2500	-6.02	1.000	12.56	43.24	18.65	1.11
100	58.4	94.9	0.2500	-6.02	1.000	12.54	43.15	18.60	1.11
110	55.7	97.6	0.2500	-6.02	1.000	12.71	43.73	18.92	1.11
120	61.1	92.2	0.2500	-6.02	1.000	12.37	42.56	18.29	1.11
130	72.6	80.7	0.2500	-6.02	1.000	11.62	39.83	16.87	1.11
140	67.6	85.7	0.2500	-6.02	1.000	11.95	41.05	17.50	1.11
150	63.1	90.2	0.2500	-6.02	1.000	12.24	42.12	18.05	1.11
160	73.0	80.3	0.2500	-6.02	1.000	11.59	39.73	16.82	1.11
170	76.5	76.8	0.2500	-6.02	1.000	11.36	38.81	16.37	1.11
180	67.8	85.5	0.2500	-6.02	1.000	11.93	41.00	17.47	1.11
190	60.9	92.4	0.2500	-6.02	1.000	12.38	42.62	18.31	1.11
200	59.9	93.4	0.2500	-6.02	1.000	12.45	42.84	18.43	1.11
210	51.4	101.9	0.2500	-6.02	1.000	12.98	44.61	19.40	1.11
220	51.8	101.5	0.2500	-6.02	1.000	12.96	44.53	19.36	1.11
230	53.8	99.5	0.2500	-6.02	1.000	12.83	44.14	19.14	1.11
240	56.5	96.8	0.2500	-6.02	1.000	12.66	43.57	18.83	1.11
250	56.1	97.2	0.2500	-6.02	1.000	12.69	43.66	18.88	1.11
260	58.9	94.4	0.2500	-6.02	1.000	12.51	43.06	18.55	1.11
270	55.3	98.0	0.2500	-6.02	1.000	12.73	43.81	18.96	1.11
280	60.7	92.6	0.2500	-6.02	1.000	12.40	42.66	18.34	1.11
290	66.1	87.2	0.2500	-6.02	1.000	12.04	41.41	17.68	1.11
300	66.0	87.3	0.2500	-6.02	1.000	12.05	41.44	17.70	1.11
310	71.9	81.4	0.2500	-6.02	1.000	11.67	40.01	16.96	1.11
320	77.9	75.4	0.2500	-6.02	1.000	11.26	38.46	16.19	1.11
330	84.9	68.4	0.2500	-6.02	1.000	10.78	36.57	15.27	1.11
340	88.9	64.4	0.2500	-6.02	1.000	10.49	35.44	14.60	1.11
350	83.1	70.2	0.2500	-6.02	1.000	10.91	37.06	15.51	1.11

AMSL= 153.3 M