OWL ENGINEERING & EMC TEST LABS, INC.
CONSULTING COMMUNICATIONS ENGINEERS - EMC TEST LABORATORIES
MINNESOTA OFFICE
5544 Hamline Avenue North, Shoreview, MN 55126
651-784-7445 • Fax 651-784-7541
800-797-1338

PROOF OF PERFORMANCE MEASUREMENT REPORT

FOR RADIO STATION KOBT-LP TOWER

AND RADIO STATION KCNN-AM

PREPARED BY:

GARRETT G. LYSIAK, P.E.

July 15, 2005

OWL ENGINEERING & EMC TEST LABS, INC.
CONSULTING COMMUNICATIONS ENGINEERS - EMC TEST LABORATORIES
MINNESOTA OFFICE
5544 Hamline Avenue North, Shoreview, MN 55126
651-784-7445 • Fax 651-784-7541
800-797-1338

ENGINEERING REPORT

BACKGROUND

This engineering report was prepared on behalf of radio station KOBT-LP to determine the effect of the station transmitting tower in Grand Forks, ND on the directional antenna patterns of radio station KCNN. The radio tower is 2.6 kilometers on a bearing of 292° from the KCNN transmitter site. Therefore, this report presents a description of the initial and post-construction measurements. Figure 1 shows the location of the radio station (KCNN) and the KOBT-LP tower.

KCNN-AM OPERATIONS

KCNN-AM, East Grand Forks, Minnesota is presently authorized operation on a frequency of 1590 kHz with a two (2) tower antenna system with a licensed daytime operating power of 5.0 kilowatts and nighttime operation of 1.0 kilowatts. The coordinates of the KCNN-AM site are as follows:

Latitude North	47° 52' 41"
Longitude West	97° 00' 24"

During the daytime KCNN-AM uses towers #1 and #3 of the antenna system and during night operation towers #2 and #3 are used.

OWL ENGINEERING & EMC TEST LABS, INC.
CONSULTING COMMUNICATIONS ENGINEERS - EMC TEST LABORATORIES
MINNESOTA OFFICE
5544 Hamline Avenue North, Shoreview, MN 55126
651-784-7445 • Fax 651-784-7541
800-797-1338

MEASUREMENT PROCEDURES

Following the initial monitoring point measurements, a series of close-in measurements were obtained to determine the re-radiated field from the KOBL-LP tower to the KCNN-AM facility operating in the daytime mode. These measurements can accurately gauge the emissions from the structure relative to the ambient KCNN-AM field strength. The field from the tower would be inherently non-directional. It can be measured along a single radial in the near field and would encounter no conductivity attenuation. Measurements were obtained from the KOBT-LP tower on a radial projecting outward at a bearing 90 degrees to a line projected from the center tower of the KCNN-AM site. A calibrated line marked at 10-foot intervals was extended from the tower out to 50 feet. A Potomac Field strength meter (FIM) was mounted on a tripod with a 90-degree rotation mark. The FIM was placed over each mark, aligned to the KCNN-AM site for the ambient reading and then rotated 90 degrees to obtain the reading from the KOBT-LP tower. The measured data obtained at the KOBT-LP tower site and the data clearly indicates that the tower is not radiating and shows an attenuation value greater than -30 db which is acceptable.

The KCNN-AM day and night monitor point field strengths were obtained pre and post construction to verify the effectiveness of the methodology. Figure 2 shows the locations of the KCNN-AM day monitoring points. Figure 3 shows the locations of the night KCNN-AM monitoring points.

The directional pattern for the day mode of operation for KCNN-AM is shown in Figure 4 and the night pattern is shown in Figure 5. These figures also show the direction of the KOBT-LP facility in relation to the day and night directional antenna patterns.

OWL ENGINEERING & EMC TEST LABS, INC.
CONSULTING COMMUNICATIONS ENGINEERS - EMC TEST LABORATORIES
MINNESOTA OFFICE
5544 Hamline Avenue North, Shoreview, MN 55126
651-784-7445 • Fax 651-784-7541
800-797-1338

The results of the monitoring point measurements are as follows:

Monitoring Point	Day	Night	Lic Max (Mv/M)
12.5°	260		320
72.5°	240		252
116.8°		1.8	4.7
132.5°	110		111
152.4		13.6	13.8
253°		84	99

Since I was involved in the recent reconstruction of the KCNN-AM facility my records show that the pattern was in compliance with FCC licensed limits before the construction of KOBT-LP.

Summary

This report satisfies the special condition on the Construction Permit (BNPL-20010615AEF) regarding demonstrating that the operation of KCNN-AM is not affected by the operation of KOBT-LP. Based on my measurements and analysis on radio station KCNN-AM It is my professional opinion that the KOBT-LP does not impact the directional antenna system of KCNN-AM.

Respectfully Submitted,

Garrett G. Lysiak

Garrett G. Lysiak, P.E.



FIGURE 1 - SITE MAP



FIGURE 2 - DAY MONITORING POINTS



FIGURE 3 - NIGHT MONITORING POINTS

FIGURE 4 - DAY PATTERN



FIGURE 5 - NIGHT PATTERN