

MINOR CHANGE APPLICATION
HINDLIN BROADCASTING, LLC
W286AX FM TRANSLATOR STATION
CH 277D - 103.3 MHZ - 0.25 KW DA
NORFOLK, VIRGINIA
July 2016

EXHIBIT D

Radio Frequency Radiation Study

This radio frequency radiation study is being conducted to determine whether this proposal is in compliance with OET Bulletin #65, dated August 1997, regarding human exposure to radio frequency radiation in the vicinity of broadcast towers. This study utilizes the appropriate formulas contained in the OET Bulletin.

The proposed W286AX antenna will be mounted with its center of radiation 110 meters (360 feet) above the ground at the tower location and will operate with an effective radiated power of 0.25 kilowatt in the vertical and horizontal planes (circularly polarized). At 2.0 meters above the ground at the base on the tower, the W286AX antenna will contribute 0.00086 mw/cm².¹ Based on exposure limitations for a controlled environment, less than 0.1% of the allowable limit is reached at 2.0 meters above the ground at the base of the tower. For uncontrolled environments, 0.43% of the ANSI limit is reached at 2.0 meters above the ground at the tower base.

Since this level for uncontrolled environments is below the 5.0% limit defined by the Commission in §1.1307(b)(3)(i) of the rules, the proposed W286AX facility is believed to be in

1) This level of signal is delivered 29.0 meters from the base of the tower and is considered a worst case scenario.

compliance with the radio frequency radiation exposure limits as is required by the Federal Communications Commission. Further, HBL will post warning signs in the vicinity of the tower and at the gated access point warning of potential radio frequency radiation hazards at the site. In addition, HBL will reduce the power of the proposed facility or cease operation, in cooperation and coordination with other tower users, as necessary, to protect persons having access to the site, tower or antenna from radio frequency radiation in excess of FCC guidelines.