



2xCA5-FM/CP/RM/CV array

1 antenna skewed 134 deg. w/97.3%power

1 antenna skewed 240 deg. w/2.2%power

Max Gain: 5.3 dBd

power-x: 3.39

Circular Polarization

Horizontal Plane Pattern



Post Office Box 4580 Phone:(541)779-6500  
Medford, OR 97501 (USA) Fax:(541)779-3991  
<http://www.kathrein-scala.com>



2xCA5-FM/CP/RM/CV array

1 antenna skewed 134 deg. w/97.3%power

1 antenna skewed 240 deg. w/2.2%power

Max Gain: 5.3 dBd

power-x: 3.39

Circular Polarization

Horizontal Plane Pattern

Angle	Field	Rel.dB	dBd	PwrMult	Angle	Field	Rel.dB	dBd	PwrMult
0	0.150	-16.45	-11.15	0.08	180	0.423	-7.47	-2.17	0.61
10	0.176	-15.09	-9.79	0.10	190	0.281	-11.01	-5.71	0.27
20	0.198	-14.07	-8.77	0.13	200	0.221	-13.10	-7.80	0.17
30	0.203	-13.84	-8.54	0.14	210	0.248	-12.10	-6.80	0.21
40	0.188	-14.51	-9.21	0.12	220	0.287	-10.85	-5.55	0.28
50	0.173	-15.23	-9.93	0.10	230	0.321	-9.87	-4.57	0.35
60	0.162	-15.81	-10.51	0.09	240	0.344	-9.27	-3.97	0.40
70	0.176	-15.09	-9.79	0.11	250	0.329	-9.66	-4.36	0.37
80	0.281	-11.02	-5.72	0.27	260	0.287	-10.83	-5.53	0.28
90	0.453	-6.89	-1.59	0.69	270	0.236	-12.55	-7.25	0.19
100	0.647	-3.79	1.51	1.42	280	0.210	-13.56	-8.26	0.15
110	0.808	-1.85	3.45	2.21	290	0.197	-14.12	-8.82	0.13
120	0.922	-0.71	4.59	2.88	300	0.198	-14.08	-8.78	0.13
130	0.986	-0.12	5.18	3.29	310	0.205	-13.76	-8.46	0.14
140	0.976	-0.21	5.09	3.23	320	0.204	-13.80	-8.50	0.14
150	0.903	-0.89	4.41	2.76	330	0.188	-14.50	-9.20	0.12
160	0.780	-2.16	3.14	2.06	340	0.168	-15.50	-10.20	0.10
170	0.611	-4.27	1.03	1.27	350	0.152	-16.34	-11.04	0.08