

Radiofrequency Electromagnetic Exposure Analysis

Source	Height AGL(m)	Antenna type	Bays	Horizontal ERP (kw)	Vertical ERP (kw)	Power Density $\mu\text{W}/\text{cm}^2$ at 2 meters AGL				
						within 10 meters distance	% controlled environment limit (1000 $\mu\text{W}/\text{cm}^2$)	Max. PD beyond 10 m	% uncontrolled environment limit (200 $\mu\text{W}/\text{cm}^2$)	Distance to maximum PD (m)
W299CF	48	SHI-6812B-8	3	0.250	0.250	0.25	0.03%	0.33	0.2%	13.6
WVBD	54	(Dipole EPA assumed)	2	0.48	0.48	7.0	0.70%	7.1	3.6%	13.0
W268AZ	42	(Dipole EPA assumed)	1	0.25	0.25	6.3	0.63%	6.3	3.2%	10.8
W221CO (PROPOSED)	42	(Dipole EPA assumed)	1	0.25	0.25	6.3	0.63%	6.3	3.2%	10.8
						7.0	1.99%	7.1	10.0%	13.6

The proposed facility is excluded from environmental processing under 47. C.F.R. Section 1.1306 (i.e., The facility will not have a significant environmental impact and complies with the maximum permissible radiofrequency electromagnetic exposure limits for controlled and uncontrolled environments).

Calculations made using FCC FMModel

In the absence of specific antenna data, the EPA-dipole, single bay model is used.