

Non-Interference Compliance

Regarding Facility id 150318

Channel 286

Description of Exhibit 12 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
19948	BLH19800505AB	WQHQ	85.4	85.4
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				85.4

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **85.4 dBμ**, this makes the proposed translator's worst-case interfering contour **125.4 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **19.6 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population"). Hence, in accordance with 47 C.F.R. § 74.1204(d) and the clarification provided by the FCC in the decision *Re: Living Way Ministries* (FCC 02-244), a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer:	PSI
Antenna Model:	FML
CORAGL:	88 m
Maximum ERP:	0.027 kW
Interfering Contour:	125.4 dBμ
Max Int. Contour Distance:	19.6 m

Adjacent Channel Study **For Station W286BB, Facility_id: 150318**

Co-channel through third adjacent:

Application_id	Facility_id	Prefix	ARN	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Channel	Adj	Dist	Overlap
1204179	28166	BXPH	20070911AAU	WQHQ	CAPSTAR TX LIMITED PARTNERSHIP	B	OCEAN CITY - SALISBU	MD	CP	20	90	284	2	13.7	0.6414
19948	28166	BLH	19800505AB	WQHQ	CUMULUS LICENSING CORP.	B	OCEAN CITY-SALISBUR	MD	LIC	33	189	284	2	13.8	0.6414
1177524	150322	BLFT	20070329AAC	W286AX	PRIORITY RADIO, INC.	D	SALISBURY	MD	LIC	0.03	76	286	0	29.3	0
100442	28167	BLH	19870413KK	WDKZ	CUMULUS LICENSING CORP.	A	SALISBURY	MD	LIC	2.1	130	288	2	40	0
1217321	150268	BLFT	20071031AEX	W286AS	EDGEWATER BROADCASTING INC.	D	SEAFORD	DE	LIC	0.016	96	286	0	47.2	0
143856	40031	BMLH	19900117KE	WSNQ	MARGATE COMMUNICATIONS LIMITED PTNP	A	CAPE MAY COURT HOU	NJ	LIC	3.3	93	288	2	82.9	0

