

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B

Shortspaced Facilities Utilizing Section 73.215

The proposed WMCD antenna location on Channel 261C1 will be shortspaced to WXKT, Channel 261A, Washington, Georgia; WOBB, Channel 262C, Tifton, Georgia; and the proposed allotment of Channel 261A at Gray, Georgia ("Gray"). The detailed spacing information with regard to these shortages is shown on Exhibit B1. Radio Statesboro, Inc., proposes to use the provisions of §73.215 of the Commission's rules to address these shortspaces. The shortages to these facilities complies with §73.215(e) of the Commission's rules. The provisions of §73.215 will be met by specifying less than maximum Class C1 facilities.

Exhibit B2 specifically demonstrates that there will be no prohibited overlap between the proposed WMCD and WXKT, WOBB and Gray. Attached as Exhibits B3 through B8 are the tabulated distances to the protected and interfering contours, along the pertinent arcs, of the proposed WMCD and the authorized WXKT, WOBB and Gray. WXKT and Gray were protected as maximum Class A facilities.¹ The contours of WOBB are based on 100.0 kilowatts at 600 meters HAAT.² Further, attached as Exhibit B9 are the tabulated and protected contours of the proposed facility, in ten degree increments. Again, there is no prohibited overlap between the facilities.

1) WXKT is operating with less than maximum Class A facilities. Its antenna center was raised to bring the antenna system to 100 meters HAAT and its power raised to 6.0 kilowatts for the §73.215 analysis.

2) WOBB is operating with less than maximum Class C height. Its antenna center of radiation was increased to bring the station's HAAT to 600 meters for the §73.215 analysis.

EXHIBIT B1

```

REFERENCE                                     DISPLAY DATES
32 10 17 N                                CLASS = C1          DATA  10-17-03
81 44 04 W                                Current  Spacings      SEARCH 10-21-03
----- Channel 261 - 100.1 MHz -----

```

Call	Channel	Location	Dist	Azi	FCC	Margin
	N. Lat.	W. Lng.	Ant	Power	HAAT	
WMCD.A	APP-N 261C1 32 09 45 Radio Statesboro, Inc.	Rincon 81 45 12 NCX	GA 2.04 75.000 kW BPH-20030702AAE	240.9 299 M	245.0	-242.96
ALLO	RSV 261C1 32 08 35	Rincon 81 42 14	GA 4.26 100.000 kW RM-10388	137.6 299 M	245.0	-240.74
WMCD	LIC 261C2 32 27 19 Radio Statesboro, Inc.	Statesboro 81 46 28 CN	GA 31.70 50.000 kW BLH-19910516KF	353.2 90 M	224.0	-192.30
* RADD	ADD 261A 32 59 11	Gray 83 34 51	GA 195.51 6.000 kW	298.1 100 M	200.0	-4.49
* WXKT	LIC 261A 33 43 50 Southern Broadcasting Comp	Washington 82 43 10 CN	GA 195.91 2.400 kW BLH-7093	332.3 98 M	200.0	-4.09
* RDEL	DEL 261A 33 43 50	Washington 82 43 10	GA 195.91 6.000 kW	332.3 100 M	200.0	-4.09
* WOBB	LIC 262C 31 25 51 Clear Channel Broadcasting	Tifton 83 45 10 C	GA 208.03 100.000 kW BLH-20000907AAS	247.2 304 M	209.0	-0.97
* RDEL	DEL 262C 31 25 49	Tifton 83 45 22	GA 208.34 100.000 kW	247.2 600 M	209.0	-0.66
WXRSM	LIC 263A 32 34 52 Lacom Communications, Inc.	Swainsboro 82 23 14 CN	GA 76.41 3.000 kW BMLH-19921120KD	306.8 91 M	75.0	1.41
WSNTFM	LIC 260A 32 58 23 Radio Station Wsnt, Inc.	Sandersville 82 48 34 CN	GA 134.51 3.000 kW BMLH-19930802KC	311.8 56 M	133.0	1.51
WYFS	LIC-D 208C1 32 04 04 Bible Broadcasting Network	Savannah 81 21 17 DEN	GA 37.63 100.000 kW BLED-19890727KA	107.8 183 M	34.0	3.63
RADD	ADD 262C0 31 25 49	Tifton 83 45 22	GA 208.34 100.000 kW	247.2 450 M	196.0	12.34

* Note: This shortage is addressed under §73.215. See Exhibit B for details.

Graham Brock, Inc. - Broadcast Technical Consultants

WMCD Proposed
Latitude: 32-10-17 N
Longitude: 081-44-04 W
ERP: 85.00 kW
Channel: 261C1
AMSL Height: 330.88 m

WOBB Max.
BLH-20000907AAS
Latitude: 31-25-51 N
Longitude: 083-45-10 W
ERP: 100.00 kW
Channel: 262C
AMSL Height: 708 m

Gray Proposed
Latitude: 32-59-11 N
Longitude: 083-34-51 W
ERP: 6.00 kW
Channel: 261A
AMSL Height: 239.72 m

WXKT Max
BLH-7093
Latitude: 33-43-50 N
Longitude: 082-43-10 W
ERP: 6.00 kW
Channel: 261A
AMSL Height: 242 m

WXKT 60 dBu (50/50)

WXKT 40 dBu (50/10)

GRAY 60 dBu (50/50)

GRAY 40 dBu (50/10)

WOBB 54 dBu (50/10)

WOBB 60 dBu (50/50)

WMCD 60 dBu (50/50)

WMCD 54 dBu (50/10)

WMCD 40 dBu (50/10)

§73.215 ANALYSIS

EXHIBIT B2
AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003



AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B3

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

WOBB - BLH-20000907AAS
Channel = 262C
Max ERP = 100 kW
RCAMSL = 708 M
N. Lat = 31 25 51
W. Lng = 83 45 10

Protected
60 dBu

Interfering
54 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
230.0	084.0000	0292.4	070.0	074.5	100.0000	0598.7	142.8	52.4
231.0	084.0000	0293.0	070.1	074.1	100.0000	0598.7	142.3	52.5
232.0	084.0000	0293.5	070.1	073.6	100.0000	0598.7	141.7	52.6
233.0	084.0000	0293.7	070.1	073.1	100.0000	0599.1	141.3	52.8
234.0	084.0000	0293.7	070.1	072.7	100.0000	0599.1	140.8	52.9
235.0	084.0000	0293.7	070.1	072.2	100.0000	0599.4	140.5	53.0
236.0	084.0000	0293.8	070.1	071.7	100.0000	0599.4	140.1	53.1
237.0	084.0000	0294.2	070.2	071.2	100.0000	0599.5	139.7	53.2
238.0	084.0000	0294.9	070.2	070.8	100.0000	0599.5	139.4	53.3
239.0	084.0000	0295.9	070.3	070.3	100.0000	0599.4	139.0	53.4
240.0	084.0000	0297.2	070.4	069.8	100.0000	0599.4	138.7	53.4
241.0	084.0000	0298.2	070.5	069.3	100.0000	0599.3	138.4	53.5
242.0	084.0000	0298.9	070.5	068.8	100.0000	0599.3	138.1	53.6
243.0	084.0000	0299.2	070.6	068.3	100.0000	0599.2	138.0	53.6
244.0	084.0000	0299.5	070.6	067.8	100.0000	0599.2	137.8	53.7
245.0	084.0000	0299.9	070.6	067.2	100.0000	0599.3	137.7	53.7
246.0	084.0000	0300.2	070.6	066.7	100.0000	0599.3	137.6	53.7
247.0	084.0000	0300.3	070.6	066.2	100.0000	0599.6	137.6	53.7
248.0	084.0000	0300.1	070.6	065.7	100.0000	0599.6	137.6	53.7
249.0	084.0000	0299.8	070.6	065.2	100.0000	0599.8	137.7	53.7
250.0	084.0000	0299.3	070.6	064.7	100.0000	0599.8	137.8	53.7
251.0	084.0000	0298.5	070.5	064.2	100.0000	0600.1	138.0	53.6
252.0	084.0000	0297.5	070.4	063.7	100.0000	0600.1	138.2	53.6
253.0	084.0000	0296.5	070.3	063.2	100.0000	0600.5	138.5	53.5
254.0	084.0000	0295.9	070.3	062.7	100.0000	0600.5	138.7	53.4
255.0	084.0000	0295.7	070.3	062.2	100.0000	0600.8	139.0	53.4
256.0	084.0000	0295.9	070.3	061.7	100.0000	0600.8	139.2	53.3
257.0	084.0000	0296.2	070.3	061.2	100.0000	0600.9	139.5	53.2
258.0	084.0000	0296.5	070.3	060.7	100.0000	0600.9	139.8	53.2
259.0	084.0000	0296.7	070.4	060.2	100.0000	0600.8	140.2	53.1
260.0	084.0000	0296.8	070.4	059.7	100.0000	0600.8	140.6	53.0
261.0	084.0000	0296.9	070.4	059.3	100.0000	0600.6	141.0	52.9
262.0	084.0000	0297.0	070.4	058.8	100.0000	0600.6	141.4	52.8
263.0	084.0000	0297.2	070.4	058.3	100.0000	0600.4	141.9	52.6
264.0	084.0000	0297.5	070.4	057.9	100.0000	0600.4	142.4	52.5
265.0	084.0000	0297.9	070.5	057.4	100.0000	0600.3	142.9	52.4
266.0	084.0000	0298.4	070.5	057.0	100.0000	0600.3	143.4	52.2
267.0	084.0000	0298.8	070.5	056.5	100.0000	0600.3	144.0	52.1
268.0	084.0000	0298.8	070.5	056.1	100.0000	0600.4	144.6	51.9
269.0	084.0000	0299.1	070.5	055.7	100.0000	0600.4	145.2	51.8
270.0	084.0000	0299.3	070.6	055.3	100.0000	0600.7	145.9	51.6

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B4

WOBB - BLH-20000907AAS
Channel = 262C
Max ERP = 100 kW
RCAMSL = 708 M
N. Lat = 31 25 51
W. Lng = 83 45 10

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

Protected
60 dBu

Interfering
54 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
050.0	100.0000	0601.4	091.9	259.4	084.0000	0296.7	122.4	48.8
051.0	100.0000	0601.2	091.9	258.8	084.0000	0296.7	121.7	49.0
052.0	100.0000	0600.9	091.9	258.1	084.0000	0296.5	121.0	49.1
053.0	100.0000	0600.8	091.8	257.4	084.0000	0296.2	120.3	49.2
054.0	100.0000	0600.8	091.8	256.7	084.0000	0296.2	119.7	49.4
055.0	100.0000	0600.7	091.8	255.9	084.0000	0295.9	119.1	49.5
056.0	100.0000	0600.4	091.8	255.2	084.0000	0295.7	118.6	49.6
057.0	100.0000	0600.3	091.8	254.5	084.0000	0295.9	118.1	49.7
058.0	100.0000	0600.4	091.8	253.7	084.0000	0295.9	117.7	49.8
059.0	100.0000	0600.6	091.8	253.0	084.0000	0296.5	117.3	49.9
060.0	100.0000	0600.8	091.8	252.2	084.0000	0297.5	116.9	50.0
061.0	100.0000	0600.9	091.9	251.4	084.0000	0298.5	116.6	50.1
062.0	100.0000	0600.8	091.8	250.6	084.0000	0298.5	116.4	50.2
063.0	100.0000	0600.5	091.8	249.9	084.0000	0299.3	116.2	50.2
064.0	100.0000	0600.1	091.8	249.1	084.0000	0299.8	116.0	50.3
065.0	100.0000	0599.8	091.8	248.3	084.0000	0300.1	116.0	50.3
066.0	100.0000	0599.6	091.8	247.5	084.0000	0300.3	115.9	50.3
067.0	100.0000	0599.3	091.8	246.7	084.0000	0300.3	115.9	50.3
068.0	100.0000	0599.2	091.8	245.9	084.0000	0300.2	116.0	50.3
069.0	100.0000	0599.3	091.8	245.1	084.0000	0299.9	116.1	50.3
070.0	100.0000	0599.4	091.8	244.3	084.0000	0299.5	116.2	50.2
071.0	100.0000	0599.5	091.8	243.5	084.0000	0299.5	116.4	50.2
072.0	100.0000	0599.4	091.8	242.7	084.0000	0299.2	116.7	50.1
073.0	100.0000	0599.1	091.8	242.0	084.0000	0298.9	117.0	50.0
074.0	100.0000	0598.7	091.8	241.2	084.0000	0298.2	117.3	49.9
075.0	100.0000	0598.4	091.8	240.5	084.0000	0297.2	117.8	49.8
076.0	100.0000	0598.2	091.8	239.7	084.0000	0297.2	118.2	49.7
077.0	100.0000	0598.3	091.8	239.0	084.0000	0295.9	118.7	49.6
078.0	100.0000	0598.5	091.8	238.2	084.0000	0294.9	119.2	49.4
079.0	100.0000	0598.1	091.7	237.5	084.0000	0294.9	119.8	49.3
080.0	100.0000	0597.4	091.7	236.8	084.0000	0294.2	120.5	49.2
081.0	100.0000	0596.8	091.7	236.1	084.0000	0293.8	121.2	49.0
082.0	100.0000	0596.4	091.7	235.5	084.0000	0293.7	121.9	48.8
083.0	100.0000	0596.8	091.7	234.8	084.0000	0293.7	122.6	48.7
084.0	100.0000	0597.3	091.7	234.1	084.0000	0293.7	123.4	48.5
085.0	100.0000	0597.8	091.7	233.5	084.0000	0293.7	124.2	48.3
086.0	100.0000	0598.2	091.8	232.9	084.0000	0293.7	125.1	48.2
087.0	100.0000	0598.6	091.8	232.3	084.0000	0293.5	126.0	48.0
088.0	100.0000	0598.9	091.8	231.7	084.0000	0293.5	126.9	47.8
089.0	100.0000	0598.9	091.8	231.1	084.0000	0293.0	127.9	47.6
090.0	100.0000	0599.1	091.8	230.6	084.0000	0293.0	128.9	47.3

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B5

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

Gray, GA Proposed
Channel = 261A
Max ERP = 6 kW
RCAMSL = 239.72 M
N. Lat = 32 59 11
W. Lng = 83 34 51

Protected
60 dBu

Interfering
40 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
280.0	084.0000	0300.8	070.7	126.8	006.0000	0096.0	129.8	30.8
281.0	084.0000	0300.2	070.6	126.3	006.0000	0096.4	129.3	30.9
282.0	084.0000	0299.4	070.6	125.8	006.0000	0096.4	128.8	31.0
283.0	084.0000	0298.5	070.5	125.3	006.0000	0095.7	128.4	31.1
284.0	084.0000	0297.7	070.4	124.8	006.0000	0095.7	128.0	31.1
285.0	084.0000	0296.9	070.4	124.3	006.0000	0094.3	127.6	31.2
286.0	084.0000	0296.1	070.3	123.7	006.0000	0094.3	127.3	31.2
287.0	084.0000	0295.5	070.3	123.2	006.0000	0092.2	126.9	31.2
288.0	084.0000	0295.0	070.2	122.7	006.0000	0092.2	126.6	31.3
289.0	084.0000	0294.7	070.2	122.1	006.0000	0089.8	126.4	31.2
290.0	084.0000	0294.3	070.2	121.6	006.0000	0089.8	126.1	31.3
291.0	084.0000	0293.9	070.1	121.0	006.0000	0087.5	125.9	31.2
292.0	084.0000	0293.7	070.1	120.5	006.0000	0085.5	125.7	31.2
293.0	084.0000	0294.0	070.1	119.9	006.0000	0085.5	125.5	31.2
294.0	084.0000	0294.6	070.2	119.4	006.0000	0083.6	125.3	31.2
295.0	084.0000	0295.2	070.2	118.8	006.0000	0083.6	125.2	31.2
296.0	084.0000	0295.7	070.3	118.2	006.0000	0081.9	125.0	31.2
297.0	084.0000	0296.0	070.3	117.7	006.0000	0081.9	125.0	31.2
298.0	084.0000	0296.1	070.3	117.1	006.0000	0080.6	125.0	31.2
299.0	084.0000	0295.6	070.3	116.6	006.0000	0080.6	125.0	31.2
300.0	084.0000	0294.7	070.2	116.0	006.0000	0080.2	125.1	31.1
301.0	084.0000	0293.7	070.1	115.4	006.0000	0080.7	125.3	31.1
302.0	084.0000	0292.8	070.0	114.9	006.0000	0080.7	125.5	31.1
303.0	084.0000	0292.4	070.0	114.3	006.0000	0081.9	125.7	31.1
304.0	084.0000	0292.7	070.0	113.8	006.0000	0081.9	125.9	31.1
305.0	084.0000	0293.5	070.1	113.2	006.0000	0083.2	126.0	31.1
306.0	084.0000	0294.4	070.2	112.7	006.0000	0083.2	126.2	31.0
307.0	084.0000	0295.3	070.2	112.1	006.0000	0084.6	126.4	31.1
308.0	084.0000	0295.8	070.3	111.6	006.0000	0084.6	126.7	31.0
309.0	084.0000	0295.7	070.3	111.1	006.0000	0086.1	127.0	31.0
310.0	084.0000	0295.2	070.2	110.5	006.0000	0086.1	127.5	30.9
311.0	084.0000	0294.5	070.2	110.0	006.0000	0087.6	127.9	30.9
312.0	084.0000	0293.8	070.1	109.5	006.0000	0087.6	128.4	30.8
313.0	084.0000	0293.3	070.1	109.0	006.0000	0089.0	128.9	30.7
314.0	084.0000	0292.7	070.0	108.5	006.0000	0089.0	129.5	30.6
315.0	084.0000	0292.2	070.0	108.0	006.0000	0090.3	130.0	30.6
316.0	084.0000	0291.7	070.0	107.6	006.0000	0090.3	130.6	30.5
317.0	084.0000	0291.3	069.9	107.1	006.0000	0091.5	131.2	30.4
318.0	084.0000	0291.2	069.9	106.7	006.0000	0091.5	131.9	30.3
319.0	084.0000	0291.2	069.9	106.2	006.0000	0092.6	132.5	30.2
320.0	084.0000	0291.4	069.9	105.8	006.0000	0092.6	133.1	30.1

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B6

GRAY, GA - Proposed
Channel = 261A
Max ERP = 6 kW
RCAMSL = 239.72 M
N. Lat = 32 59 11
W. Lng = 83 34 51

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

Protected
60 dBu

Interfering
40 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
100.0	006.0000	0095.1	027.6	300.9	084.0000	0293.7	169.4	39.6
101.0	006.0000	0095.0	027.6	300.7	084.0000	0293.7	169.3	39.6
102.0	006.0000	0094.2	027.5	300.6	084.0000	0293.7	169.2	39.6
103.0	006.0000	0093.6	027.4	300.4	084.0000	0294.7	169.2	39.6
104.0	006.0000	0093.3	027.4	300.2	084.0000	0294.7	169.1	39.7
105.0	006.0000	0093.2	027.4	300.1	084.0000	0294.7	169.0	39.7
106.0	006.0000	0092.6	027.3	299.9	084.0000	0294.7	168.9	39.7
107.0	006.0000	0091.5	027.1	299.7	084.0000	0294.7	169.0	39.7
108.0	006.0000	0090.3	027.0	299.6	084.0000	0294.7	169.1	39.7
109.0	006.0000	0089.0	026.8	299.4	084.0000	0295.6	169.1	39.7
110.0	006.0000	0087.6	026.6	299.2	084.0000	0295.6	169.3	39.6
111.0	006.0000	0086.1	026.4	299.1	084.0000	0295.6	169.4	39.6
112.0	006.0000	0084.6	026.1	298.9	084.0000	0295.6	169.6	39.6
113.0	006.0000	0083.2	025.9	298.8	084.0000	0295.6	169.7	39.5
114.0	006.0000	0081.9	025.8	298.6	084.0000	0295.6	169.9	39.5
115.0	006.0000	0080.7	025.6	298.4	084.0000	0296.1	170.0	39.5
116.0	006.0000	0080.2	025.5	298.3	084.0000	0296.1	170.1	39.5
117.0	006.0000	0080.6	025.6	298.1	084.0000	0296.1	170.0	39.5
118.0	006.0000	0081.9	025.7	298.0	084.0000	0296.1	169.9	39.5
119.0	006.0000	0083.6	026.0	297.8	084.0000	0296.1	169.6	39.6
120.0	006.0000	0085.5	026.3	297.7	084.0000	0296.1	169.4	39.6
121.0	006.0000	0087.5	026.6	297.5	084.0000	0296.1	169.1	39.7
122.0	006.0000	0089.8	026.9	297.3	084.0000	0296.0	168.8	39.7
123.0	006.0000	0092.2	027.2	297.2	084.0000	0296.0	168.5	39.8
124.0	006.0000	0094.3	027.5	297.0	084.0000	0296.0	168.3	39.8
125.0	006.0000	0095.7	027.7	296.8	084.0000	0296.0	168.2	39.8
126.0	006.0000	0096.4	027.8	296.7	084.0000	0296.0	168.2	39.8
127.0	006.0000	0096.0	027.8	296.5	084.0000	0295.7	168.3	39.8
128.0	006.0000	0094.7	027.6	296.3	084.0000	0295.7	168.6	39.7
129.0	006.0000	0092.8	027.3	296.2	084.0000	0295.7	169.0	39.7
130.0	006.0000	0091.0	027.1	296.1	084.0000	0295.7	169.3	39.6
131.0	006.0000	0089.6	026.9	295.9	084.0000	0295.7	169.6	39.6
132.0	006.0000	0088.7	026.7	295.8	084.0000	0295.7	169.9	39.5
133.0	006.0000	0088.5	026.7	295.7	084.0000	0295.7	170.1	39.5
134.0	006.0000	0088.8	026.7	295.5	084.0000	0295.2	170.2	39.5
135.0	006.0000	0089.1	026.8	295.3	084.0000	0295.2	170.3	39.4
136.0	006.0000	0088.9	026.8	295.2	084.0000	0295.2	170.5	39.4
137.0	006.0000	0087.8	026.6	295.1	084.0000	0295.2	170.8	39.4
138.0	006.0000	0085.9	026.3	295.0	084.0000	0295.2	171.2	39.3
139.0	006.0000	0084.5	026.1	294.9	084.0000	0295.2	171.6	39.2
140.0	006.0000	0084.6	026.1	294.7	084.0000	0295.2	171.8	39.2

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B7

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

WXKT BPH-7093
Channel = 261A
Max ERP = 6 kW
RCAMSL = 242 M
N. Lat = 33 43 50
W. Lng = 82 43 10

Protected
60 dBu

Interfering
40 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
315.0	084.0000	0292.2	070.0	161.0	006.0000	0102.4	130.5	30.9
316.0	084.0000	0291.7	070.0	160.5	006.0000	0102.4	130.0	31.0
317.0	084.0000	0291.3	069.9	160.0	006.0000	0102.4	129.5	31.1
318.0	084.0000	0291.2	069.9	159.5	006.0000	0102.4	129.1	31.1
319.0	084.0000	0291.2	069.9	159.0	006.0000	0102.0	128.6	31.2
320.0	084.0000	0291.4	069.9	158.5	006.0000	0102.0	128.2	31.3
321.0	084.0000	0291.7	070.0	158.0	006.0000	0101.3	127.8	31.4
322.0	084.0000	0292.4	070.0	157.5	006.0000	0100.7	127.4	31.4
323.0	084.0000	0293.2	070.1	156.9	006.0000	0100.7	127.1	31.5
324.0	084.0000	0293.7	070.1	156.4	006.0000	0100.3	126.7	31.5
325.0	084.0000	0293.8	070.1	155.9	006.0000	0100.3	126.5	31.6
326.0	084.0000	0293.5	070.1	155.3	006.0000	0100.1	126.3	31.6
327.0	084.0000	0293.0	070.1	154.8	006.0000	0100.1	126.1	31.6
328.0	084.0000	0292.4	070.0	154.2	006.0000	0100.2	126.0	31.6
329.0	084.0000	0291.8	070.0	153.7	006.0000	0100.2	126.0	31.7
330.0	084.0000	0291.0	069.9	153.1	006.0000	0100.7	125.9	31.7
331.0	084.0000	0290.3	069.9	152.5	006.0000	0100.7	125.9	31.7
332.0	084.0000	0289.9	069.8	152.0	006.0000	0101.3	126.0	31.7
333.0	084.0000	0289.5	069.8	151.4	006.0000	0101.9	126.0	31.7
334.0	084.0000	0289.1	069.8	150.9	006.0000	0101.9	126.1	31.7
335.0	084.0000	0288.5	069.7	150.3	006.0000	0102.3	126.2	31.7
336.0	084.0000	0287.9	069.7	149.8	006.0000	0102.3	126.4	31.6
337.0	084.0000	0287.4	069.6	149.2	006.0000	0102.5	126.6	31.6
338.0	084.0000	0287.1	069.6	148.7	006.0000	0102.5	126.8	31.6
339.0	084.0000	0286.7	069.6	148.2	006.0000	0102.8	127.0	31.5
340.0	084.0000	0286.2	069.5	147.6	006.0000	0102.8	127.3	31.5
341.0	084.0000	0285.5	069.5	147.1	006.0000	0103.1	127.6	31.4
342.0	084.0000	0284.6	069.4	146.6	006.0000	0103.1	128.0	31.4
343.0	084.0000	0283.7	069.3	146.1	006.0000	0103.3	128.4	31.3
344.0	084.0000	0282.8	069.2	145.6	006.0000	0103.3	128.8	31.2
345.0	084.0000	0281.9	069.2	145.1	006.0000	0103.6	129.3	31.1
346.0	084.0000	0281.4	069.1	144.6	006.0000	0103.6	129.8	31.1
347.0	084.0000	0281.1	069.1	144.1	006.0000	0104.2	130.2	31.0
348.0	084.0000	0281.1	069.1	143.6	006.0000	0104.2	130.7	30.9
349.0	084.0000	0281.4	069.1	143.1	006.0000	0105.1	131.2	30.8
350.0	084.0000	0281.7	069.2	142.6	006.0000	0105.1	131.7	30.7
351.0	084.0000	0282.1	069.2	142.1	006.0000	0106.4	132.3	30.7
352.0	084.0000	0282.5	069.2	141.7	006.0000	0106.4	132.8	30.6
353.0	084.0000	0283.0	069.3	141.2	006.0000	0107.7	133.4	30.5
354.0	084.0000	0283.7	069.3	140.8	006.0000	0107.7	134.0	30.4
355.0	084.0000	0284.5	069.4	140.3	006.0000	0109.1	134.6	30.3

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B8

WXKT - BPH-7093
Channel = 261A
Max ERP = 6 kW
RCAMSL = 242 M
N. Lat = 33 43 50
W. Lng = 82 43 10

WMCD - Proposed
Channel = 261C1
Max ERP = 84 kW
RCAMSL = 330.88 M
N. Lat = 32 10 17
W. Lng = 81 44 04

Protected
60 dBu

Interfering
40 dBu

30 Second terrain database

Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Azimuth (degrees)	ERP (kW)	HAAT (m)	Dist (km)	Actual (dBu)
132.0	006.0000	0105.0	028.9	335.6	084.0000	0287.9	169.0	39.5
133.0	006.0000	0106.3	029.1	335.5	084.0000	0288.5	168.7	39.6
134.0	006.0000	0107.7	029.3	335.3	084.0000	0288.5	168.3	39.7
135.0	006.0000	0109.0	029.4	335.2	084.0000	0288.5	168.0	39.7
136.0	006.0000	0110.0	029.6	335.0	084.0000	0288.5	167.7	39.8
137.0	006.0000	0110.6	029.6	334.9	084.0000	0288.5	167.5	39.8
138.0	006.0000	0110.6	029.7	334.7	084.0000	0288.5	167.3	39.8
139.0	006.0000	0110.1	029.6	334.5	084.0000	0288.5	167.3	39.9
140.0	006.0000	0109.1	029.5	334.3	084.0000	0289.1	167.2	39.9
141.0	006.0000	0107.7	029.3	334.2	084.0000	0289.1	167.3	39.9
142.0	006.0000	0106.4	029.1	334.0	084.0000	0289.1	167.3	39.8
143.0	006.0000	0105.1	029.0	333.8	084.0000	0289.1	167.4	39.8
144.0	006.0000	0104.2	028.8	333.6	084.0000	0289.1	167.4	39.8
145.0	006.0000	0103.6	028.8	333.4	084.0000	0289.5	167.4	39.8
146.0	006.0000	0103.3	028.7	333.3	084.0000	0289.5	167.4	39.8
147.0	006.0000	0103.1	028.7	333.1	084.0000	0289.5	167.4	39.8
148.0	006.0000	0102.8	028.7	332.9	084.0000	0289.5	167.4	39.8
149.0	006.0000	0102.5	028.6	332.8	084.0000	0289.5	167.4	39.8
150.0	006.0000	0102.3	028.6	332.6	084.0000	0289.5	167.4	39.8
151.0	006.0000	0101.9	028.5	332.4	084.0000	0289.9	167.4	39.8
152.0	006.0000	0101.3	028.5	332.3	084.0000	0289.9	167.5	39.8
153.0	006.0000	0100.7	028.4	332.1	084.0000	0289.9	167.6	39.8
154.0	006.0000	0100.2	028.3	331.9	084.0000	0289.9	167.7	39.8
155.0	006.0000	0100.1	028.3	331.8	084.0000	0289.9	167.7	39.8
156.0	006.0000	0100.3	028.3	331.6	084.0000	0289.9	167.7	39.8
157.0	006.0000	0100.7	028.4	331.4	084.0000	0290.3	167.7	39.8
158.0	006.0000	0101.3	028.5	331.2	084.0000	0290.3	167.7	39.8
159.0	006.0000	0102.0	028.6	331.1	084.0000	0290.3	167.7	39.8
160.0	006.0000	0102.4	028.6	330.9	084.0000	0290.3	167.7	39.8
161.0	006.0000	0102.4	028.6	330.7	084.0000	0290.3	167.8	39.8
162.0	006.0000	0102.3	028.6	330.6	084.0000	0290.3	167.9	39.8
163.0	006.0000	0102.4	028.6	330.4	084.0000	0291.0	168.0	39.8
164.0	006.0000	0103.1	028.7	330.2	084.0000	0291.0	168.0	39.8
165.0	006.0000	0103.8	028.8	330.1	084.0000	0291.0	168.0	39.8
166.0	006.0000	0104.3	028.9	329.9	084.0000	0291.0	168.1	39.7
167.0	006.0000	0104.6	028.9	329.7	084.0000	0291.0	168.2	39.7
168.0	006.0000	0104.7	028.9	329.6	084.0000	0291.0	168.4	39.7
169.0	006.0000	0104.6	028.9	329.4	084.0000	0291.8	168.6	39.7
170.0	006.0000	0104.5	028.9	329.3	084.0000	0291.8	168.8	39.7
171.0	006.0000	0104.3	028.9	329.1	084.0000	0291.8	169.0	39.6
172.0	006.0000	0103.9	028.8	328.9	084.0000	0291.8	169.2	39.6

AMEND BPH-20030702AAE
RADIO STATESBORO, INC.
WMCD (FM) RADIO STATION
CH 261C1 - 100.1 MHZ - 84.0 KW
RINCON, GEORGIA
October 2003

EXHIBIT B9

Predicted contours:

N. Lat. = 32 10 17 - Tabulated Protected and Interfering Contours
W. Lng. = 81 44 04 - WMCD Radio Station - Rincon, Georgia

HAAT and Distance to Contour - FCC Method - 30 Arc Second terrain database									
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5	40-F1	54-F1	100-F1
000	41.7	289.2	84.0000	19.24	1.000	69.76	166.46	101.55	9.50
010	38.8	292.0	84.0000	19.24	1.000	69.99	166.74	101.83	9.55
020	34.8	296.1	84.0000	19.24	1.000	70.31	167.15	102.23	9.62
030	31.0	299.9	84.0000	19.24	1.000	70.61	167.55	102.60	9.67
040	30.5	300.4	84.0000	19.24	1.000	70.65	167.60	102.64	9.68
050	30.5	300.4	84.0000	19.24	1.000	70.65	167.60	102.64	9.68
060	28.2	302.7	84.0000	19.24	1.000	70.82	167.85	102.87	9.72
070	27.1	303.8	84.0000	19.24	1.000	70.91	167.97	102.97	9.73
080	28.1	302.7	84.0000	19.24	1.000	70.83	167.86	102.87	9.72
090	27.6	303.3	84.0000	19.24	1.000	70.87	167.92	102.93	9.73
100	29.7	301.1	84.0000	19.24	1.000	70.71	167.68	102.72	9.69
110	26.7	304.1	84.0000	19.24	1.000	70.93	168.01	103.01	9.74
120	25.1	305.7	84.0000	19.24	1.000	71.05	168.19	103.16	9.76
130	23.2	307.7	84.0000	19.24	1.000	71.20	168.42	103.36	9.79
140	20.9	310.0	84.0000	19.24	1.000	71.37	168.70	103.59	9.82
150	17.4	313.5	84.0000	19.24	1.000	71.63	169.13	103.96	9.87
160	18.8	312.1	84.0000	19.24	1.000	71.52	168.95	103.80	9.85
170	21.7	309.1	84.0000	19.24	1.000	71.31	168.59	103.50	9.81
180	23.7	307.2	84.0000	19.24	1.000	71.16	168.36	103.31	9.78
190	26.5	304.3	84.0000	19.24	1.000	70.95	168.04	103.03	9.74
200	29.7	301.2	84.0000	19.24	1.000	70.71	167.69	102.73	9.69
210	33.6	297.3	84.0000	19.24	1.000	70.41	167.27	102.34	9.63
220	35.7	295.2	84.0000	19.24	1.000	70.24	167.05	102.13	9.60
230	38.5	292.4	84.0000	19.24	1.000	70.02	166.77	101.86	9.56
240	33.7	297.2	84.0000	19.24	1.000	70.40	167.26	102.33	9.63
250	31.6	299.3	84.0000	19.24	1.000	70.56	167.48	102.53	9.66
260	34.1	296.8	84.0000	19.24	1.000	70.37	167.22	102.29	9.63
270	31.6	299.3	84.0000	19.24	1.000	70.56	167.48	102.54	9.67
280	30.1	300.8	84.0000	19.24	1.000	70.68	167.64	102.68	9.69
290	36.6	294.3	84.0000	19.24	1.000	70.17	166.96	102.05	9.59
300	36.1	294.7	84.0000	19.24	1.000	70.21	167.01	102.09	9.59
310	35.6	295.2	84.0000	19.24	1.000	70.25	167.06	102.14	9.60
320	39.5	291.4	84.0000	19.24	1.000	69.94	166.67	101.76	9.54
330	39.8	291.0	84.0000	19.24	1.000	69.91	166.64	101.73	9.53
340	44.7	286.2	84.0000	19.24	1.000	69.52	166.18	101.26	9.46
350	49.2	281.7	84.0000	19.24	1.000	69.15	165.76	100.81	9.38

AMSL= 330.88 M