

TECHNICAL EXHIBIT
CONCERNING HUMAN EXPOSURE TO RF ELECTROMAGNETIC ENERGY
PREPARED FOR
STATION WTJR-DT
QUINCY, ILLINOIS
CH 32 43 KW 308 M


Technical Statement

The proposed facilities were evaluated in terms of potential radio frequency (RF) energy exposure at ground level to workers and the general public. The radiation center for the proposed DTV antenna is located 268 meters above ground level. The maximum DTV ERP is 43 kW (horizontal polarization). A “worst-case” vertical plane relative field value of 0.1 (for angles below 60 degrees downward) was presumed for the antenna's downward radiation (see Figure 1). The calculated power density at a point 2 meters above ground level is 0.0002 mW/cm^2 . This is 0.05% of the FCC's recommended limit of 0.39 mW/cm^2 for channel 32 for an “uncontrolled” environment. Therefore, based on the responsibility threshold of 5%, the proposal will comply with the RF emission rules.

Access to the transmitting site will be restricted and appropriately marked with RFR warning signs. Furthermore, in the event that workers or other authorized personnel enter the restricted area or climb the tower, appropriate measures will be taken to assure worker safety with respect to radio frequency radiation exposure. Such measures include reducing the average exposure by spreading out the work over a longer period of time, wearing “accepted” RFR protective clothing and/or RFR exposure.

Finally, it is noted that this technical exhibit only addresses the potential for radio frequency electromagnetic field exposure. All other aspects of the

environmental processing analysis will be or already has been provided to the FCC by the tower owner as part of the tower registration process.




Jerome J. Manarchuck

du Treil, Lundin & Rackley, Inc.
201 Fletcher Avenue
Sarasota, Florida 34237-6019
(941) 329-6000
JERRY@DLR.COM

May 23, 2008

ELEVATION PATTERN

Type:	ATW15H2H		Channel:	32
Directivity:	Numeric	dBd	Location:	
Main Lobe:	15.00	11.76	Beam Tilt:	-0.50
Horizontal:	14.16	11.51	Polarization:	Horizontal



Preliminary, subject to final design and review.

TABULATED DATA FOR ELEVATION PATTERN

Type: ATW15H2H
PolarizationHorizontal

ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB	ANGLEFIELD	dB
5.00	0.304	-10.36	-6.75	0.259	-11.73	-27.00	0.077	-22.33	-50.50
4.75	0.303	-10.37	-7.00	0.228	-12.84	-27.50	0.065	-23.74	-51.00
4.50	0.292	-10.71	-7.25	0.197	-14.11	-28.00	0.050	-26.11	-51.50
4.25	0.271	-11.34	-7.50	0.168	-15.49	-28.50	0.038	-28.40	-52.00
4.00	0.240	-12.40	-7.75	0.145	-16.77	-29.00	0.039	-28.18	-52.50
3.75	0.202	-13.89	-8.00	0.133	-17.56	-29.50	0.051	-25.93	-53.00
3.50	0.161	-15.86	-8.25	0.131	-17.65	-30.00	0.063	-24.01	-53.50
3.25	0.129	-17.79	-8.50	0.140	-17.11	-30.50	0.072	-22.91	-54.00
3.00	0.132	-17.59	-8.75	0.153	-16.31	-31.00	0.074	-22.62	-54.50
2.75	0.176	-15.09	-9.00	0.168	-15.52	-31.50	0.070	-23.16	-55.00
2.50	0.247	-12.15	-9.25	0.180	-14.89	-32.00	0.059	-24.58	-55.50
2.25	0.330	-9.63	-9.50	0.189	-14.49	-32.50	0.046	-26.84	-56.00
2.00	0.419	-7.56	-9.75	0.193	-14.29	-33.00	0.035	-29.12	-56.50
1.75	0.509	-5.87	-10.00	0.191	-14.38	-33.50	0.035	-29.24	-57.00
1.50	0.597	-4.47	-10.50	0.174	-15.19	-34.00	0.045	-26.94	-57.50
1.25	0.682	-3.32	-11.00	0.142	-16.98	-34.50	0.057	-24.88	-58.00
1.00	0.760	-2.38	-11.50	0.106	-19.53	-35.00	0.067	-23.54	-58.50
0.75	0.830	-1.62	-12.00	0.084	-21.57	-35.50	0.070	-23.10	-59.00
0.50	0.889	-1.02	-12.50	0.092	-20.72	-36.00	0.069	-23.29	-59.50
0.25	0.937	-0.57	-13.00	0.115	-18.82	-36.50	0.061	-24.29	-60.00
0.00	0.972	-0.25	-13.50	0.132	-17.59	-37.00	0.050	-26.11	-60.50
-0.25	0.993	-0.06	-14.00	0.137	-17.30	-37.50	0.037	-28.64	-61.00
-0.50	1.000	0.00	-14.50	0.127	-17.96	-38.00	0.031	-30.31	-61.50
-0.75	0.993	-0.06	-15.00	0.105	-19.62	-38.50	0.035	-29.12	-62.00
-1.00	0.972	-0.24	-15.50	0.079	-22.10	-39.00	0.046	-26.74	-62.50
-1.25	0.939	-0.55	-16.00	0.062	-24.22	-39.50	0.057	-24.88	-63.00
-1.50	0.893	-0.98	-16.50	0.069	-23.29	-40.00	0.065	-23.74	-63.50
-1.75	0.837	-1.55	-17.00	0.087	-21.21	-40.50	0.068	-23.35	-64.00
-2.00	0.773	-2.24	-17.50	0.103	-19.74	-41.00	0.067	-23.54	-64.50
-2.25	0.701	-3.09	-18.00	0.109	-19.25	-41.50	0.059	-24.58	-65.00
-2.50	0.627	-4.06	-18.50	0.103	-19.74	-42.00	0.049	-26.20	-65.50
-2.75	0.551	-5.18	-19.00	0.087	-21.21	-42.50	0.038	-28.52	-66.00
-3.00	0.478	-6.41	-19.50	0.066	-23.61	-43.00	0.030	-30.60	-66.50
-3.25	0.411	-7.72	-20.00	0.051	-25.85	-43.50	0.031	-30.17	-67.00
-3.50	0.356	-8.98	-20.50	0.053	-25.51	-44.00	0.041	-27.85	-67.50
-3.75	0.315	-10.03	-21.00	0.068	-23.35	-44.50	0.052	-25.68	-68.00
-4.00	0.293	-10.68	-21.50	0.083	-21.62	-45.00	0.061	-24.29	-68.50
-4.25	0.287	-10.84	-22.00	0.091	-20.87	-45.50	0.067	-23.54	-69.00
-4.50	0.296	-10.59	-22.50	0.090	-20.96	-46.00	0.068	-23.35	-69.50
-4.75	0.309	-10.20	-23.00	0.079	-22.10	-46.50	0.066	-23.68	-70.00
-5.00	0.323	-9.83	-23.50	0.063	-24.08	-47.00	0.059	-24.66	-70.50
-5.25	0.333	-9.55	-24.00	0.047	-26.56	-47.50	0.049	-26.20	-71.00
-5.50	0.338	-9.42	-24.50	0.042	-27.43	-48.00	0.038	-28.40	-71.50
-5.75	0.336	-9.47	-25.00	0.053	-25.60	-48.50	0.029	-30.75	-72.00
-6.00	0.326	-9.75	-25.50	0.068	-23.41	-49.00	0.029	-30.90	-72.50
-6.25	0.309	-10.20	-26.00	0.078	-22.21	-49.50	0.036	-28.87	-73.00
-6.50	0.286	-10.87	-26.50	0.081	-21.83	-50.00	0.047	-26.56	-73.50

Preliminary, subject to final design and review.