

MARCH 2002

EXHIBIT E-3.02-D

Page 1 of 1

PROPOSED KTXV

JEFFREY N. EUSTIS

890 kHz 2 kW/0.008 kW DA-2

FRANKSTON, TEXAS

STANDARD HORIZONTAL PLANE PATTERN

Trw.No.	Field	Phasing	Spacing	Azimuth	Height
1	1.000	+0.0	0.0	0.0	63.5
2	0.400	+12.0	255.0	24.0	63.5
3	0.280	+136.0	254.4	4.8	63.5
4	0.700	+124.0	85.0	284.0	63.5
5	0.420	+131.0	273.3	225.6	63.5
6	0.600	+7.0	240.0	208.0	63.5
Theo. RMS= 397.14 mV/m/km RSS= 580.82 Q= 14.52					

STANDARD HORIZONTAL PLANE PATTERN

Azimuth	mV/m/km	Azimuth	mV/m/km
0	75.0	180	113.8
5	108.1	185	148.4
10	149.0	190	171.0
15	191.4	195	179.8
20	229.8	200	175.5
25	259.4	205	160.4
30	275.9	210	138.0
35	276.5	215	112.2
40	259.6	220	86.7
45	225.5	225	64.8
50	177.6	230	48.4
55	123.9	235	37.8
60	81.3	240	32.3
65	75.8	245	30.1
70	96.4	250	28.2
75	121.7	255	26.1
80	172.9	260	38.8
85	282.3	265	78.5
90	451.5	270	139.2
95	660.9	275	212.6
100	881.7	280	287.5
105	1080.7	285	350.8
110	1225.4	290	390.3
115	1291.2	295	398.3
120	1266.5	300	373.6
125	1155.6	305	322.2
130	977.9	310	255.6
135	762.3	315	187.1
140	541.6	320	128.4
145	344.8	325	87.0
150	192.4	330	64.1
155	93.3	335	54.9
160	42.1	340	52.4
165	17.6	345	51.3
170	32.3	350	50.6
175	72.2	355	55.8