

MINOR CHANGE APPLICATION
SEVEN RANGES RADIO CO., INC.
WVVV (FM) RADIO STATION
CH 245A - 96.9 MHZ - 3.5 KW
WILLIAMSTOWN, WEST VIRGINIA
August 2012

EXHIBIT #6

Radio Frequency Assessment

A study has been made to determine whether this proposal is in compliance with 47 C.F.R. §1.1307 of the Commission's rules and with OET Bulletin #65, dated August 1997 ("Bulletin"), regarding human exposure to radio frequency radiation in the vicinity of broadcast towers. This study considers all nearby contributing stations, specifically WDMX¹, and utilizes the appropriate formulas contained in the OET Bulletin.²

The proposed WVVV antenna system will be mounted with its center of radiation 56.2 meters (184.4 feet) above the ground at the tower location and operate with an effective radiated power of 3.5 kilowatts in the horizontal and vertical planes (circularly polarized). At 2.0 meters, the height of an average person, above the ground at the base of the tower, the WVVV antenna system will contribute 0.0479 mw/cm².³ Based on exposure limitations for controlled environments, 4.8% of the allowable limit is reached at 2.0 meters above the ground at the base of the tower. For uncontrolled environments, 24.0% of the limit is reached at 2.0 meters above the ground at the base of the tower.

-
- 1) WDMX is located on an adjacent tower 350 feet from the proposed WVVV and is considered co-located for this RF study.
 - 2) The contributions of all the FM facilities were calculated using the FM Model program. A single bay EPA dipole antenna was used for calculation purposes. In cases where the number of bays of the antenna was known, this data was used in the FMModel program.
 - 3) This level of field occurs at 15.0 meters out from the base of the tower and is considered worst case.

The authorized WDMX antenna system is mounted with its center of radiation 55.0 meters (180.4 feet) above the ground at the tower location and operates with an effective radiated power of 1.65 kilowatts in the horizontal and vertical planes (circularly polarized). At 2.0 meters, the height of an average person, above the ground at the base of the tower, the WDMX antenna system contribute 0.0236 mw/cm^2 .⁴ Based on exposure limitations for controlled environments, 2.4% of the allowable limit is reached at 2.0 meters above the ground at the base of the tower. For uncontrolled environments, 11.8% of the limit is reached at 2.0 meters above the ground at the base of the tower.

Combining the contributions of WVVV and WDMX, a total of 35.8% is reached at 2.0 meters above the ground at the base of the existing tower. Since this level is well below the 100% limit defined by the Commission, the proposed WVVV facility is believed to be in compliance with the radio frequency radiation exposure limits as required by the Federal Communications Commission. Further, SRR will insure warning signs are posted in the vicinity of the tower warning of potential radio frequency radiation hazards at the site. In addition, SRR will reduce the power of the proposed facility or cease operation, in cooperation and coordination with other tower users, as necessary, to protect persons having access to the site, tower or antenna from radio frequency radiation in excess of FCC guidelines.

4) This level of field occurs at 13.0 meters out from the base of the tower and is considered worst case.

RF WORKSHEET #1 - FM (including translators & boosters)

PLEASE COPY BEFORE USING. THE DETERMINATION OF COMPLIANCE MAY INVOLVE REPEATED CALCULATIONS. IF LOCATED ON A MULTIPLE FM USER TOWER, PLEASE COMPLETE RFWORKSHEET 1A BEFORE PROCEEDING.

EFFECTIVE RADIATION CENTER HEIGHT

Enter proposed "Height of radiation center above ground" OR as listed in line 1 of Worksheet 1A 50.0 m (1)

Is antenna supporting structure located on the roof of a building? (check one) .. Yes No (2)

If line 2 is "yes," enter the building height measured at the base of the antenna supporting structure in line 3

If line 2 is "no," enter "0" in line 3 0 m (3)

Subtract line (3) from line (1) 50.0 m (4)

Subtract the value 2.0 from line (4) 48.0 m (5)

TOTAL EFFECTIVE RADIATED POWER

(If "beam tilt" is utilized, list maximum values)

List Effective Radiated Power in the Horizontal Plane kW (6)

List Effective Radiated Power in the Vertical Plane kW (7)

Add Lines (6) and (7) OR list value from Line 2 in Worksheet 1A 11.3 kW (8)

PERCENTAGE OF FCC RF LIMIT(S) FOR MAXIMUM PERMISSIBLE EXPOSURE

Multiply Line (8) by 33.41 344.123 (9)

Multiply the value listed in line (5) by itself 2,304 (10)

Divide Line (9) by Line (10) 0.1493 (11)

Multiply Line (11) by (100) 14.9 % (12)

DETERMINATION OF COMPLIANCE WITH CONTROLLED/OCCUPATIONAL LIMIT

Does Line (12) exceed 100% Yes No (13)

IF YOU ANSWERED "YES" IN LINE (13), THE WORKSHEETS MAY NOT BE USED IN THIS CASE.*

IF YOU ANSWERED "NO" IN LINE (13), THEN THE SITE SHOULD COMPLY WITH THE FCC'S CONTROLLED/OCCUPATIONAL RF EXPOSURE LIMITS FOR GROUND LEVEL EXPOSURE.

CONTINUE

*In this case, you may need to prepare an Environmental Assessment. See Instructions for Section III-C of FCC Form 301.

EXHIBIT #6A
MINOR CHANGE APPLICATION
SEVEN RANGES RADIO CO., INC.
WVVV (FM) RADIO STATION
CH 245A - 96.9 MHZ - 3.5 KW
WILLIAMSTOWN, WEST VIRGINIA
August 2012

RF WORKSHEET #1 - FM (continued)

DETERMINATION OF COMPLIANCE WITH THE UNCONTROLLED/GENERAL POPULATION LIMIT

Does Line (12) exceed 20% Yes No (14)

IF YOU ANSWERED "NO" IN LINE (14), THEN THE SITE SHOULD COMPLY WITH THE FCC'S UNCONTROLLED/GENERAL POPULATION RF EXPOSURE LIMITS FOR GROUND LEVEL EXPOSURE. NO FURTHER STUDY REQUIRED.

IF YOU ANSWERED "YES" IN LINE (14), CONTINUE.

Rooftop with restricted access.

If you answered "yes" in Line (14) and "yes" in Line (2) (indicating that the tower is located on the roof of a building), and the general public is not allowed access to the rooftop level, repeat lines 5 through 12, entering the value in Line (1) directly in Line (4). (If Multiple FM Use Tower, recalculations should be in accordance with instructions on Worksheet #1A.) **Otherwise, go to the next section.**

Upon recalculation, Does Line (12) exceed 20% Yes No (15)

IF YOU ANSWERED "YES" IN LINE (15), THE WORKSHEETS MAY NOT BE USED IN THIS CASE. *

IF YOU ANSWERED "NO" IN LINE (15), THEN THE AREA AT GROUND LEVEL SHOULD COMPLY WITH THE FCC'S UNCONTROLLED/GENERAL POPULATION EXPOSURE LIMIT. NO FURTHER STUDY REQUIRED.

Access to base of tower restricted by fencing.

If the tower is not located on the roof of a building, is the base of the tower surrounded by fencing or other restrictive barrier and are appropriate warning signs posted on the fence that adequately detail the nature of the RF exposure environment contained therein? Yes No (16)

IF YOU ANSWERED "NO" IN LINE (16), THE WORKSHEETS MAY NOT BE USED IN THIS CASE. *

If you answered "yes" in line (16), what is the distance from the base of the tower to the fence or barrier at its nearest point _____ m (17)
Multiply Line (9) (as calculated previously) by 5 _____ (18)
Subtract Line (10) (as calculated previously) from Line (18) _____ (19)
Take the square root of Line (19) _____ m (20)
Is Line (20) less than or equal to Line (17) Yes No (21)

IF YOU ANSWERED "YES" IN LINE (21), THEN THE RF FIELD OUTSIDE THE FENCE COMPLIES WITH THE FCC'S UNCONTROLLED/GENERAL POPULATION EXPOSURE LIMIT. NO FURTHER STUDY REQUIRED.

IF YOU ANSWERED "NO" IN LINE (21), THE WORKSHEETS MAY NOT BE USED IN THIS CASE. *

* In this case, you may need to prepare an Environmental Assessment. See Instructions for Section III-C of FCC Form 301.

RF WORKSHEET #1A - Multiple FM User Tower

The procedure below will allow for a “worst-case” determination to be made in situations where several FM stations share a common tower. This determination is based upon the “worst case” assumption that all RF energy is emanating from a single antenna located at the same height (i.e. antenna center of radiation above ground level) as the lowest user on the tower.

Complete this sheet for all call signs.

For each call sign, the total of the Horizontal and the Vertical ERP’s must be used. If “beam tilt” is utilized, list maximum values.

COLUMN 1 CALL SIGN	COLUMN 2 HEIGHT OF ANTENNA RADIATION CENTER ABOVE GROUND LEVEL	COLUMN 3 TOTAL EFFECTIVE RADIATED POWER (HORIZONTAL AND VERTICAL)
WVVV	50.0 meters	7.0 kilowatts
WDMX	55.0 meters	3.3 kilowatts
	meters	kilowatts
	meters	kilowatts
	meters	kilowatts
	meters	kilowatts

List the smallest value in Column 2 50.0 m (1)
 List the total of all values in Column 3 10.3 kW (2)

The value listed in line (1) above must be used in line (1) on Worksheet 1.
 The value listed in line (2) above must be used in line (8) on Worksheet 2.

Now complete worksheet 1 (except for lines 6 and 7).