

Environmental Protection

There are two main factors that need to be addressed in order to make sure that the environment around a proposed facility is protected.

1) Significant affects to the environment.

No physical changes will be made to the existing KLVS facility, therefore there will be no adverse effects on the surrounding environment.

2) Human exposure to excess levels of radiofrequency radiation.

The proposed facility is built using a 6-bay horizontally polarized half-wave spaced antenna.

According to OET 65, "Applicants and licensees should be able to calculate, based on considerations of frequency, power and antenna characteristics the distance from their transmitter where their signal produces an RF field equal to, or greater than, the 5% threshold limit. The applicant or licensee then shares responsibility for compliance in any accessible area or areas within this 5% "contour" where the appropriate limits are found to be exceeded."

As can be seen in Exhibit 32-A, the proposed facility's maximum contribution to RF on the site is $3.6416 \mu\text{W}/\text{cm}^2$ at a distance of 59 meters from the tower, which is 1.82% of the uncontrolled (public) exposure limit.

Therefore, because the proposed facility will not cause an RF field that is equal to or greater than 5% of the $200 \mu\text{W}/\text{cm}^2$ limit for uncontrolled exposure at any point, the proposed facility complies with the requirements of OET 65.

The licensee will fully cooperate with other site users to temporarily reduce power or cease broadcasting, as necessary, to protect workers and others having access to the site from excessive levels of RF Radiation.

Exhibit 32-A
RF Analysis: KLVS Stockton, CA

KLVS
Site type: Proposed
Channel: 297
Class: B
ERP: 8.1kw
Antenna: JAM
 EPA Type 2
 6 bay
 half wave
COR AGL: 34m
Polarization: horizontal

Distance From Tower (m)	KLVS Facility	Total RF (uW/cm ²)	Percent of 200uW/cm ²
0	0.0000	0.00	0.00
1	0.0000	0.00	0.00
2	0.0000	0.00	0.00
3	0.0002	0.00	0.00
4	0.0006	0.00	0.00
5	0.0017	0.00	0.00
6	0.0039	0.00	0.00
7	0.0089	0.01	0.00
8	0.0183	0.02	0.01
9	0.0341	0.03	0.02
10	0.0607	0.06	0.03
11	0.1011	0.10	0.05
12	0.1583	0.16	0.08
13	0.2424	0.24	0.12
14	0.3581	0.36	0.18
15	0.5040	0.50	0.25
16	0.6748	0.67	0.34
17	0.8413	0.84	0.42
18	1.0160	1.02	0.51
19	1.1909	1.19	0.60
20	1.3664	1.37	0.68
21	1.5421	1.54	0.77
22	1.6910	1.69	0.85
23	1.8030	1.80	0.90
24	1.8625	1.86	0.93
25	1.8429	1.84	0.92
26	1.7756	1.78	0.89
27	1.6640	1.66	0.83
28	1.5139	1.51	0.76
29	1.3485	1.35	0.67
30	1.1713	1.17	0.59
31	0.9736	0.97	0.49
32	0.7678	0.77	0.38
33	0.5662	0.57	0.28
34	0.3810	0.38	0.19
35	0.2226	0.22	0.11
36	0.1021	0.10	0.05
37	0.0263	0.03	0.01
38	0.0000	0.00	0.00
39	0.0254	0.03	0.01
40	0.1025	0.10	0.05
41	0.2280	0.23	0.11
42	0.3953	0.40	0.20
43	0.5988	0.60	0.30
44	0.8314	0.83	0.42
45	1.0859	1.09	0.54

Distance From Tower (m)	KLVS Facility	Total RF (uW/cm2)	Percent of 200uW/cm2
46	1.3548	1.35	0.68
47	1.6308	1.63	0.82
48	1.9072	1.91	0.95
49	2.1756	2.18	1.09
50	2.4296	2.43	1.21
51	2.6664	2.67	1.33
52	2.8822	2.88	1.44
53	3.0740	3.07	1.54
54	3.2394	3.24	1.62
55	3.3772	3.38	1.69
56	3.4863	3.49	1.74
57	3.5666	3.57	1.78
58	3.6185	3.62	1.81
59	3.6416	3.64	1.82
60	3.6276	3.63	1.81
61	3.5895	3.59	1.79
62	3.5292	3.53	1.76
63	3.4489	3.45	1.72
64	3.3509	3.35	1.68
65	3.2373	3.24	1.62
66	3.1105	3.11	1.56
67	2.9726	2.97	1.49
68	2.8259	2.83	1.41
69	2.6724	2.67	1.34
70	2.5139	2.51	1.26
71	2.3524	2.35	1.18
72	2.1896	2.19	1.09
73	2.0264	2.03	1.01
74	1.8605	1.86	0.93
75	1.6983	1.70	0.85
76	1.5409	1.54	0.77
77	1.3890	1.39	0.69
78	1.2436	1.24	0.62
79	1.1053	1.11	0.55
80	0.9744	0.97	0.49
81	0.8515	0.85	0.43
82	0.7369	0.74	0.37
83	0.6307	0.63	0.32
84	0.5331	0.53	0.27
85	0.4441	0.44	0.22
86	0.3638	0.36	0.18
87	0.2920	0.29	0.15
88	0.2287	0.23	0.11
89	0.1736	0.17	0.09
90	0.1267	0.13	0.06
91	0.0876	0.09	0.04
92	0.0561	0.06	0.03
93	0.0318	0.03	0.02
94	0.0147	0.01	0.01
95	0.0042	0.00	0.00
96	0.0001	0.00	0.00
97	0.0020	0.00	0.00
98	0.0097	0.01	0.00
99	0.0228	0.02	0.01
100	0.0408	0.04	0.02